



DATE: Sep 24, 2025
QUOTE #:370735-01

BURNET COUNTY
TESSA ROWLAND
220 S PIERCE ST
BURNET, TEXAS 78611-3136

Howell, Jeffrey
512.970.5564

One (1) New Caterpillar Inc Model: CB4.0 Paving and Compaction with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER: HLK049323 SERIAL NUMBER: 064901132 YEAR: 2025 HOURS: 0

LIST PRICE	\$102,962.00
SOURCEWELL DISCOUNT	(\$8,340.00)
ADJUSTED SALES PRICE	\$94,622.00
DEALER PREP AND DELIVERY	\$2,378.00
WARRANTY: STANDARD AND EXTENDED	\$2,560.00
SUBTOTAL	\$99,560.00
HOLT DISCOUNTS	(\$19,184.00)
TOTAL PURCHASE PRICE	\$80,376.00

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
Extended Warranty: CB4.0-60 MO/3000 HR POWERTRAIN + HYDRAULICS + TECH

NOTES

MACHINE SPECIFICATIONS**STOCK NUMBER: HLK049323****SERIAL NUMBER: 064901132****YEAR: 2025****HOURS: 0**

DESCRIPTION	REF.#
CB4.0 03A UTILITY COMPACTOR	562-0800
ENGINE, CAT C1.7T	611-1364
OIL, HYD, STANDARD	574-6039
LIGHTS, WORKING, LED	568-5154
SWITCH, BATTERY DISCONNECT,RED	565-3671
PUMP, PROPEL, STANDARD	367-6593
SEAT, WITH SAFETY SWITCH	573-5962
SUPPORT, SLIDING FOR SEAT	364-2279
ROPS, FOLDABLE, LOCKABLE	576-8242
TRAVEL CONTROL,DUAL LEVER	367-6538
PRODUCT LINK, CELLULAR PL243	602-4197
GUARDS, BUMPER	569-8093
DRUM SCRAPER, FOLDING	562-0851
INSTRUCTIONS, ANSI	574-6030
CONTROL, TRACTION	562-0808
LIGHT, BEACON	575-4457
MATS, COCOA	457-9154
FREEZE PROTECTION	574-6076
MIRROR, REAR VIEW	660-5143
TRAVEL CONTROL, STD	569-6569
SEAT BELT, 3"	542-6995
SERIALIZED TECHNICAL MEDIA KIT	421-8926
LANE 3 ORDER	0P-9003
PACKING, LAST MILE PROGRAM	0P-4299

STANDARD EQUIPMENT

POWERTRAIN

CAT C1.7T diesel engine
-Turbocharged, EPA tier 4 final and EU stage V certified engine with DOC/DPF aftertreatment
-Gross power per ISO 14396 36kW (48.3 hp) @2800 RPM
-Liquid cooled, direct injection
Aftercooler, air to air (ATAAC)
Fuel filter/water separator/manual priming pump
Dual element air cleaner with dust

ejection
3 Engine speeds - idle, med, high
Engine belt guard
Programable auto Idle Shutdown
Aluminum bar plate cooling system
Hydrostatic transmission
Auto warmup cycle
Hydraulic on demand cooling fan
Service and parking brakes - spring applied hydraulically released

ELECTRICAL

Engine start switch with auto preheat
12-volt starting and charging system
85 ampere alternator
Maintenance free battery, 750 CCA
Isolated and cooled battery compartment
Backup alarm and forward facing warning horn

Product Link ready
Beacon ready
Diagnostic connector
CAT ET Compatible
Labeled and sealed electrical connectors
LED work lights (2 front, 2 rear)

OPERATOR ENVIRONMENT

Gauge Cluster:
-Water level gauge
-Fuel level gauge
-Hour meter
-Engine coolant temperature gauge
-Faults
Simple rocker switches
Emergency stop switch
Operator warning system indicators:
-Water in fuel indicator
-Parking brake engaged
-Operator out of seat
-Hydraulic oil temperature high
-Hydraulic oil restriction
-Engine oil low pressure
-Electrical system voltage low
-Low fuel

-Engine preheat
-Engine emission system
-High/low vibe frequency
-Beacon status
Lockable, vandalism guard for instrument panel
Travel control, single lever
High Vis Orange retractable seatbelt, 76mm (3")
2 platform handrails/single guardrail
Steering wheel spinner
12-volt power point
ROPS
Sealed storage compartment
Isolated operator platform
Vibration reducing, diesel resistant rubber floor mat

DRUMS

Two smooth drums: 1300 mm (51") wide x 800 mm (31.5") diameter
Single amplitude with dual frequency vibratory system

vibration
Pressurized drum watering system with selectable continuous or intermittent flow

Automatic vibration control to prevent vibration in neutral
Selection of front drum or both drum

4 nozzle spray bars
Triple spray system filtration

FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection

to -37C (-35F)

OTHER STANDARD EQUIPMENT

Lockable engine enclosure with safety hold open batch
Lockable external fuel fill
Sight gauges:
-Hydraulic tank level
-Engine coolant
Lockable hydraulic tank cap
Articulated frame with safety lock
3 point hitch
4 transport tie-down and 4 lift points
81L (21 gal) fuel tank capacity

300L (79 gal) water tank capacity
6 quick connect hydraulic pressure test ports + 1 SOS port
Caterpillar o-ring face-seals couplings
Offset hitch with 50 mm (2") of manual adjustment
Ecology drains:
-Hydraulic Tank
-Radiator
-Engine Oil