



Hx520 SFA

Sales Proposal For:
CITY OF FLAGSTAFF

Presented By:
RWC Group

Prepared For:
CITY OF FLAGSTAFF
Nathan Naliborski
211 WEST ASPEN AVE.
FLAGSTAFF, AZ 86001-
(928)779 - 7619
Reference ID: N/A

Presented By:
RWC Group
Mary R Wilson
600 North 75th Avenue
PHOENIX AZ 85043 -
(602)307-1050

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2026 HX520 SFA (HX520)

AXLE CONFIG:	6X4
APPLICATION:	Front Plow with spreader
MISSION:	Requested GVWR: 66000. Calc. GVWR: 66000. Calc. GCWR: 80000 Calc. Start / Grade Ability: 32.00% / 2.92% @ 55 MPH Calc. Geared Speed: 79.5 MPH
DIMENSION:	Wheelbase: 240.00, CA: 150.00, Axle to Frame: 67.00
ENGINE, DIESEL:	{Cummins X15 470V} Productivity Series, EPA 2024, 470HP @ 1900 RPM, 1750 lb-ft Torque @ 900 RPM, 2000 RPM Governed Speed, 481 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 4500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-164P} Single Reduction, Standard Width, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 4.56
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 425/65R22.5 Load Range L HAC 3 (CONTINENTAL), 465 rev/mile, 68 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
SUSPENSION, REAR, TANDEM:	{Hendrickson HMX EX 460} Walking Beam, 46,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings
PAINT:	Cab schematic 100LY Location 1: 9219, Winter White (Std) Chassis schematic N/A

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
HX52000	Base Chassis, Model HX520 SFA with 240.00 Wheelbase, 150.00 CA, and 67.00 Axle to Frame.	8886/7472	16358

AXLE CONFIGURATION

1AND	AXLE CONFIGURATION 6x4 <u>Notes</u> : Pricing may change if axle configuration is changed.	133/215	348
------	--	---------	-----

ENGINE

12EWY	ENGINE, DIESEL {Cummins X15 470V} Productivity Series, EPA 2024, 470HP @ 1900 RPM, 1750 lb-ft Torque @ 900 RPM, 2000 RPM Governed Speed, 481 Peak HP (Max)	0/0	0
12VJZ	EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2025	0/0	0
12XCS	CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty	0/0	0
12WZE	CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations	0/0	0
12WVG	EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood	0/0	0
10UAV	VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA / OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle. <u>Notes</u> : CANNOT BE REGISTERED IN CA. For vehicles that will be registered in States other than CA.	0/0	0
12XBN	RADIATOR Aluminum, Welded, Cross Flow, Front to Back System, 1084 SqIn, with 866 SqIn Charge Air Cooler <u>Includes</u> : RADIATOR HOSES Premium, Rubber	0/0	0
12THT	FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed <u>Includes</u> : FAN Nylon	0/0	0
12VCC	AIR CLEANER Single Element, with Integral Pre-Cleaner, Integral Snow Valve and In-Cab Control, Engine Mounted	1/0	1
12703	ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
12WCT	BLOCK HEATER, ENGINE {Phillips} 120V/1500W, with "Y" Cord for Fuel Heater <u>Includes</u> : BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door	2/0	2
12WTA	FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted	0/0	0
12WCX	HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type	0/0	0
12WYZ	RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System	0/0	0

TRANSMISSION

13BEK	TRANSMISSION, AUTOMATIC {Allison 4500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, On/Off Highway	170/78	248
-------	---	--------	-----

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
13WUC	ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223	0/0	0
13WVV	NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released	0/0	0
13WCT	OIL COOLER, TRANSMISSION {Champ} Remote Mounted, for Automatic Transmission	0/0	0
13WDZ	SHIFT CONTROL PARAMETERS {Allison} 3000 or 4000 Series Transmissions, S1 Performance in Primary and Fixed Programming in Secondary	0/0	0
13WLM	TRANSMISSION OIL Synthetic; 63 thru 76 Pints	0/0	0
13WET	TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1

CLUTCH

11001	CLUTCH Omit Item (Clutch & Control)	-105/-28	-133
-------	-------------------------------------	----------	------

REAR AXLES, SUSPENSIONS

14HRE	AXLE, REAR, TANDEM {Meritor RT-46-164P} Single Reduction, Standard Width, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Forward-Rear and Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 4.56	0/514	514
14UMX	SUSPENSION, REAR, TANDEM {Hendrickson HMX EX 460} Walking Beam, 46,000-lb Capacity, 54" Axle Spacing, Rubber Springs, with Transverse Torque Rods, Rubber End Bushings	0/9	9
14WCR	TRANSVERSE TORQUE RODS {Hendrickson} TRAAX Rod, Transverse Only	0/-4	-4

FRONT AXLES

2ARY	AXLE, FRONT NON-DRIVING {Meritor MFS-20-133A} Wide Track, I-Beam Type, 20,000-lb Capacity	186/0	186
------	---	-------	-----

FRONT SUSPENSIONS

3ADJ	SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 20,000-lb Capacity, Steel Springs 18K Capacity and (2) Rubber Auxiliary Springs 2K Capacity, Less Shock Absorbers	173/0	173
3772	SHOCK ABSORBERS, FRONT for Suspensions 20,000-lb Capacity and Above	79/0	79

CABS, COWLS, BODIES

16030	CAB Conventional, Day Cab <u>Includes</u> : CAB REAR SUSPENSION Air : CLEARANCE/MARKER LIGHTS (5) LED Roof Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area : CONSOLE, OVERHEAD Molded Plastic with Dual Storage Pockets, Retainer Nets and CB Radio Pocket; Located Above Driver and Passenger : COURTESY LIGHT (2) Driver and Passenger Door Mounted : DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console : FLOOR COVERING Rubber, Black : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side : READING LIGHT, CAB Located in Overhead Console	0/0	0
-------	---	-----	---

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
16ZJA	: STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door ACCESS, CAB Aluminum, Self-Cleaning, Open and Serrated Design, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab, Extended Cab or Sleeper Cab	6/1	7
16BAM	AIR CONDITIONER with Integral Heater and Defroster <u>Includes</u>	0/0	0
16VKK	: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps CAB INTERIOR TRIM Diamond, for Day Cab	0/0	0
16GEG	GAUGE CLUSTER Premium Level; English with English Electronic Speedometer <u>Includes</u> : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/ Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)	0/0	0
16HHE	GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} Mounted in Instrument Panel	2/0	2
16SDC	GRAB HANDLE, EXTERIOR (2) Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left and Right Side at B-Pillar	6/0	6
16XJP	INSTRUMENT PANEL Wing Panel	0/0	0
16HKT	IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
16SNP	MIRRORS (2) C-Loop, Power Adjust, Heated, Black Heads and Arms, 7.5" x 14" Flat Glass, Includes 7.5" x 7" Convex Mirrors, for 102" Load Width <u>Notes</u> : Mirror Dimensions are Rounded to the Nearest 0.5"	3/0	3
16SNW	MIRROR, CONVEX, LOOK DOWN Right Side, Black, 6" x 10.5"	3/0	3
16SBY	MIRROR, CONVEX, HOOD MOUNTED SPECIAL, Wiring Only for Right Side Heated Mirror, Does Not Include Mirror or Mounting Brackets	5/0	5
16XRX	MODESTY PANEL Painted	0/0	0
16VLV	MONITOR, TIRE PRESSURE Omit	-9/-2	-11
16VCC	SEAT BELT All Orange; 1 to 3	0/0	0
16LWK	SEAT, DRIVER {ISRI} Series 300, Air Suspension, High Back, Vinyl, Single Chamber Lumbar, Inboard Armrest, Suspension Cover, Fore/Aft Isolator, Cushion Extension, Seat Tilt	0/0	0
16LUM	SEAT, PASSENGER {National} Non Suspension, High Back with Integral Headrest, Vinyl, with Fixed Back, with Under Seat Storage	28/12	40
16WJU	WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0
16XWJ	WINDSHIELD WIPER BLADES Winter Type	2/0	2
FRAMES			
1CGD	FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 12.50" x 3.750" x 0.500" (317.5mm x 95.25mm x 12.7mm); 480.8" (12212mm) Maximum OAL	292/474	766
1LPG	BUMPER, FRONT Gull Wing, Aluminum, Stainless Steel Clad, Heavy Duty	0/0	0
1AMS	CROSSMEMBER, FRAME TIE for Heavy Duty	52/4	56
OBD001	CROSSMEMBER, INTERMEDIATE LOC 0	0/0	0
1652	CROSSMEMBER, REAR Relocated to End of Frame	-16/81	65
1WCP	FRAME EXTENSION, FRONT Integral; 27" in Front of Grille, Includes Crossmember for Front PTO	179/-22	157
1WRZ	TOW HOOK, REAR (2) Frame Mounted; 80,000-lb. Total Capacity	-8/41	33
1WXD	WHEELBASE RANGE 211" (535cm) Through and Including 256" (650cm)	117/-117	0

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
BRAKES			
4091	BRAKE SYSTEM, AIR Dual System for Straight Truck Applications <u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel : PARKING BRAKE VALVE For Truck : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4 : SPRING BRAKE MODULATOR VALVE SR-7 with relay valve for 6x4/8x6	0/0	0
4AZJ	AIR BRAKE ABS {Bendix AntiLock Brake System} 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System, with Automatic Traction Control	0/0	0
4GBM	BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
4XDT	BRAKES, FRONT {Meritor 16.5X6 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 6", 23,000-lb Capacity	33/0	33
4EXV	BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqIn	4/0	4
4LAA	SLACK ADJUSTERS, FRONT {Haldex} Automatic	14/0	14
4WBX	DUST SHIELDS, FRONT BRAKE for Air Cam Brakes	10/0	10
4XDR	BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle	0/104	104
4EXU	BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqIn Spring Brake	0/14	14
4LGA	SLACK ADJUSTERS, REAR {Haldex} Automatic	0/32	32
4WDM	DUST SHIELDS, REAR BRAKE for Air Cam Brakes	0/20	20
4XEE	PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/60	60
4SPA	AIR COMPRESSOR {Cummins} 18.7 CFM	0/0	0
4EDM	AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
4VKC	AIR DRYER LOCATION Mounted Inside Left Rail, Back of Cab	0/0	0
4VGN	AIR TANK Painted Aluminum, with Straight Thread O-Ring Ports	-20/-8	-28
4VJJ	AIR TANK LOCATION (3) : One Mounted Inside Right Rail, Back of Cab, Two Mounted Between Rails, Back of Cab	-15/5	-10
4WVL	DRAIN VALVE {Bendix DV-2} (3) Automatic, with Heater, for Air Tanks	2/2	4
4619	TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck	2/0	2
STEERING			
5PUB	STEERING GEAR (2) {Sheppard M100/HD94} Dual Power	103/-4	99
5710	STEERING COLUMN Tilting and Telescoping	0/0	0
5CAW	STEERING WHEEL 4-Spoke; 18" Dia., Black	0/0	0
DRIVELINES			
6DGX	DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	0/0	0
EXHAUST SYSTEMS			
7BLY	EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Cab Mounted Right Side	0/0	0
7BES	AFTERTREATMENT COVER Polished Aluminum	9/2	11
7SAP	ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ ISX/X15 Engines; Furnished with Engine	0/0	0
7WDM	EXHAUST HEIGHT 10'	0/0	0
7WDN	MUFFLER/TAIL PIPE GUARD (1) Aluminum	12/8	20
7WDT	TAIL PIPE (1) Straight Type	0/0	0

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
ELECTRICAL SYSTEMS			
8000	ELECTRICAL SYSTEM 12-Volt, Standard Equipment <u>Includes</u> : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light : STARTER SWITCH Electric, Key Operated : STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted	0/0	0
12VYL	ACCESSORY WIRING, SPECIAL for Road Speed Wire Coiled Under Instrument Panel for Customer Use	0/0	0
8GXJ	ALTERNATOR {Leece-Neville AV1160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	0/0	0
8RPP	ANTENNA Shark Fin, Roof Mounted	1/0	1
8THB	BACK-UP ALARM Electric, 102 dBA	0/3	3
8VUK	BATTERY BOX Aluminum, with Plastic Cover, 18" Wide, 2-4 Battery Capacity, Mounted Right Side Back of Cab	0/0	0
8RLZ	BATTERY DISCONNECT SWITCH {Cole-Hersee 75920-06} 300 Amp, Disconnects Cab Power, Does Not Disconnect Charging Circuits, Locks with Padlock, Battery Box Mounted	0/0	0
8MJU	BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 2850CCA Total, Top Threaded Stud	13/9	22
8XMA	BEACON MOUNTING BRACKET (2) Stainless, For Customer Furnished Beacon; Includes Wiring and Dash Mounted Switch	9/4	13
8HAE	BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/ Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn	3/0	3
8RNC	CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, Two Antennas and Antenna Bases with Wiring on Both Side Mirrors	0/0	0
8RGA	2-WAY RADIO Wiring Effects; Wiring with 20 Amp Fuse Protection, Includes Ignition Wire with 5 Amp Fuse, Wire Ends Heat Shrink and Routed to Center of Header Console in Cab	1/0	1
8XAH	CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
8HAH	ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket	0/2	2
8WXB	HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	0/0	0
8XNY	HEADLIGHTS Halogen	0/0	0
8WRB	HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On	0/0	0
8836	HORN, AIR (2) Single Bell, Organ Tone, Extra Long, Chrome	4/0	4
8VAY	HORN, ELECTRIC Disc Style	0/0	0
8RPS	RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	3/0	3
8695	SNOW SHIELD (2) Chrome; for Dual Air Horns	1/0	1
8RBZ	SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door	0/0	0
8RMV	SPEAKERS (2) 6.5" Dual Cone Mounted in Doors	0/0	0
8WTL	STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection	1/0	1

Vehicle Specifications
2026 HX520 SFA (HX520)

Code	Description	F/R Wt (lbs)	Tot Wt (lbs)
8TKJ	STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn, Tail and Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes License Plate Light	-1/9	8
8WPZ	TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
8TKK	TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/ Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch	1/0	1
8WEZ	TURN SIGNAL SWITCH Self-Canceling	0/0	0
8WGL	WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0

FRONT END

9ASE	FRONT END Tilting, Composite	0/0	0
9WAC	BUG SCREEN Mounted Behind Grille	5/0	5
9585	FENDER EXTENSIONS Rubber	13/0	13
9HCN	GRILLE Chrome Vertical Accent Bars, with Black Mesh	0/0	0
9AAB	LOGOS EXTERIOR Model Badges	0/0	0
9AAE	LOGOS EXTERIOR, ENGINE Badges	0/0	0

SPEEDOMETER, TOOLS, MISC

10AGB	COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360	0/0	0
10WLC	GCWR RANGE GCWR Equal to or Less than 80,000-lb, Higher GCWR May Result in Reduced Engine Performance While Operating in Extreme Hot Weather Conditions	0/0	0
10NWE	OVER WIDTH IDENTITY Customer Approval, This Combination will Result in Vehicle Width Over 102"	0/0	0
10060	PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
10761	PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
10SLV	PROMOTIONAL PACKAGE Government Silver Package	0/0	0
10WCY	SAFETY TRIANGLES	5/1	6

FUEL TANKS

15SSN	FUEL TANK Non-Polished Aluminum, 24" Dia, 60 US Gal (227L), Mounted Left Side, Under Cab	0/0	0
15WEY	DEF TANK 10.8 US Gal (41L) Capacity, Frame Mounted Outside Left Rail, Under Cab	0/0	0
15LNA	FUEL HEATER PLUMBING {Cummins} Plumbing for Thermal Recirculation Valve (TRV) Mounted to Cummins X15 Engines, Thermostatically Controlled	0/0	0
15LRV	FUEL/WATER SEPARATOR {Davco 386} 120 VAC Plug-In Electric Pre-Heater, 12 VDC Electric Heater, with ESOC Fittings, Includes Water-in-Fuel Sensor	4/0	4

WHEELS, TIRES - FRONT

27DBE	WHEELS, FRONT {Alcoa 82362} DISC; 22.5x12.25 Rims, High Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs, Offset 3.875"	0/0	0
7752665441	(2) TIRE, FRONT 425/65R22.5 Load Range L HAC 3 (CONTINENTAL), 465 rev/mile, 68 MPH, All-Position	112/0	112

WHEELS, TIRES - REAR

28DUK	WHEELS, REAR {Accuride 29169} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 5-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with .472" Thick Increased Capacity Disc and Steel Hubs	0/88	88
-------	--	------	----

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
7372135439	(8) TIRE, REAR 11R22.5 Load Range G HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position	0/0	0

BODY INTEGRATION

60AAG	BDY INTG, REMOTE POWER MODULE Mounted Inside Cab Behind Driver Seat, Up to 6 Outputs & 6 Inputs, Max 20 amp per Channel, Max 80 amp Total; Includes 1 Switch Pack with Latched Switches	0/0	0
60AAT	BDY INTG, ADDITIONAL CAB HOLE for Customer Use	0/0	0
60AKZ	BDY INTG, DASH IND LT TRICOLOR (2) for Optional Usage Customer to Program	0/0	0
60AKG	BDY INTG, PTO ACCOMMODATION for (3) Latched Rocker Switches, (1) PTO Switch, (2) Generic Switches to Control (3) 30 amp relays, with Programmable Interlocks, for Body Builder Hook up in the Engine Compartment Left Side, Recommended for Automatic Transmissions Cab schematic 100LY Location 1: 9219, Winter White (Std) Chassis schematic N/A	0/0	0

Services Section:

WARRANTY

40132	WARRANTY Standard for HX520, HX620, Effective with Vehicles Built January 1, 2021 or Later, CTS-2015B	0/0	0
-------	---	-----	---

Total Component Weight:

10518/9079 **19597**
 (lbs) (lbs)

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
1	<p>NEW CRYSTEEL SELECT DUMP BODY 150" MIN CA NEEDED 16' LONG X 87" W ID X 96" W OD 8" TALL WESTERN LONGSILLS WITH 5/8" RUBBER WEAR PADS BETWEEN FRAME FRONT WALL IS 58" TALL , 10GA A1011 STEEL , WITH STD 1/2 CAB SHIELD VERTICAL DOGHOUSE HOIST (does not protrude more then 12" into body) TAPERED SIDES 54" - 46" TALL, 7GA A1011 STEEL FLOOR IS 3/16" AR-400 ABRASION RESISTANT STEEL TAILGATE IS 46" TALL, 7-GA A1011 STEEL, STD SWING WITH AIR OP GATE LOCK 10" SPREAD APRON AT REAR STEPS AND GRAB HANDLE AT DRIVERS SIDE REAR POST HD REMOVABLE REAR MUDFLAPS BEHIND DRIVE AXLE STEEL FENDERS/MUDGUARDS AHEAD OF DRIVE AXLES LED LIGHTS TO DOT REQUIREMENTS, INCLUDES BODY UP LIGHT ALL WIRING FOR BODY LIGHTS IS IN FLEX CONDUITE. & SS NEMA ELECT BOX INSTALLED COMPLETE PAINTED CUST COLOR HOT SHIFT PTO AND DIRECT MOUNT HYD PUMP FOR ALLISON TRANSMISSION BODY, PLOW & SANDER CONTROL SYSTEM IS FORCE AMERICA 6100 ULTRA CONTROL INCLUDES POWER FLOAT OPTION & ADDITIONAL INVIEW SWITCH PANEL INCLUDES HYD LINES RUN TO FRONT AND REAR OF CHASSIS FOR PLOW & SANDER</p> <p>ELECTRIC TARP SYSTEM WITH ALUM TARP ARMS AND HD MESH TARP INSTALLED</p> <p>HENKE 12' X 42" FULL MOLDBOARD TRIP, REVERSABLE PLOW. (7) MOLDBOARD TO PUSH-FRAME CONNECTION POINTS WITH BUSHINGS 12" RUBBER SNOW DEFLECTOR, AND CURB GUARD INCLUDED PLOW LIGHTS AND BRACKETS INSTALLED TO CUST SPECS (Truck must have plow light switch) INCLUDES FRONT FOG LIGHTS AND WORK LIGHTS</p> <p>MONROE 14' STAINLESS STEEL V-BOX SANDER ON SKID ASSEMBLY HEATED - INCLUDES FLEX EXHAUST ROUTED TO TRUCK EXHAUST 10GA HOPPER, 62" HIGH SIDES, INCLUDES TOP GRATE KITS 10GA TIP UP SPINNER ASSEMBLY SS FOLD UP LADDER IN REAR SS LIGHT BAR AT REAR OF SANDER, INCLUDES STROBE LIGHTS AND WORK LIGHTS INCLUDES SELF LOADING LEG KITS, AND RATCHET / BINDER TIE DOWNS</p> <p>STROBE LIGHTS MOUNTED ON CAB GUARD OF DUMP BODY STROBE LIGHTS MOUNTED IN REAR POST OF DUMP BODY EACH SIDE 18-18-36 STEEL TOOL BOX MOUNTED LS OF FRAME</p> <p>HD REAR HITCH PLATE WITH REMOVABLE, SWIVEL PINTLE HITCH, & BUILT IN CHIP BAR INCLUDES D-RINGS GLAD HANDS AND 7-WAY LIGHT SOCKET.</p> <p>FURTHER DISCUSSION SHOULD BE DONE WITH CUSTOMER TO MAKE SURE ALL OPTIONS ARE CORRECT FOR THE CUSTOMERS NEEDS BEFORE PROJECT IS STARTED</p> <p>Chassis will need front frame extensions for plow hitch mount. Chassis will need plow light switch & relay prewired in cab</p>	0/0	0

Vehicle Specifications
2026 HX520 SFA (HX520)

<u>Code</u>	<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
	Total Body Allied:	0/0 (lbs)	0 (lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.

Financial Summary
2026 HX520 SFA (HX520)

Table with 3 columns: Description, (US DOLLAR), Price. Rows include Total Factory List Price Including Options, Freight Charge, Total Freight, Total Factory List Price Including Freight, Less Customer Allowance, Total Vehicle Price, Total Body/Allied Equipment, Total Sale Price, Total Per Vehicle Sales Price, Total Net Sales Excluding Taxes, Arizona Tire Tax, Sales Tax, Pima County, Total Taxes, Net Sales Price.

State Contract CTR069476

If applicable, Federal Excise Tax (FET) is included in the net sales price above.

Terms of payment are cash on delivery and prices quoted are FOB Phoenix, AZ (unless otherwise noted).

This quote is good for 30 days. All inventory units are subject to prior sale. Unless otherwise noted, the quote above does NOT include title and licensing charges or Arizona state sales tax.

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

This proposal is not binding upon the seller without Seller's Authorized Signature

Official Title and Date

The TOPS FET calculation is an estimate for reference purposes only. The seller or retailer is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described herein are Navistar, Inc.'s standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.