



City of Ft. Pierce
 52 Savannah Rd.
 Fort Pierce, Florida 34954
 Att. Chuck Penachino

April 2, 2019

One (1) Peterbilt Model 520, Per Florida Sheriffs Association

Bid No: FSA18-VEH18-VEL 26.0 Specification # 16

(1) 2019 Peterbilt Model 520 - Cab & Chassis only Painted White	\$135,685.
Options Added:	
1. 380 HP with C-Brake by Jacobs	2,672.
2. Front 425 R22.5 296 Bridge Stone M864	987.
3. Rear tires 12R22.5 Bridge Stone M853	2,276.
4. Right Hand Drive	1,333.
5. Shock Absorbers for HMX Suspension	427.

Sub Total \$ 143,380.

One New Heil Dura-Pack Side Loader 28 cu. yd.	130,594.
Double Camera System, 20 Lb. Fire Extinguisher, all Standard, Features 12 Month Warranty	

Total Price Per Unit \$273,974.

WARRANTY OPTIONS:

Cummins ISX12 Protection Plan 1 & Aftertreatment Coverage 5Year/300, Miles	2,610.
Allison Transmission 2+3=5 Year Warranty	1,241.

Thank you for the opportunity to quote the Peterbilt product and we are looking forward to your most valued order.

Prepared By:
 Rudy Mangino Jr.



Corporate Office
 2441 S. State Road 7 (441)
 Fort Lauderdale, FL 33317
 (954) 584-3200

Fort Pierce
 5750 Orange Ave.
 Fort Pierce, FL 34947
 (772) 489-2300



Fort Myers
 5313 St. Rd. 82 / MLK Blvd.
 Fort Myers, FL 33905
 (239) 337-0188



West Palm Beach
 7206 Belvedere Road
 West Pam Beach, FL 33411
 (561) 253-0129

Clewiston
 111 S. San Benito St.
 Clewiston, FL 33440
 (863) 301-3700



P19-117A 520RH X12 4500 Fleet

Phone:
Fax:
Contact Email:
Prepared for:

Vehicle Summary

Unit		Chassis	
Model:	Model 520	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	46000
Description:	P19-117A 520RH X12 4500 Fleet	G.C.W. (lbs):	66000
Application		Road Conditions:	
Intended Serv.:	Refuse/Landfill	Class A (Highway)	90
Commodity:	Refuse, Scrap, Recycling	Class B (Hwy/Mtn)	10
Body		Class C (Off-Hwy)	0
Type:	Automated Side Loader	Class D (Off-Road)	0
Length (ft):	20	Maximum Grade:	6
Height (ft):	8.0	Wheelbase (in):	215
Max Laden Weight (lbs):	17000	Overhang (in):	110
Trailer		Fr Axle to BOC (in):	0.1
No. of Trailer Axles:	0	Cab to Axle (in):	214.9
Type:		Cab to EOF (in):	324.9
Length (ft):	0	Overall Comb. Length (in):	382
Height (ft):	0.0	Special Req.	
Kingpin Inset (in):	0	California Registry	
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

	Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com .
	PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



P19-117A 520RH X12 4500 Fleet

Phone:
Fax:
Contact Email:
Prepared for:

	Description	Weight
Base Model		
	Model 520	16,475
	Refuse, Scrap, Recycling	0
	Refuse/Landfill Truck which picks up refuse or recycled material from curbside containers in residential areas. Operation typically includes very frequent stops and starts. Unloading can be at transfer station or at landfill (may enter landfill).	0
	Automated Side Loader	0
	California Registry Required for all vehicles that will be registered in the State of California.	0
Configuration		
	Not Applicable Secondary Manufacturer	0
Frame & Equipment		
	10-3/4in Steel Rails 343-450in 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	351
	Full Steel Inner Liner	774
	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	0
	FEPTO Provision 4-7/8in Bumper Extension Includes 1350 Series Front Drive PTO Attachment Provision, Radiator with PTO Cut-Out in Grille, Radiator Protection Sleeve, and Bumper Extension	45
	EOF Square without Xmbr For use with body builder installed crossmember.	0
	Peterbilt Rear Mudflaps and Straight Hangers	25
	(2) Solid Mount Cable Hooks	0

Front Axle & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number: Model 520
Quote/DTPO/CO: Q05304584
Version Number: 35.20



Description	Weight
Meritor MFS20 20,000 lb, 3.74 in Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life.	-4
Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0
Power Steering Sheppard SD110 Dual For use with 22,000 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	40
PHP10 Iron PreSet PLUS Hubs	84
Meritor 5in Drop IPO 3.5in, Front Axle 5" drop (127MM) provides lower chassis suspension and profile.	0
Meritor Wide Track IPO Standard, Front Axle MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles For improved turning radius.	5
Meritor Q+ Air Cam Front Drum Brakes 16.5x7 Not RSD compliant.	0
Long Stroke Brakes, Front Axle	0

Rear Axle & Equipment

Meritor RT46-160 46,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	0
PHP10 Iron PreSet PLUS Hubs	0
Long Stroke Parking Brakes, Drive Axle(s)	0
Optional Longer Studs For Hub Piloted Whl System For use with F/O installed aluminum wheels with cast drums.	0
Bendix Smart ATC Traction Control	2
Refuse Service Brakes, Steer And Drive Axles	0
Rear Brake Camshaft Reinforcement	9
Lube Pump, Drive Axle(s)	36

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



Description	Weight
SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
Meritor Q+ Air Cam Rear Drum Brakes 16.5x8.625	0
Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	35
Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
Ratio 4.89 Rear Axle	0
Hendrickson Haulmax HMX460 46,000 lb, 54in Axle Spacing, 60K Creep Rating	-15
Shock Absorbers For HMX Suspension	31
HMX Double Rebound Strap Kit	6

Engine & Equipment

ISX12 350R 350@1800 GOV@2100 1450@1100 Refuse Service (2013 Emissions) Includes aluminum flywheel housing. Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21340 P112 120..Hard Maximum Speed Limit N21350 P001 65...Maximum Accelerator Pedal Vehicle Speed N21370 P059 65...Maximum Cruise Speed N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 YES..Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Overrule	1,030
---	-------

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



Description	Weight
N21590 P230 YES..Enable Hot Ambient Automatic Overrule	
N21610 P172 40...Low Ambient Temperature Threshold	
N21620 P173 60...Intermediate Ambient Temperature Threshold	
N21630 P171 80...High Ambient Temperature Threshold	
Engine Idle Shutdown Timer Enabled	0
Enable EIST Ambient Temp Overrule	0
Eff EIST NA Expiration Miles	0
Effective VSL Setting NA	0
Remote PTO And Throttle Provision	0
CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
160 Amp Alternator, 36 SI Brushless	10
Remote Voltage Sense Wiring	0
Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
Delco 39MT Starter, Overcrank Protection	0
3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
Kissling Battery Disconnect Switch Mounted on battery box	3
2-Speed Fan Clutch For Frequent Start/Stops	0
18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
C-Brake By Jacobs, ISX12, ISX12-G Includes 2 switches: A 2-position on/off engine switch. As well as a 3-position up, down, hold range selector switch.	0
DAVCO 382 Fuel/Water Separator	0
No Fluid Heat Option for Fuel Filter	0
12V and 120V Heat for Fuel Filter	0
Engine Protection Shutdown Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:
Quote/DTPO/CO:
Version Number:

Model 520
Q05304584
35.20



Description	Weight
High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
Bugscreen-Removable Type Grill Mtd Additional clips at bottom of bugscreen.	0
Stainless Steel Grille	0
Heavy Duty Air Cleaner Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
Exhaust Vertical LH DPF/SCR transverse mounted (ISX12 Only).	0
Curved Tip Standpipe(s)	0
18in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	-2
Transmission & Equipment	
Allison 4500 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-4.70, 2nd-2.21, 3rd-1.53, 4th-1.00, 5th-0.76, 6th-0.67 / Reverse Ratios: DR-(5.55)	365
1810 HD Driveline, 1 Midship Bearing 4.5in x .180 wall tubing	70
Allison FuelSense Basic Includes 5th Generation Controls, EcoCal and Dynamic Shift Sensing. For additional information see Product Portfolio.	0
Console Mounted Push Button Shifter Allison transmissions	0
Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 Transmission Only	0

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



Description	Weight
<p>Allison Output Function S Neutral Indicator For PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is switched On. Also, with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.</p>	0
<p>Allison Transmission Fluid Test Port Remote coupler. The fluid test port provides easy access to transmission fluid for testing from its location under the hood on the right-hand frame rail.</p>	0
<p>Rolling Direction Change Shift Inhibit Feature Allison Transmissions. A programmable feature that keeps the transmission from shifting from Drive to Reverse or from Reverse to Drive above a preset speed. This wireless function is enabled when a switch is closed to complete the circuit between input wire 101 and ground. Frequently the function is interfaced with a switch indicating activation of another vehicle function, such as application of the service brakes. When the function is enabled, the TCM will recognize the request for a direction change shift, Reverse-to-Drive or Drive-to-Reverse. If all other operating conditions are acceptable, the TCM will command the requested shift. The enable remains in effect until the switch is opened, followed by the selection of a different direction, Reverse or Drive, at the shift selector. This could be used for doc spotters and refuse. If the function is not enabled, any shift which results in a change of direction is inhibited.</p>	0
Air & Trailer Equipment	
<p>Bendix AD-IS EP Air Dryer with Heater And Coalescing Filter; Extended Purge</p>	0
Air Tank Valve Guards	0
Nylon Chassis Hose	0
Compressor Discharge Line Test Valve	0
<p>Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.</p>	0
<p>Clear Outside Frame of All Air System Components RH BOC</p>	0
Tires & Wheels	
<p>FF: BR 20ply 315/80R22.5 M860A Diameter = 42.8 inches; SLR = 19.9 inches</p>	-4

Unpublished options may require review/approval.
 Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



Description	Weight
RR: BR 20ply 315/80R22.5 M860A	376
Diameter = 42.8 inches; SLR = 19.9 inches	
Code-rear Tire Qty 08	0
FF: Alcoa 89U637 22.5X9.00 Clean Buff Finish	-70
Aluminum, Ultra ONE wheels with MagnaForce alloy.	
RR: Alcoa 89U647 22.5X9.00 Clean Buff Finish	-216
Aluminum, Ultra ONE wheels with MagnaForce alloy.	
Code-rear Rim Qty 08	0

Fuel Tanks

26in Aluminum 80 Gallon Fuel Tank LH BOC	13
Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	
Location LH BOC Rear-Most 80 Gallon	0
Fuel Cooler	0
Required with single fuel tank.	
Top Of Fuel Tank 5in Below Top Of Frame	33
DEF Tank Mounted LH BOC	0
Models 210, 220 and 320 mounted LH cab fender.	
Standard DEF To Fuel Ratio 2:1 Or Greater	0
DEF Tank 520	0

Battery Box & Bumper

Aluminum Space Saver Battery Box LH Back Of Cab	-11
Rubber Battery Pad In Bottom Of (1) Battery Box	2
(Mat in box that holds batteries only)	
Mount Space Saver Battery Box Top Of Box 8in	0
Below top of frame	
Steel Bumper Swept Back Painted	2
Requires bumper extension. Includes two front tow eyes with pins.	
Notched Top Flange Of Bumper	0

Cab & Equipment

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:

Model 520

Quote/DTPO/CO:

Q05304584

Version Number:

35.20



Description	Weight
53in LCF ProBilt Cab RH Drive Use with auto trans. Includes steel frames with alum and fiberglass panels, all alum doors, dual door stops, door locks, tinted safety glass thru-out, cab and door mounted entry grab handles, 65 degree hydraulic tilt, stainless steel grille, dual rear cab fenders, service module BOC (cab tilt pump, oil fill and dipstick, coolant fill and check, fluid fill and dipstick for auto trans), door mounted armrests, power windows, full insulation, rubber floor mats, ergonomic center control console, removable instrument panel, Driver Information Display, LED backlit gauges, pull down windshield sunshade, 16in steering wheel with integrated horn button, tilt/telescopic adjustable column, over-door storage, driver and passenger side cup holders, USB charging port and 12VDC charging outlet, header includes HVAC controls, rear cab corner windows, 18in bolt-on step on each side, self-canceling turn signals and Front Directional and Side Mounted Turn Signals.	0
Key All Units Alike Please add your 3 digit key code number in the key code field.	0
KEY G479	0
4.5 Inch Rubber Flares on Cab and Wheel Well Fenders	0
Sears C2 Driver Seat	0
Peterbilt Passenger Seat	0
Seat Belt Color Orange IPO Standard Black	0
Air Ride Driver	0
Mid Back Driver	0
Fabric Driver	0
Non-Air Ride Passenger	0
Low Back Passenger	0
Vinyl Passenger	0
Gray Interior Color Includes ABS gray headliner & rear cab panel, gray vinyl engine tunnel cover.	0
Adjustable Steering Column - Tilt/Telescope	0
Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
Rear Window Back of Cab Standard Tint 18.5in X 54in	0
Two Piece Flat Windshield	0
Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:
Quote/DTPO/CO:
Version Number:

Model 520
Q05304584
35.20



Description	Weight
Mirrors SSTL Each Side Heated and Motorized with Switch on Door. Right Click on option to See Picture in Product Portfolio.	-7
(2) Convex 8 Inch SS Mirror Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	2
(1) Air Horn 15in Painted Mounted under cab.	0
ConcertClass w/CD, Bluetooth Phone and Audio Includes AM/FM, WB, USB and MP3.	10
Midlevel Speaker Package For Cab (4) Speakers	6
Radio Mute when Allison Transmission in reverse - requires option 8140690 for 520 only.	0
SmartLINQ Remote Diagnostics SmartLINQ is Peterbilt's proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesn't require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available.. SmartLINQ is standard with MX-13 engines and available on the models 587,579,567,389,367 and 365.	0
Pre-Wire Cab 3rd Eye Vision System	0
Pre-wire Chassis for 3rd Eye Vision System	0
Cab Tilt Pump Air Assist	0
Rain Gutters Over Driver and Passenger Doors	8
Peterbilt Pantograph Windshield Wipers With intermittent feature.	0
Triangle Reflector Kit Shipped Loose	13
Ecco DS-1500 Reverse Motion Sensor Use with backup alarm.	0
Backup Alarm (87-112 Decibels) Self Adjusting	6
Engine Oil Temperature Gauge Located in Driver Information Display	0
Main Transmission Oil Temperature Gauge Located in Driver Information Display	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20



	Description	Weight
	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall.	0
	Warning Light Battery Disconnect, Switch Engaged (Marker light) external mounted.	0
	Indicator Light For F/O PTO Controls Located in Driver Information Display	0
	Headlights Single Rectangular Halogen	0
	(5) Light Guards On Marker Lights	2
	(5) LED Clearance With (2) LED Marker Lights Includes (5) lights mounted on roof of cab and (1) cab side marker light mounted in front of each cab door.	0
	None Furnished Stop/Tail/Backup Lights Available with Full Truck only. Not available with Tractor.	0
	Daytime Running Lights (Required on Canadian units)	0
	Brake Lights Activated by Park Brake Requires Option 7726010	0
Paint		
	Standard Paint Color Selection	0
	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EB WHITE - STAND N85500 CAB ROOF L0006EB WHITE - STAND N85200 FRAME N0001EA BLACK N85700 BUMPER N0001EA BLACK	0
Miscellaneous		
	2017 EPA Emissions Engine Warranty Only	0
Total Weight		19542

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Complete

Model Number:	Model 520
Quote/DTPO/CO:	Q05304584
Version Number:	35.20