



10/27/2021

City of Fort Pierce
52 Savannah Rd.
Ft. Pierce, FL 34854

Att: Charles Penachio

Five (5) Peterbilt Model 337, per FI Sheriffs Association
Bid FSA20-VEH18.0 Heavy Truck
QUO-580664-M9F1X0

(1) 2023 Peterbilt 337- Cab & Chassis only \$76,320

Option added:

- | | |
|---|----------|
| 1. PX7-270HP with Allison 3000 RDS transmission | \$14,565 |
| 2. Dana Spicer Front Axle 12K lb | \$1,379 |
| 3. 10 3/4 steel frame | \$4,885 |
| 4. Refuse Svc. Brakes package | \$1,039 |
| 5. Rear Diff. Lock | \$1,763 |
| 6. Front & Rear Alum. Wheels | \$3,881 |
| 7. Rayco Helper Springs | \$936 |

Sub Total \$104,768

Petersen TL-C HARDOX LOADER \$82,449

Total Price Per Unit \$187,217

Thank You for the opportunity to quote the Peterbilt product and we are looking forward to Your most valued order.

Prepared by:
John DeMarco

Buyers Signature:

DATE:

THEPETESTORE.COM



The Peterbilt Store - Fort Lauderdale (P750)
 2441 South State Road 7
 Ft. Lauderdale, Florida 33317

City Of Ft Pierce
 59 Savannah Rd
 Ft Peirce, Florida 34954
 United States of America

John DeMarco
 Cell Phone:
 Office Phone:
 Email: jdemarco@thepetestore.com

Chuck penachino
 Email: cpenachio@cityoffortpierce.com

Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	21000
Description 1:	Grappel	G.C.W. (lbs):	62000
Description 2:			
Intended Serv.:	Application Refuse/On-Highway	Road Conditions:	
Commodity:	Refuse, Scrap, Recycling	Class A (Highway)	100
		Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Type:	Body End Dump	Maximum Grade:	6
Length (ft):	20	Wheelbase (in):	238
Height (ft):	10	Overhang (in):	75
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	69.8
		Cab to Axle (in):	168.2
		Cab to EOF (in):	243.2
No. of Trailer Axles:	0	Overall Comb. Length (in):	351.2
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Comer Radius (in):	0		
	Restrictions		
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
Base Model		
S	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	10,070
O	Refuse, Scrap, Recycling	0
O	Refuse/On-Highway Truck or tractor which hauls refuse, recycled material, etc. Includes roll-on/roll-off container movement, as well as hauling refuse from transfer stations to, but not into, landfills.	0
O	End Dump	0
S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipso MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0
Configuration		
S	Not Applicable Secondary Manufacturer	0
Frame & Equipment		
O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	535
O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	4
O	Custom Wheelbase or Overhang Engineering approval may be required.	0
O	Three-Piece Crossmembers	58
S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0
S	Omit Rear Mudflaps and Hangers	0
Front Axle & Equipment		
O	Dana Spicer E1202IL 12,000 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 lb. The axles have exclusive one-piece forged	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	design knuckle including steer arm, tie rod arm and spindle. This feature helps in greater durability and reduced maintenance.	
O	Taper Leaf Springs, Shocks 12,000 lb Hendrickson taper leaf springs, shocks for 12,000 lbs.	0
S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0
O	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0
S	PHP10 Iron PreSet Hubs	0
O	Dana Spicer Wide Track IPO Standard Dana Spicer wide track front axles offer added stability and deliver greater turn angles. 71in KPI IPO 69in for E1202, E1322, E1462, D2000F front axles.	15
S	Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
S	Gusseted Cam Brackets, Steer Axle	0
Rear Axle & Equipment		
O	Dana Spicer P22060S 21,000 lb	117
S	PHP10 Iron PreSet Hubs	0
O	Refuse Service Brakes, Steer And Drive Axles Designed for heavy-duty applications for refuse industry, providing long brake life, safety and performance.	0
O	Gusseted Cam Brackets, Drive Axle(s)	2
S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
O	Diff Lock, Single Drive Axle with Speed Interlock	30
S	Stability System Not Selected Or Not Available	0
S	Single Drive Axle (Model 337)	0
S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0
S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	
S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
O	Ratio 5.57 Rear Axle	0
S	Reyco 79KB Taper Leaf 21,000 lb	0
O	Reyco Helper Springs 4,500 lb For use with Reyco 79KB suspension	62

Engine & Equipment

O	PACCAR PX-9 270@2000 GOV@2200 860@1200 Productivity (2021 EMISSIONS)	0
	N21350 C121 51....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 1.....Timer Setting (P030) N21610 C188 0.....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 0.....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 30....Timer For Impending Shutdown N21320 C399 0.....Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)	
O	Engine Idle Shutdown Timer Enabled	0
O	Enable EIST Ambient Temp Overrule	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	Eff EIST NA Expiration Miles	0
	Effective VSL Setting NA	0
O	Typical Operating Speed 62 MPH	0
O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0
O	Remote PTO and Throttle Provision 12-pin connector on engine harness.	0
S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
O	Remote Throttle/PTO Control Switch & Wiring BOC W/ Park Brake	0
O	CARB Compliant Engine	0
S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0
S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0
O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	0
S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
O	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0
S	Spin-On Fuel/Water Separator	0
S	No Fluid Heat Option for Fuel Filter	0
S	No Electric Heat Option for Fuel Filter	0
O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0
S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
O	Exhaust Single RH Horizontal DPF/SCR RH Under Frame.	-158
Transmission & Equipment		
O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	195
O	SPL170 HD-XL Driveline, 3 Midship Bearings	230
O	(1) Dash Mounted Single Acting Air PTO Control Standard with PTO engaged indicator light on Class 8 units. Occupies the space of one gauge. Specing PTO switch does not ensure the PTO will fit.	0
O	Park Brake Interlock For use with transmission mounted PTO	2
O	Auto Neutral Activates With Parking Brake Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	0
O	Allison FuelSense 2.0 Not Desired	0
O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0
O	Allison 6-Speed Configuration, Close Ratio Gears	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	3000 Series Transmissions.	
O	Dash Mounted Push Button Shifter Available with Allison transmissions	0
O	Rolling Direction Change Shift Inhibit Feature Allison transmissions. A programmable feature that keeps the transmission from shifting from Drive to Reverse or from Reverse to Drive above a preset speed. This wireless function is enabled when a switch is closed to complete the circuit between input wire 101 and ground. Frequently the function is interfaced with a switch indicating activation of another vehicle function, such as application of the service brakes. When the function is enabled, the TCM will recognize the request for a direction change shift, Reverse-to-Drive or Drive-to-Reverse. If all other operating conditions are acceptable, the TCM will command the requested shift. The enable remains in effect until the switch is opened, followed by the selection of a different direction, Reverse or Drive, at the shift selector. This could be used for doc spotters and refuse. If the function is not enabled, any shift which results in a change of direction is inhibited.	0

Air & Trailer Equipment

S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0
O	Pull Cords All Air Tanks	0
S	Nylon Chassis Hose	0
S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0
O	Clear Outside Frame of All Air System Components LH BOC	0
O	Body Lighting Junction Box Without Wiring Located at EOF	3
O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	4

Tires & Wheels

O	FF: GY 14ply 11R22.5 Endurance LHS Efficiency Rating: Poor SmartWay-Verified, long haul tires for high miles to removal. Diameter=	-8
---	---	----

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	41.5 inches; SLR= 19.4 inches.	
O	RR: GY 16ply 11R22.5 Endurance LHS Efficiency Rating: Fair SmartWay-Verified, long haul tires for high miles to removal. Diameter= 41.5 inches; SLR= 19.4 inches	-16
O	Code-rear Tire Qty 04	0
O	FF: Alcoa ULT397 22.5X8.25 High Polish Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	-56
O	RR: Alcoa ULT397 22.5X8.25 High Polish Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	-112
O	Code-rear Rim Qty 04	0
Fuel Tanks		
O	26" Aluminum 70 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	-115
O	Location LH U/C 70 Gallon	0
O	Polish (1) Aluminum Fuel Tank	0
O	Locking Fuel Tank Cap(s)	0
S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0
O	DEF To Fuel Ratio 2:1 Or Greater	0
O	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0
Battery Box & Bumper		
O	Aluminum Battery Box RH Under Cab, Non-Slip Step	-55
O	Steel Styled Aero Bumper Painted Black Two tow points	0
Cab & Equipment		
S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
O	Severe Service Cab Package #1	39

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	
O	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
S	National Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0
S	(2) Person Passenger Seat	0
O	Drivers Armrest - RH Only	2
O	Seat Belt Color Orange IPO Standard Black	0
O	Air Ride Driver	0
S	High Back Driver	0
S	Vinyl Driver	0
S	Non-Air Ride Passenger	0
S	Low Back Passenger	0
S	Vinyl Passenger	0
O	Adjustable Steering Column - Tilt/Telescope	11
S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0
S	Interior Gray/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
O	NFPA Cab Entry Grabhandles National Fire Prevention Association compliant grabhandles featuring a larger diameter and slip resistant inserts required by many fire companies.	0
O	Dark Window Tint IPO Standard Tint - Day Cab	0
S	Day Cab Rear Window Day cab rear window flush to back of cab.	0
S	1-Piece Curved Windshield	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
O	Peterbilt Comfort Control - Cab	6
O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	4
O	Mirrors SSTL Each Side Heated and Motorized with Switch on Door.	2
O	(2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	4
S	Power Package Includes power door locks and power windows.	0
O	(1) Air Horn 24.5" Chrome - Round w/Horn Shield	8
O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	10
O	Standard Speaker Package For Cab (2) Speakers	4
O	USB Port	0
O	CB Terminals/Wiring Mounted Under Header	0
O	CB Antenna Mounting, RH Mirror Available with Rami only on 1.9m, available without Rami on medium duty	1
O	Radio Antenna Mounted on LH Mirror Bracket	0
O	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	0
S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	13
O	Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC	8
O	Backup Alarm Wiring To EOF	0
O	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0
O	Bright Bezel Gauges	0

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
	52mm Round Gauges Only- B Panel	
S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
O	(1) Additional Dash Switch With Wiring (1) additional dash switch with wiring. Spare 1 and 2 share 15 amp fuse, spares 3, 4, and 5 share 15 amp fuse. Availability subject to dash space.	0
S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0
S	(5) Marker Lights, Aero LED	0
O	(1) 6 in Spotlight, Round Halogen LH (1) 6" spotlight, round halogen left hand side.	4
O	(2) LED Strobe Lights Roof Mounted (2) LED strobe lights roof mounted on each side of the cab with stainless steel brackets. LED technology provides continual heavy-duty use in the toughest conditions with a weatherproof and vibration resistant design for external use. Offering four times the brightness in a more compact housing, 4.5" shorter and 3" smaller in diameter. Classified as a Class 1 light incandescent light.	10
O	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0
S	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	0
O	(1) F/O Load Light, Switch, 10' Wire Coil Under / in cab / sleeper baggage compartment	2
Paint		
O	Standard Paint Color Selection	0
S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A- L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0

Price Level: April 1, 2021 _____

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Std/ Opt	Description	Weight
Shipping Destination		
<input type="radio"/>	Shipping Destination Other Than Dealer	0
Options Not Subject To Discount		
S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0
<input type="radio"/>	Prepaid Freight Delivery Increase For 2022 Delivery	0
<input type="radio"/>	Base Warr: Emissions (CARB Surcharge) 5YR/150K MI - PX-9 Engine	0
<input type="radio"/>	Final Frame Layout See Truck Sales Bulletin 12-89 for additional information.	0
Miscellaneous		
<input type="radio"/>	State Registry: Florida	0
<input type="radio"/>	Cancel/Reorder Reorder Chassis	0

Promotions

Order Comments

Total Weight

10,937

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: April 1, 2021

100% Complete

Date: October 26, 2021

Deal: Grappel

Quote Number: QUO-580664-M9F1X0

Printed On: 10/26/2021 12:29:41 PM



Shipping Destinations

Intermediate Destination: none

Final Destinations	Quantity
P751 - The Peterbilt Store – Fort Pierce 5750 Orange Avenue Ft Pierce, Florida 34947	5