



Property Maintenance Inspection Report

Property Address Parcel ID #

House Color # of Units Building Occupied

Type of Structure Source of Complaint

Action to be taken - Select all that apply

- Unsafe Building - Rehab Permitted Unsafe Building - Demo Recommended Other - See Comments

Posting Type Red - 108.1.5 - Dangerous Structure

Inspector Date Property Posted?

Comments

- Active Code Cases NONE Active Building Permit NONE
- Lis Pendens check Rehab letter sent
- Demo letter sent Nuisance letter sent
- Title search done Affidavit recorded

Misc. Notes
and
Comments

Contact Information

Contact Info

Comments



Section 111 - Unsafe structures

111.1.1 - Unsafe structure

Comments

111.1.2 - Unsafe equipment

Comments

111.1.3 - Structure unfit for human occupancy

Comments

111.1.4 - Unlawful structure

Comments

111.1.5 - Dangerous structure or premises

- (1) Any door, aisle, passageway, stairway, or exit that does not comply to requirements for exiting the building
- (2) The walking surface of means of egress is so warped, worn, loose, torn or otherwise unsafe to provide means of egress.
- (3) Any portion of a structure damaged by fire, earthquake, wind, flood, deterioration, neglect, abandonment, vandalism or any other cause that it is likely to partially or completely collapse, or to become detached or dislodged.
- (4) Any portion of a building, appurtenance or ornamentations that is not of sufficient strength or stability, or is not so anchored or attached to be capable of resisting natural or artificial loads of one and one-half the original designed value.
- (5) The structure or part of structure because of dilapidation, deterioration, decay, faulty construction, the removal or movement of ground necessary for support or any other reason is likely to collapse or under pining is likely to fail or give way.
- (6) The building or structure, or any portion thereof, is clearly unsafe for its use and occupancy.
- (7) The structure is neglected, damaged, dilapidated, unsecured or abandoned so as to become an attractive nuisance.
- (8) Any structure that exists or has been maintained in violation of any specific requirement or prohibition to such an extent as to present either a substantial risk of fire, building collapse or any other threat to life and safety.
- (9) Any structure intended to be used for dwelling purposes, due to inadequate maintenance, dilapidation, decay, damage, faulty construction, inadequate light, ventilation, mechanical or plumbing system is determined to be unsanitary, unfit for human habitation or in such a condition that it is likely to cause sickness or disease.
- (10) Any structure, due to lack of sufficient fire resistance rated construction, fire protection systems, electrical system, fuel connections, mechanical system, plumbing system or other cause is determined to be a threat to life or health.
- (11) Any portion of a building remains on a site after the demolition of the structure or whenever any building or structure is abandoned so as to constitute such building or portion thereof as an attractive nuisance or hazard to the public.

Comments

Section 302 - Exterior property areas

Section 303 - Swimming Pools, Spas and Hot Tubs

Section 304 - Exterior Structure

304.1 - General - The exterior of a structure shall be maintained in good repair, structurally sound and sanitary so as not to pose a threat to the public health, safety and welfare.

304.1.1 - Unsafe conditions - The following conditions shall be determined as unsafe and shall be repaired or replaced to comply with the IBC or the IEBC as required for existing buildings.

- 1. The nominal strength of any structural member is exceeded by nominal loads, the load effects or the required strength.
- 2. The anchorage of the floor or roof to walls or columns, and of walls and columns to foundations is not capable of resisting all nominal loads or load effects.



<input type="checkbox"/>	3. Structures or components thereof that have reached their limit state.
<input checked="" type="checkbox"/>	4. Siding and masonry joints are not maintained, weather resistant or water tight.
<input checked="" type="checkbox"/>	5. Structural members that have evidence of deterioration or cannot safely support all nominal loads and load effects.
<input type="checkbox"/>	6. Foundation systems that are not firmly supported by footings, are not plumb without cracks and breaks and are not properly anchored or cannot support all nominal loads and resisting all load effects.
<input checked="" type="checkbox"/>	7. Exterior walls that are not anchored to supporting elements or are not plumb or free from holes, cracks, breaks or loose or rotting materials, are not properly anchored and not able of supporting all nominal loads and resisting load effects.
<input checked="" type="checkbox"/>	8. Roofing that have defects that admit rain, roof surfaces with inadequate drainage, or any portion that is not in good repair with signs of deterioration, fatigue or without property anchorage and incapable of supporting all nominal loads.
<input type="checkbox"/>	9. Flooring with defects that affect serviceability or that show signs of deterioration or fatigue, are not properly anchored or are incapable of supporting all nominal loads and resisting all load effects.
<input type="checkbox"/>	10. Veneer, cornices, belt courses, corbels, trim , wall facings not properly anchored or that are anchored with connections not capable of supporting all nominal loads and resisting load effects.
<input type="checkbox"/>	11. Overhang extensions or projections including trash chutes, canopies, marquees, signs, awnings, fire escapes, standpipes and exhaust ducts not properly anchored or anchored with connections unable to support all nominal loads.
<input type="checkbox"/>	12. Exterior stairs, decks, porches, balconies and all attachments such as guards and handrails are not structurally sound, not properly anchored or anchored with connections unable to support all nominal loads and resisting all load effects.
<input type="checkbox"/>	13. Chimneys, cooling towers, smokestacks not properly anchored or that are anchored with connections unable to support all nominal loads and resisting all load effects.

<input checked="" type="checkbox"/>	304.2 - Protective Treatment - Exterior surfaces, including doors, door and window frames, cornices, porches, trim, balconies, decks and fences shall be maintained in good condition. Exterior surfaces shall be protected from elements and decay by painting or other protective treatment. Peeling, flaking and chipped paint shall be eliminated and surfaces repainted. Siding and masonry joints shall be maintained weather resistant and water tight. Metal surfaces subject to rust or corrosion shall be coated to inhibit such rust and corrosion.
<input type="checkbox"/>	304.3 - Address identification - Buildings shall be provided with approved address identification that are legible and placed to be visible from the street fronting the property. They must contrast with their background, be numerical and a minimum of 4" tall.
<input checked="" type="checkbox"/>	304.4 - Structural members - Structural members shall be maintained free from deterioration, and shall be capable of safely supporting the imposed dead and live loads.
<input type="checkbox"/>	304.5 - Foundation walls - Foundation walls shall be maintained plumb and free from cracks and breaks and shall be kept in such condition so as to prevent the entry of rodents and other pests.
<input checked="" type="checkbox"/>	304.6 - Exterior walls - Exterior walls shall be free from holes, breaks and loose or rotting materials; and maintained weatherproof and properly surface coated where required to prevent deterioration.
<input checked="" type="checkbox"/>	304.7 - Roofs and drainage - The roof and flashing shall be sound, tight and not have defects that admit rain. Drainage must prevent dampness or deterioration in the walls or interior portion of the structure. Drains, gutters and downspouts must be in good repair and free from obstruction. Roof water shall not be discharged in a manner that creates a public nuisance.
<input type="checkbox"/>	304.8 - Decorative features - Cornices, belt courses, corbels, terra cotta trim, wall facing and similar decorative features shall be in good repair with proper anchorage and in safe condition.
<input type="checkbox"/>	304.9 - Overhang extensions - Overhang extensions including canopies, marquees, signs, metal awnings, fire escapes, standpipes and exhaust ducts shall be in good repair and properly anchored and kept in sound condition. All exposed surfaces of metal or wood shall be protected from the elements with weather coating material such as paint or similar surface treatment.
<input type="checkbox"/>	304.10 - Stairways, decks, porches and balconies - Every exterior stairway, deck, porch and balcony shall be structurally sound, in good repair, with proper anchorage and capable of supporting the imposed loads.
<input type="checkbox"/>	304.11 - Chimneys and towers - Chimneys, cooling towers, smoke stacks, shall be structurally safe and sound and in good repair. Exposed surfaces shall be protected by paint or similar surface treatment.
<input type="checkbox"/>	304.12 - Handrails and guards - Every handrail and guard shall be firmly fastened and capable of supporting normally imposed loads and shall be maintained in good condition.
<input checked="" type="checkbox"/>	304.13 - Window, skylight and door frames - Every window, skylight, door and frame shall be kept in sound condition, good repair and weather tight.
<input checked="" type="checkbox"/>	304.13.1 - Glazing - Glazing materials shall be maintained free from cracks or holes.



304.13.2 - Openable windows - Every window, other than a fixed window, shall be easily openable and capable of being held in position by window hardware.

304.14 - Insect screens - Every door, window and other outside opening required for ventilation or food preparation areas shall have tightly fitting screens of minimum 16 mesh per inch and every screen door must have self closing device is good working condition.

304.15 - Doors - Exterior doors and hardware shall be maintained in good condition. Locks at all entrances to dwelling units and sleeping units shall tightly secure the door.

304.18 - Building security - Doors, windows or hatchways for dwelling units, room units or housekeeping units shall be provided with devices designed to provide security for the occupants and property within.

304.18.1 - Doors - Doors providing access to a dwelling unit, rooming unit or housekeeping unit that is rented, leased or let shall have a dead bolt designed to open from the inside without a key.

304.18.2 - Windows - Operable windows located within 6 ft. above the ground that provides access to a dwelling unit, rooming unit or housekeeping unit that is rented, leased or let shall be equipped with a window sash locking device.

304.19 - Gates - Exterior gates, gate assemblies, operator systems and hardware shall be maintained in good condition.

Comments

Section 305 - Interior Structure

305.1 - General - The interior of a structure and equipment shall be maintained in good repair, structurally sound and in a sanitary condition.

305.1.1 - Unsafe conditions - The following conditions shall be determined as unsafe and shall be repaired or replaced to comply with the IBC or the IEBD as required for existing buildings.

1. The nominal strength of any structural member is exceeded by nominal loads, the load effects or the required strength.

2. The anchorage of the floor or roof to walls or columns, and walls and columns to foundations is not capable of resisting all nominal loads or load effects.

3. Structures or components thereof that have reached their limit state.

4. Structural members are incapable of supporting nominal loads and load effects.

5. Stairs, landings, balconies, including guards and handrails, are not structurally sound, not properly anchored or are anchored with connections not capable of supporting all nominal loads and resisting all load effects.

6. Foundation systems that are not firmly supported by footings are not plumb and free from open cracks and breaks, are not properly anchored or are not capable of supporting all nominal loads and resisting all load effects.

305.2 - Structural members - Structural members shall be maintained structurally sound, and capable of supporting the imposed loads.

305.3 - Interior surfaces - Interior surfaces, including windows and doors, shall be maintained in good, clean and sanitary condition.

Peeling, chipping, flaking or abraded paint shall be repaired, removed or covered. Cracked plaster, decaying wood and other defective surface conditions shall be corrected.

305.4 - Stairs and walking surfaces - Every stair, ramp, landing, balcony, porch, deck or other waling surface shall be maintained in sound condition and good repair.

305.5 - Handrails and guards - Every handrail and guard shall be firmly fastened and capable of supporting normally imposed loads and shall be maintained in good condition.

305.6 - Interior doors - Every interior door shall fit reasonably well within its frame and shall be capable of being opened and closed by being properly and securely attached to jambs, headers or tracks as intended by the manufacturer.

Comments

Section 306 - Component Serviceability



<input checked="" type="checkbox"/>	306.1 - General - The components of a structure and equipment therein shall be maintained in good repair, structurally sound and in a sanitary condition.
<input checked="" type="checkbox"/>	306.1.1 Unsafe Conditions - Where any of the following conditions cause the component or system to be beyond its limit state, the component or system shall be determined as unsafe and shall be repaired or replaced to comply with the IBC or the IEBC as required for existing buildings.
<input type="checkbox"/>	1. Soils that have been subjected to any of the following conditions:
<input type="checkbox"/>	1.1 Collapse of footing or foundation.
<input type="checkbox"/>	1.2 Damage to footing, foundation, concrete or other structural element due to soil expansion
<input type="checkbox"/>	1.3 Adverse effects to the design strength of footing, foundation concrete or other structural element due to a chemical reaction from the soil.
<input type="checkbox"/>	1.4 Inadequate soil as determined by a geotechnical investigation.
<input type="checkbox"/>	1.5 Where the allowable bearing capacity of the soil is in doubt.
<input type="checkbox"/>	1.6 Adverse effects to the footing, foundation, concrete or other structural element due to the ground water table.
<input type="checkbox"/>	2. Concrete that has been subjected to any of the following conditions:
<input type="checkbox"/>	2.1 Deterioration
<input type="checkbox"/>	2.2 Ultimate deformation
<input type="checkbox"/>	2.3 Fractures
<input type="checkbox"/>	2.4 Fissures
<input type="checkbox"/>	2.5 Spalling
<input type="checkbox"/>	2.6 Exposed reinforcement
<input type="checkbox"/>	2.7 Detached, dislodged or failing connections
<input type="checkbox"/>	3. Aluminum that has been subjected to any of the following conditions:
<input type="checkbox"/>	3.1 Deterioration
<input type="checkbox"/>	3.2 Corrosion
<input type="checkbox"/>	3.3 Elastic deformation
<input type="checkbox"/>	3.4 Ultimate deformation
<input type="checkbox"/>	3.5 Stress or strain cracks
<input type="checkbox"/>	3.6 Joint fatigue



3.7 Detached, dislodged or failing connections

4. Masonry that has been subjected to any of the following:

4.1 Deterioration

4.2 Ultimate deformation

4.3 Fractures in masonry or mortar joints

4.4 Fissures in masonry or mortar joints

4.5 Spalling

4.6 Exposed reinforcement

4.7 Detached, dislodged or failing connections

5. Steel that has been subjected to any of the following conditions:

5.1 Deterioration

5.2 Elastic deformation

5.3 Ultimate deformation

5.4 Metal fatigue

5.5 Detached, dislodged or failing connections

6. Wood that has been subjected to any of the following conditions:

6.1 Ultimate deformation

6.2 Deterioration

6.3 Damage from insects, rodents and other vermin

6.4 Fire damage beyond charring

6.5 Significant splits and checks

6.6 Horizontal shear cracks

6.7 Vertical shear cracks

6.8 Inadequate support

6.9 Detached, dislodged or failing connections

6.10 Excessive cutting and notching

Comments

Section 307 - Handrails and guardrails

Section 308 - Rubbish and garbage

Section 309 - Pest Elimination

Section 404 - Occupancy Limits

Section 502 - Required facilities

Section 503 - Toilet Rooms

Section 504 - Plumbing systems and fixtures



- 504.1 General - Plumbing fixtures shall be properly installed and maintained in working order and shall be kept free from obstructions, leaks and defects and be maintained in a safe, sanitary and functional condition.
- 504.2 Fixture clearances - Plumbing fixtures shall have adequate clearances for usage and cleaning.
- 504.3 Plumbing system hazards - Where it is found that a plumbing system in a structure constitutes a hazard due to inadequate service, venting, cross connection, backsiphonage, improper installation, deterioration or damage, they must be corrected.

Comments

Section 505 - Water system

Section 506 - Sanitary drainage system

- 506.1 General - Plumbing fixtures shall be properly connected to either a public sewer system or to an approved private sewage disposal system.
- 506.2 Maintenance - Every plumbing stack, vent, waste and sewer line shall function properly and be kept free from obstructions, leaks and defects.
- 506.3 Grease interceptors - Grease interceptors and automatic grease removal devices shall be maintained in accordance with this code and the manufacturer's installation instructions. Grease interceptors and automatic grease removal devices shall be regularly serviced and cleaned to prevent the discharge of oil, grease, and other substances harmful or hazardous to the building drainage system, the public sewer, the private sewage disposal system or the sewage treatment plant or processes. Records of maintenance, cleaning and repairs shall be available for inspection by the code official.

Comments

Section 507 - Storm drainage

Section 601 - Mechanical - General

Section 602 - Heating facilities

Section 603 - Mechanical equipment

Section 604 - Electrical Facilities

- 604.1 Facilities required - Every occupied building shall be provided with an electrical system in compliance with the requirements of this section and Section 605.
- 604.2 Service - Dwelling units shall be served by a three-wire, 120/240 volt, single phase service with a minimum of 60 amps.
- 604.3 Electrical system hazards - Where it found that the electrical system in a structure constitutes a hazard t the occupants or has inadequate service, improper fusing, insufficient receptacle and lighting outlets, improper wiring or installation, deterioration or damage, the code official shall require the defects to be corrected to eliminate the hazard.
 - 604.3.1.1 - Electrical distribution equipment, motor circuits, power equipment, transformers, wire cable, flexible cords, wiring devices, ground fault circuit interrupters, surge protectors, molded case circuit breakers, low voltage fuses, luminaires, ballasts, motors, electronic control, signaling and communication equipment that were exposed to water shall be replaced.
 - 604.3.2.1 - Electric switches, receptacles and fixtures, including furnace, water heating, security system and power distribution circuits that have been exposed to fire shall be replaced.

Comments

Section 605 - Electrical equipment

Section 606 - Elevators, escalators and dumbwaiters

Section 607 - Duct systems

Section 701 - General fire safety requirements

Section 702 - Means of egress

Section 703 - Fire resistance ratings

Section 704 - Fire protection systems



- | | |
|-------------------------------------|--|
| <input type="checkbox"/> | 704.1 Inspection, testing and maintenance - Fire detection systems shall be maintained in accordance with the IFC in an operative condition at all times, and shall be replaced or repaired where defective. |
| <input type="checkbox"/> | 704.1.1 - Fire protection and life safety systems - Fire protection systems shall be installed, repaired, operated and maintained in accordance with this code and the IFC and IBC. |
| <input type="checkbox"/> | 704.1.2 - Required fire protection systems - Fire protection systems required by this code, the IFC or the IBC shall be installed, repaired, operated tested and maintained in accordance with this code. |
| <input type="checkbox"/> | 704.1.3 Fire Protection systems - Fire protection systems shall be inspected, maintained and tested in accordance with the IFC requirements. |
| <input type="checkbox"/> | 704.2 Standards - Fire protection systems shall be inspected, tested and maintained in accordance with the referenced standards listed in Table 7042 and as required by this section. |
| <input type="checkbox"/> | 704.2.1 Records - Records shall be maintained of all systems inspections, tests and maintenance required by the referenced standards. |
| <input type="checkbox"/> | 704.4 Removal of or tampering with equipment - It shall be unlawful for any person to remove, tamper with or otherwise disturb any fire protection or life safety system required by this code except for extinguishing fire, training, recharging or repairs. |
| <input type="checkbox"/> | 704.4.1 Removal of or tampering with appurtenances - Locks, gates, doors, barricades, chains, enclosures, signs, tags and seals that have been installed by or at the direction of the fire code official shall not be removed, unlocked, destroyed or tampered with in any manner. |
| <input type="checkbox"/> | 704.5 Fire department connection - where the fire department connection isn ot visible to approaching fire apparatus, the fire department connection shall be indicated by an approved sign mounted on the street front or on the side of the building, subject to approval by the fire code official. |
| <input type="checkbox"/> | 704.5.1 Fire department connection access - Ready access to fire department connections shall be maintained at all times without obstruction by fences, bushes, trees, walls or any other fixed or removable object. |
| <input type="checkbox"/> | 704.6 Single and multiple station smoke alarms - Single- and multiple-station smoke alarms shall be installed in Group I-1 and R occupancies in accordance with Sections 704.6.1 through 704.6.3 |
| <input checked="" type="checkbox"/> | 704.6.1 Where required - Existing Group I-1 and R occupancies shall be provided with single-station smoke alarms in accordane with Sections 704.6.1.1 through 704.6.1.4. Interconnection and power sources shall be in accordance with Sections 704.6.2 and 704.6.3. |
| <input type="checkbox"/> | 704.6.1.1 Group R-1 - Single or Multi-station smoke alarms shall be installed in all of the following locations in Group R-1: 1 - Sleeping areas; 2 - In every room in the path of the means of egress from the sleeping area to the door leading from the sleeping unit; 3 - In each story within the sleeping unit, including basement. For sleeping units with split levels and without an intervening door between the adjacent levels, a smoke alarm installed on the upper level shall suffice for the adjacent lower level provided that the lower level is less than one full story below the upper level |
| <input checked="" type="checkbox"/> | 704.6.1.2 Groups R-2, R-3, R-4 and I-1 - Single or multi-station alarms shall be installed and maintained in Groups R-2, R-3, R-4 and I-1 regardless of occupant load at all of the following locations: 1 - On the ceiling or wall outside of each separate sleeping area in the immediate vicinity of bedrooms; 2 - In each room used for sleeping purposes; 3 - In each story within a dwelling unit, including basements but not including crawl spaces and uninhabitable attics. In dwellings or dwelling units with split levels and without an intervening door between the adjacent levels, a smoke alarm installed on the upper level shall suffice for the adjacent lower level provided that the lower level is less than one full story below the upper level. |
| <input type="checkbox"/> | 704.6.1.3 Installation near cooking appliances - Smoke alarms shall not be installed in the following locations unless this would prevent placement of a smoke alarm in a location required by Section 704.2.1.1 or 704.2.1.2:
1 - Ionization smoke alarms shall not be installed less than 20' horizontally from a permanently installed cooking appliance; 2 - Ionization smoke alarms with an alarm silencing switch shall not be installed less than 10' horizontally from a permanently installed cooking appliance; 3 - Photoelectric smoke alarms shall not be installed less than 6' horizontally from a permanently installed cooking appliance. |



- 704.6.2 Interconnection - Where more than one smoke alarm is required to be installed within an individual dwelling or sleeping unit, the smoke alarms shall be interconnected in such a manner that the activation of one alarm will activate all of the alarms in the individual unit. The alarm shall be clearly audible in all bedrooms over background noise levels with all intervening doors closed.
- 704.6.3 Power source - Single station smoke alarms shall receive their primary power from the building wiring provided that such wiring is served from a commercial source and shall be equipped with a battery backup. Smoke alarms with integral strobes that are not equipped with battery backup shall be connected to an emergency electrical system. Smoke alarms shall emit a signal when the batteries are low. Wiring shall be permanent and without a disconnecting switch.
- 704.6.4 Smoke detection system - Smoke detectors listed in accordance with UL 268 and provided as part of the building's fire alarm system shall be an acceptable alternative to single or multi station smoke alarms and shall comply with the following: 1 - The fire alarm system shall comply with all applicable requirements in Section 907 of the IFC; Activation of a smoke detector in a dwelling or sleeping unit shall initiate alarm notification in the dwelling or sleeping unit in accordance with Section 907.5.2 of the IFC; 3 - Activation of a smoke detector in a dwelling or sleeping unit shall not activate alarm notification appliances outside of the dwelling or sleeping unit, provided that a supervisory signal is generated and monitored in accordance with Section 907.6.5 of the IFC.

- 704.7 Single- and multiple-station smoke alarms - Single- and multiple-station smoke alarms shall be tested and maintained in accordance with the manufacturer's instructions. Smoke alarms that do not function shall be replaced. Smoke alarms installed in one- and two-family dwellings shall be replaced not more than 10 years from the date of manufacture marked on the unit, or shall be replaced in the date of manufacture cannot be determined.
- 705.1 General - Carbon monoxide alarms shall be installed in dwellings in accordance with Section 1103.9 of the IFC, except that alarms in dwellings covered by the IRC shall be installed in accordance with Section R315 of that code.
- 705.2 Carbon monoxide alarms and detectors - Carbon monoxide alarms and detection systems shall be maintained in accordance with NFPA 720. Carbon monoxide alarms and detectors that become inoperable or being producing end-of-life signals shall be replaced.

Comments

Additional Comments

Property Identification

Site Address: 505 N 6th ST
Sec/Town/Range: 10/35S/40E
Parcel ID: 2403-705-0140-000-0
Jurisdiction: Fort Pierce

Use Type: 0100
Account #: 16036
Map ID: 24/10N
Zoning: General Co

Ownership

Barbara Nowell
Willie Nowell
505 N 6th St
Fort Pierce, FL 34950

Legal Description

ASSESSOR'S MAP OF N PART OF FORT PIERCE BLK 16-K- S 1/2 OF LOTS 16, 18 AND 20 (MAP 24/10C) (OR 2654-232; 2982-892)

Current Values

Just/Market Value: \$29,900
Assessed Value: \$19,501
Exemptions: \$19,501
Taxable Value: \$0



Property taxes are subject to change upon change of ownership.

- Past taxes are not a reliable projection of future taxes.
- The sale of a property will prompt the removal of all exemptions, assessment caps, and special classifications.

Taxes for this parcel: [SLC Tax Collector's Office](#)
Download TRIM for this parcel: [Download PDF](#)

Total Areas

Finished/Under Air (SF): 1,050
Gross Sketched Area (SF): 2,058
Land Size (acres): 0.17
Land Size (SF): 7,500

Building Design Wind Speed

Occupancy Category	I	II	III & IV
Speed	140	160	160

Sources/links:

Shaun Coss

From: Nick Mimms
Sent: Monday, November 8, 2021 2:20 PM
To: Shaun Coss
Cc: Paul Thomas; Karen Murphy; Curtis Johnson
Subject: Re: 505 N 6th St.

Shaun,

Good Afternoon!!

Thank you for this excellent response and the informational update. Please assist this property owner as much as possible.

Nicholas C. Mimms, P.E., ICMA-CM
City Manager
The Beautiful City of Fort Pierce

From: Curtis Johnson <cjohnson@cityoffortpierces.com>
Sent: Monday, November 8, 2021 2:11 PM
To: Shaun Coss; Nick Mimms
Cc: Paul Thomas; Karen Murphy
Subject: Re: 505 N 6th St.

Contact for this property is Barbara Bell 772-332-6432

Curtis Johnson, Jr., MBA, | City Commissioner | City of Fort Pierce
Phone: [772.467.3065](tel:772.467.3065) Fax: [772.467.3841](tel:772.467.3841) 100 North U.S. 1 Fort Pierce, FL 34950

[Website](#) | [Facebook](#) | [Survey](#)

"To provide community leadership, quality public service, and a safe environment for all citizens, by an empowered team of employees motivated by pride in themselves and their work."

From: Shaun Coss <scoss@cityoffortpierces.com>
Sent: Monday, November 8, 2021 1:48:15 PM
To: Nick Mimms <nmimms@cityoffortpierces.com>
Cc: Paul Thomas <pthomas@cityoffortpierces.com>; Karen Murphy <kmurphy@cityoffortpierces.com>; Curtis Johnson <cjohnson@cityoffortpierces.com>
Subject: RE: 505 N 6th St.

Good afternoon Mr. Mimms,

I have performed an inspection of this home; due to the extent of damage it will be condemned. However, this home is a contributing structure within the Lincoln Park Historic District and could be a great candidate for a complete restoration. I have reached out to our Historic Preservation Officer and our Grants Administration Department to see if any funding or programs are available. I have attempted to contact the owner, Mrs. Nowell, but her voicemail is full. I will continue to contact her and provide her with the information I receive.

Best regards,

Shaun Coss, CFM | Building Department Coordinator | City of Fort Pierce
Building Department
Phone: (772) 467-3187, Fax: (772) 467-3849, 100 North U.S. 1 Fort Pierce, FL 34950

[Website](#) | [Facebook](#) | [Survey](#)



"To provide community leadership, quality public service, and a safe environment for all citizens, by an empowered team of employees motivated by pride in themselves and their work."

From: Nick Mimms <nmimms@cityoffortpierces.com>
Sent: Monday, November 8, 2021 9:11 AM
To: Shaun Coss <scoss@cityoffortpierces.com>
Cc: Paul Thomas <pthomas@cityoffortpierces.com>; Karen Murphy <kmurphy@cityoffortpierces.com>; Curtis Johnson <cjohnson@cityoffortpierces.com>
Subject: Re: 505 N 6th St.

Shaun,

Good Morning!!

Thank you for researching this matter. Please perform an inspection and work with the property owner to rehabilitate this property.

Have a Spectacular Day!!!

Nicholas C. Mimms, P.E., ICMA-CM
City Manager
The Beautiful City of Fort Pierce

From: Shaun Coss <scoss@cityoffortpierces.com>
Sent: Monday, November 8, 2021 9:07 AM
To: Nick Mimms
Cc: Paul Thomas; Karen Murphy
Subject: 505 N 6th St.

Good morning Mr. Mimms,

We do not have any records of a fire occurring at 505 N 6th St. I'll have this property investigated today and will report my findings once the investigation is complete.

Best regards,

Shaun Coss, CFM | Building Department Coordinator | City of Fort Pierce

Building Department

Phone: (772) 467-3187, Fax: (772) 467-3849, 100 North U.S. 1 Fort Pierce, FL 34950

[Website](#) | [Facebook](#) | [Survey](#)



"To provide community leadership, quality public service, and a safe environment for all citizens, by an empowered team of employees motivated by pride in themselves and their work."