



SITE PLAN - NTS

SIGN SCHEDULE:

A	D/F PYLON SIGN	717.76 SQ. FT.
B	INT. ILLUM. CHANNEL LOGO & LETTERS	1237.00 SQ. FT.
C	INT. ILLUM. CHANNEL LOGO & LETTERS	403.86 SQ. FT.
D	INT. ILLUM. COFFEE MATE SIGN	238.71 SQ. FT.
E	D/F INT. ILLUM. TOTEM	75.00 SQ. FT.
F	D/F INT-ILLUM. TOTEM DIR'L.	18.00 SQ. FT.
G	D/F INT-ILLUM. TOTEM DIR'L.	18.00 SQ. FT.
H	D/F INT-ILLUM. TOTEM DIR'L.	19.00 SQ. FT.
I	D/F INT-ILLUM. TOTEM DIR'L.	27.00 SQ. FT.

GENERAL NOTES

- INSTALLER SHALL VERIFY WALL CONDITIONS IN THE FIELD
- TYPE, SIZE & QTY. OF FASTENERS TBD
- ALL BOLT HOLES TO BE DRILLED OR PUNCHED
- ISOLATE ALL ALUMINUM FROM STEEL

NEW & REMODEL CONSTRUCTION
ADEQUATE BEHIND THE WALL BACKING AND ACCESS IS REQUIRED FOR THE INSTALLATION OF NEW SIGNAGE. CUSTOMER TO FORWARD APPROVED SIGNAGE DRAWINGS TO THE ON SITE CONTACT TO INSURE THAT THE REQUIRED PROVISIONS ARE MADE DURING CONSTRUCTION. PRIOR TO THE SIGN INSTALLATION.

INSTALLER REQUIREMENTS FOR EIFS WALLS
IT IS THE RESPONSIBILITY OF THE INSTALLATION CONTRACTOR TO PROVIDE ANY WALL SPACERS REQUIRED TO KEEP EIFS WALL MATERIAL FROM BEING COMPACTED DURING INSTALLATION OF ANY MOUNTING BOLTS REQUIRED FOR SIGNAGE.

INSTALLER REQUIREMENTS
ALL INSTALLATION (MOUNTING) HARDWARE AND SECONDARY WIRING COMPONENTS, CONDUIT & CONNECTORS, ETC ARE TO BE PROVIDED BY THE INSTALLATION CONTRACTOR

ALL WALL PENETRATIONS TO BE SEALED WITH SILICONE TO HELP PREVENT MOISTURE PENETRATION @ EXTERIOR LOCATIONS.

ANY DEVIATION FROM FEDERAL HEALTH REQUIREMENTS MAY RESULT IN DAMAGE TO OR IMPROPER OPERATION OF SIGNAGE, CAUSING DELAYS AND ADDITIONAL COSTS.

CUSTOMER TO PROVIDE DEDICATED BRANCH CIRCUITS FOR SIGNS ONLY PER NEC CODE 600.5

ALL BRANCH CIRCUITS FOR SIGNS MUST BE TOTALLY DEDICATED TO SIGNS (INCLUDING DEDICATED GROUND & NEUTRAL, PER CIRCUIT) AND SHALL NOT BE SHARED WITH OTHER LOADS (SUCH AS LIGHTING, A/C and OTHER EQUIPMENT). PROPERLY SIZED GROUND WIRE THAT CAN BE TRACED BACK TO THE BREAKER PANEL IS REQUIRED.

NUMBER AND SIZE OF CIRCUITS FOR EACH SIGN MUST MEET FEDERAL HEALTH SIGN REQUIREMENTS.

ALL ELECTRICAL SIGNS SHALL CONFORM TO THE REQUIREMENTS OF ARTICLE 600 OF THE N.E.C. AND U.L. 48 ALONG WITH OTHER APPLICABLE STATE & LOCAL CODE REQUIREMENTS. THIS INCLUDES PROPER GROUNDING AND BONDING OF THE SIGN

120V - 20 AMP (PRIMARY ELECTRICAL SERVICE) CIRCUITS AND FINAL CONNECTION TO EACH SIGN, TO WITHIN 6 FT TO BE BY THE CUSTOMER'S CERTIFIED ELECTRICIAN. NUMBER AND SIZE OF CIRCUITS FOR EACH SIGN TO MEET FEDERAL HEALTH SIGN COMPANY REQUIREMENTS

WARRANTY NOTICE

CERTAIN ELECTRICAL COMPONENTS OF SIGNS WILL FAIL PREMATURELY IF NOT SHUT OFF FOR A PERIOD OF TIME, ONCE EACH DAY. FOR BEST PERFORMANCE WE RECOMMEND THAT SIGNS BE CONNECTED TO AN AUTOMATIC CONTROLLING DEVICE SUCH AS AN EMERGENCY MANAGEMENT SYSTEM, TIME CLOCK OR PHOTO CELL TO CONTROL THE DAILY SHUT-OFF PERIOD. FAILURE TO FOLLOW THESE RECOMMENDATIONS CAN CAUSE DAMAGE TO ELECTRICAL COMPONENTS OF THE SIGN AND VOID THE WARRANTY. SOME DIMMING DEVICES WILL ADVERSELY AFFECT THE ELECTRICAL COMPONENTS OF THE SIGN IT IS ATTACHED TO, CAUSING FAILURE. ANY DIMMING OF THE SIGN WITHOUT CONSULTATION WITH FEDERAL HEALTH SIGN CO. WILL VOID THE WARRANTY.



VISUAL COMMUNICATIONS
www.FederalHeath.com

3609 Ocean Ranch Blvd., Ste 204 Oceanside, Ca 92056
(760) 901-7447 Fax (760) 757-2279

Building Quality Signage Since 1901

Revisions: R1 BW 2.10.22 Increase size & change color of B & C, revise copy on signs C, D, E & H.
R2 BW 2.16.22 Revise address, reduce height of E, F & G & revise copy on sign H.
R3 10.24.22 GB Rev E, F, G & H to Non-Illuminated
R4 JG 11.4.22 Update A to 100' oah scaled to match
R5 1.19.23 GB Rev All Color Specs; Add Coffee Mate @ A & C
R6 2.1.23 GB Rev C & D location, update elev. Del. D/Opt. 2
R7 2.8.23 BW Complete re-design of pylon sign A.
Colors Depicted in This Rendering May Not Match Actual Finished Materials. Refer To Product Samples For Exact Color Match.
R8 2.17.23 GB Rev Signs F, G, H, & I to Internally Illuminated.
R9 3.13.23 BW Add size options for pylon sign A.
R10 4.17.23 GB Del. Sign A Opts 1, 2 & 4; Add 70' Flagging Photos
R11 6.14.23 BW Revise poles on sign A & add cladding.
R12 6.15.23 BW Revise overall length of building elevations.
R13 6.20.23 BW Add tagline to pylon sign A.
R14 8.4.23 JC Delete tagline from pylon sign A. Make pole cladding solid. Lower height to 63' oah. R15 8.23.23 BW Rev OAH of A to 69'.

Client Approval/Date: _____

Landlord Approval/Date: _____

Account Rep: Steve Emery
Project Manager: Lynn Anderson
Drawn By: Gene Bourbonnais

Underwriters Laboratories Inc. nfc
ELECTRICAL TO USE U.L. LISTED COMPONENTS AND SHALL MEET ALL N.E.C. STANDARDS
ALL ELECTRICAL SIGNS ARE TO COMPLY WITH U.L. 48 AND ARTICLE 600 OF THE N.E.C. STANDARDS, INCLUDING THE PROPER GROUNDING AND BONDING OF ALL SIGNS.

Project / Location:



8351 N. 150th Avenue
Glendale, AZ

Job Number: 29-13133-00
Date: 03 February 2022
Sheet Number: 1 Of 18
Design Number: 29-13133-00 R15a

This original drawing is provided as part of a planned project and is not to be exhibited, copied or reproduced without the written permission of Federal Heath Sign Company, LLC or its authorized agent. ©FHSC