

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

Description

FLOOR COVERING, TRIM Aluminum
CLAMPS, HEATER HOSE Constant Torque for Heater System
FAN, DEFOG FAR RIGHT (01) Mounted Right Above Windshield, Forward Entrance Door, 2-Speed Switch in Panel
FAN, DEFOG RIGHT CENTER 6.50" Diam., Mounted Over Windshield, 15" Right of Centerline, 2-Speed Switch in Panel
FILTER, HEATER AIR, DRIVER Heater, Conventional
FILTER, HEATER AIR, LEFT REAR For Passenger Heater, 50,000 BTU
HEATER, DRIVER 90,000 BTU, and Defroster Hot Water Type

Includes

: CLAMPS, HEATER HOSE Mubea Constant Tension Clamps
: HEATER HOSES Premium
HEATER, PASS, LT REAR 50,000 BTU
HEATER, WATER PUMP (2MPU 12) Self Priming, With Plastic Housing
HEATER CUT OFF, VALVE Ball, With Butterfly Handle
HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Forward of Driver Heater
ROOF VENT, FRONT Static
SEAT BELT, DRIVER 3 Point, With Adjustable D-Loop, With Suspension Seat
NUTS, BELT MOUNTING Standard Nuts For Seat Belt Mounting
UPHOLSTERY, DRIVER SEAT, STYLE Plain, With Cloth Insert
UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Gray
UPHOLSTERY, PASS SEATS, COLOR Gray, for Seats, Barriers and Head Bumpers
UPHOLSTERY, DRIVER SEAT, TYPE Vinyl, 42 oz.
HAND RAIL, ENTRANCE DOOR, AFT Stainless Steel, 4", Above Step
SEAT CLIPS Positive Type
CUSHION, SEAT 15" Depth
UPHOLSTERY, SEAT, STITCHING Single
SEAT, DRIVER (National 2000) Air Suspension, High Back With Integral Headrest, Cloth, Isolated, With 2 Position Front Cushion
Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes Additional Back Padding For School Bus Use
UPHOLSTERY, PASS SEATS, TYPE Vinyl, 42 Ounce
ANCHOR, SEATS To Make Seat Belt Ready, (01-02)
LIGHT, ENTRY DOOR Light Mounted in Skirt Behind Entrance Door, Wired To Step Light
LIGHTS, BACK UP (2) 7" Diameter, Clear
LIGHTS, TAIL, LICENSE PLATE (2) 4" Red With Light Window
LIGHTS, MARKER, SIDE (Truck Lite) Amber, Intermediate, Centered, Light Emitting Diode Type; Required for Units 30 Foot or Longer
LIGHT, STROBE, REAR Low Profile, Self Contained, Double Flash 2nd Section from Rear
WIRE, FEED 4 Gauge, Chassis To Body
SWITCH, DRIVER PANEL, TYPE Rocker
ALARM, BACKING (Ecco #575) 107 db
SWITCH, REAR DOOR BUZZER Rear Door With Knob, for State of Texas
CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses

Includes

: ACCESS PANEL for Body and Chassis Fuses/Circuit Breakers Located on Body Exterior; Below Driver Window
SWITCH, MAGNETIC, DISCONNECT Master, Ignition Operated, All Body Circuits
SOURCE, POWER 12 Volt DC, Mounted On Dash
LIGHT, DRIVER Mounted in Wiring Access Panel Left of Driver, Switch Located in Switch Panel
LIGHTS, DOME Conventional; Two Full Rows Rectangular Recessed Dome Lights, 31'2", 31'11", 32'8", 33' 5", 34'2", 34'11", Body Length
SWITCH, DOME LIGHTS, RHEOSTAT For All Dome Lights
LIGHT, STEP Wired to Clearance Lights
LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection
LIGHTS, CLUSTER Recessed in Cap; Amber in Front and Red in Rear
FLASHER SYSTEM Omit; To be Used for Multi Functional School Activity Bus or Commercial Models Only, Non Route Use
LIGHTS, STOP (2) (Sound Off ECV7561SST) and Tail; 7", LED, Red
LIGHTS, DIRECTIONAL, REAR (2) (Sound Off ECV7561ITY) LED, 7" Amber
LIGHTS, MARKER, FRONT, REAR (Sound Off ECVML153Y&R) LED, Armored, (8) Four Amber Front and Four Red Rear
KIT, FIRST AID Plastic; 24 Unit, Spec State
MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners
MIRROR, REAR VIEW, EXTERIOR (Rosco) Suspended, Black, With Breakaway Bracket, Motorized Head
VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield
KIT, BODY FLUID Texas

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

WINDSHIELD WIPERS (2) Cowl Mounted
LOCATION, FIRST AID KIT Right Side Front Bulkhead With Screws
FIRE EXTINGUISHER, DRIVER AREA 5 lb 2A-40BC Minimum With Flexible Hose and Metal Nozzle
SAFETY TRIANGLES 1 Kit; Warning Reflectors, Mounted on Floor Between Driver Seat and Drivers Crash Barrier/Stanchion
REFLECTORS, SIDE, INTERMEDIATE (2) 3" Amber, 1 Each Side, Mounted With Screws, Below The Third Rub Rail From the Top
REFLECTORS, SIDE, REAR (2) 3", Red, Mounted With Screws
REFLECTORS, SIDE, FRONT (2) 3", Amber; 1 Aft Drivers Window Left, 1 Aft Entrance Door Right, Mounted With Screws
REFLECTORS, REAR (2) 3", Red, Mounted With Screws
FUEL FILLER DOOR With Locking Latch
INSPECTION PLATE 5" Dia. Steel
WINDSHIELD WASHER Kit; 6 Quart Capacity, Bottle

Includes

: WINDSHIELD WASHER ELECTRICAL CONNECTIONS Sealed and Locking Type
MIRROR, BRACE, EXTERIOR Telescoping for Breakaway Bracket
STATE OF OPERATION Texas
COMMERCIAL BUS NOT FOR SCHOOLS - This Code Certifies that the Dealer has Verified with the Purchaser that this Bus will Not Be Used for the Transportation of Passengers by Daycare Facilities, Preprimary, Primary or Secondary Schools to or from School or School-Related Activities
(2) TIRE, FRONT 11R22.5 AH12 (HANKOOK) 503 rev/mile, load range H, 16 ply
(4) TIRE, REAR 11R22.5 AH12 (HANKOOK) 503 rev/mile, load range H, 16 ply
SEAT, PASS, LEFT, 2 LEG, 30" OMIT SEAT, PASS, LEFT, 2 LEG, 30"
BODY PLAN, NON-SPECIAL NEEDS USE BODY PLAN Ihorn506
GRILLE omit chrome grille 009had use standard painted white
MISCELLANEOUS 47ATE second partion for rear per body plan Ihorn 506

Services Section:

SERVICES, TOWING To 24-Month/Unlimited Mileage; Service Call to the Vehicle or Towing to the Nearest International Dealership for a Non-Driveable Unit in Conjunction with an International Warrantable Failure; \$250 (USA) Maximum Benefit per Incident
WARRANTY 5-Year, Limited

1) Install QTY 2 Standard Seat, 4 Leg, 26" RH with 42oz vinyl, single stitch, no welt upholstery and with lap seat belt. 090120-02

Air conditioning 126K btu

1) Install Polar latches with Master Series #5 lock to 2 individual cages.

745778-090126-01

Install Lexan Shields to front and rear partitions.

AMA chad

Install 7 LH 8 RH Freedman Prison Seat, 35 DBL, Wall Mount, w/shackle rings, FWD Facing. .

1 RH Freedman Seat, 35 DBL, Floor Mount, w/shackle rings, inboard Facing.

2 LH Seat, 17.5 Single, Wall Mount, w/shackle rings, FWD Facing.

BSC 090203

1) Install Fixed Exterior window screens over 13LH and 13 RH window sections, 2 rear quarter glass, and top rear emergency door glass. BSC 090202-01

1) Install interior window screens for 2 LH single seat cages.

The interior screens will be mounted to the cage walls.

BSC 090120-04

1) Install two Individual Single Occupancy, Wire Mesh, Caged Compartments with Outward Opening Swing Doors.

Note: Requires Freedman Citi-Seat, Single Forward Facing. BSC-090114-04

Graphics Package per SAL Graphics

INSTALL 2 BIG SKY GUN rack with Handcuff Keys

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

Install Gun Safe

VSL total emergency light system, 3 camera inside with DVD, siren, rear camera
(reviewed by HCSD)

rear step aftermarket for rear door access

Financial Summary
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

<u>Description</u>	<u>(USA DOLLAR)</u>	<u>Price</u>
Net Sales Price:		\$273,552.00
Memo Item(s):		
Warranty:	\$0.00	
Note: Memo item(s) shown here are included in the above Net Sales Price.		

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an IC Corporation vehicle.

Approved by Seller:

Accepted by Purchaser:

Official Title and Date

Firm or Business Name

Authorized Signature

Authorized Signature and Date

LONGHORN BUS SALES
6921 HOMESTEAD ROAD
HOUSTON TX 77028 -
(713)631-9306

**This proposal is not binding upon the seller without
Seller's Authorized Signature**

Official Title and Date

March 16, 2009

Prepared For:
Hidalgo County Sheriff
Richard Ozuna
711 W El Cibolo Rd.
Edinburg, TX 78541-9848
(956)393 - 6022
Reference ID: N/A

Presented By:
LONGHORN BUS SALES
James Connell
6921 HOMESTEAD ROAD
HOUSTON TX 77028 -
(713)631-9306

Thank you for the opportunity to provide you with the following quotation on a new IC Corporation vehicle. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2010 INTEGRATED CE C BUS (PC105)

MISSION:	Requested GVWR: 26500. Calc. GVWR: 29800 Calc. Start / Grade Ability: 23.10% / 2.21% @ 55 MPH Calc. Geared Speed: 85.3 MPH
FUEL ECONOMY:	9.94 MPG @ 55 MPH
DIMENSION:	Wheelbase: 193.00, CA: N/A, Axle to Frame: 114.00
ENGINE, DIESEL:	{International MaxxForce 7} 215 HP @ 2600 RPM, 560 lb-ft Torque @ 1400 RPM, 2800 RPM Governed Speed, 215 Peak HP (Max)
TRANSMISSION, AUTOMATIC:	{Allison 2500_PTS} 4th Generation Controls; Wide Ratio, 5-Speed, With Overdrive; Less PTO Provision, Less Retarder, With 33,000-lb GVW & GCW Max. School Bus
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{International I-100SG} I-Beam Type, 10,000-lb Capacity
AXLE, REAR, SINGLE:	{Dana Spicer 19060S} Single Reduction, 19,800-lb Capacity, With 190 Wheel Ends, Gear Ratio: 5.29
TIRE, FRONT:	(2) 11R22.5 AH12 (HANKOOK) 503 rev/mile, load range H, 16 ply
TIRE, REAR:	(4) 11R22.5 AH12 (HANKOOK) 503 rev/mile, load range H, 16 ply
SUSPENSION, RR, SPRING, SINGLE:	Two Stage, Vari-Rate; 19,800-lb Capacity
PAINT:	Cab schematic 100NB Location 1: 9219, Winter White (Std) Chassis schematic N/A

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

Base Chassis, Model INTEGRATED CE C BUS with 193.00 Wheelbase, N/A CA, and 114.00 Axle to Frame.

TOW HOOK, FRONT (2) Inside Rail, Frame Mounted.

FRAME RAILS High Strength Low Alloy Steel (50,000 PSI Yield); 10.125" x 3.062" x 0.312" (257.2mm x 77.8mm x 8.0mm);
471.1" (11965mm) Maximum OAL

Includes

: CHASSIS PAINT Chassis Painted Prior to Body Mounting

: FRAME RAILS All holes Laser Aligned and Machine Punched, Powder Coated Prior to Full Assembly, Assembled in Fixture using "Grade 8" Bolts

: FRAME REINFORCEMENT, SPECIAL 3.30" x 1.80" x 0.312" x 31.50" Inverted "L" in Front Shock Absorber Mounting Area

BUMPER, FRONT Full Width, Aerodynamic, Heavy Duty, Steel

Includes

: BUMPER, FRONT THICKNESS 1/4 Inch

CROSSMEMBER, REAR, AF (01)

WHEELBASE RANGE 193" (490cm) Through and Including 217" (550cm)

AXLE, FRONT NON-DRIVING {International I-100SG} I-Beam Type, 10,000-lb Capacity

Includes

: AXLE, FRONT SQUARING to Plus or Minus .015 Inch, using a Special Fixture to Assure Parallelism of Springs

SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 10,000-lb Capacity; With Shock Absorbers

Includes

: SPRING PINS 1" Diameter Bolt and Nut Type

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE CHAMBERS, SPRING (2) Rear Parking

: BRAKE LINES Color and Size Coded Nylon

: DRAIN VALVE Twist-Type

: DUST SHIELDS, FRONT BRAKE

: DUST SHIELDS, REAR BRAKE

: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster

: INVERSION VALVE and Double Check Valve

: PARKING BRAKE VALVE Controlled by Yellow Knob, Located on Instrument Panel

: SLACK ADJUSTERS, FRONT Automatic

: SLACK ADJUSTERS, REAR Automatic

DRAIN VALVE, AUTOMATIC {Bendix DV-2} With Heater; for Air Tank

AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel)

AIR DRYER {Bendix AD-9} With Heater

BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. MGM Long Stroke Brake Chambers

BRAKES, REAR, AIR CAM 16.5" x 7.0"; Includes MGM TR3030 Long Stroke Brake Chamber and Heavy Duty Spring Actuated Parking Brake

AIR COMPRESSOR {Bendix Tu-Flo 550} 13.2 CFM Capacity

STEERING COLUMN Tilting

STEERING WHEEL 2-Spoke, 18" Diam., Black

STEERING GEAR {TRW (Ross) TAS-66} Power

EXHAUST SYSTEM Single, Horizontal Aftertreatment Device Frame Mounted Right Side, Includes Long Horizontal Tail Pipe

Includes

: PLEASE NOTE: The Horizontal Tailpipe Includes a Temperature Control Device

TAIL PIPE Long Horizontal, Exits Right Side Through Bumper

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: FUSES, ELECTRICAL SAE Blade-Type

: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: MISCELLANEOUS FEATURES Modular, Loom Protected, Grommets in all Applicable Body Openings, Assembled in Computer Assisted Fixture which Verifies Continuity and Correct Assembly Prior to Installation

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: TURN SIGNAL FLASHER

: TURN SIGNAL SWITCH Self-Cancelling with Lane Change Feature

: TURN SIGNALS, FRONT Includes Reflectors; Flush Mounted

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
: WIRING, CHASSIS Color Coded and Continuously Numbered
HORN, ELECTRIC (2)
ALTERNATOR {Leece-Neveille 4949PA} Brush Type; 12 Volt 270 Amp. Capacity, Pad Mounted
BATTERY SYSTEM {International} Maintenance-Free, (3) 12-Volt 1950CCA Total
HEADLIGHTS Halogen; Composite Aero Design for Two Light System; Includes Daytime Running Lights
FOG LIGHTS (2) Clear, Oval, With H355W Halogen Bulb
LIGHTS TURN ADDITIONAL Amber, Mounted at Rear of Front Fender
INDICATOR, LOW COOLANT LEVEL With Audible Alarm
STARTING MOTOR {Delco Remy 29MT} 12 Volt; Less Thermal Over-Crank Protection, With Integrated Magnetic Switch
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses
HOOD TILT ASSIST {EASY TILT} Mechanical
FRONT END Tilting, Fiberglass, With Three Piece Construction

Includes

: AIR INTAKE SYSTEM Integrated Pre-Cleaning System to Enhance Air Filter Life
: GRILLE Removable; Fiberglass Painted Hood Color
: SPLASH SHIELD Integral with Front End Assembly
CHASSIS PAINT Full Chassis
PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "NB"
PAINT TYPE Urethane, One or Two Colors, Other than Imron or International.
CLUTCH Omit Item (Clutch & Control)
ENGINE, DIESEL {International MaxxForce 7} 215 HP @ 2600 RPM, 560 lb-ft Torque @ 1400 RPM, 2800 RPM Governed Speed, 215 Peak HP (Max)

Includes

: AIR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated
: ENGINE OIL DRAIN PLUG Magnetic
: ENGINE SHUTDOWN Electric, Key Operated
: FUEL FILTER Engine Mounted
: FUEL HEATER Included with Fuel/Water Separator
: FUEL/WATER SEPARATOR Engine Mounted
: GLOW PLUG Automatic with Indicator Light
: OIL FILTER, ENGINE Spin-On Type
FAN DRIVE {Borg-Warner Series 790} Viscous Screw On Type

Includes

: FAN Nylon
THROTTLE, HAND CONTROL Electronic
RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 717 SqIn Louvered, With 313 SqIn Charge Air Cooler. With In-Tank Transmission Cooler

Includes

: ANTI-FREEZE Red Shell Rotella Extended Life Coolant -40F (-40C)
: DEAERATION SYSTEM with Surge Tank
: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps
: RADIATOR HOSES Premium, Rubber
AIR CLEANER Single Element

Includes

: AIR CLEANER with Vacuator
: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted
CRUISE CONTROL Electronic
GOVERNOR Electronic Road Speed Type; for International Electronic Engines and Bus Models; With 55 MPH Default
ENGINE SOUND ABATEMENT PACKAGE Exterior, for International Engines With Underhood Blanket and Foam Covered Splash Shields.
EMISSION COMPLIANCE Engine Shutdown System Exempt Vehicles, Complies With California Clean Air Regulations
TRANSMISSION, AUTOMATIC {Allison 2500_PTS} 4th Generation Controls; Wide Ratio, 5-Speed, With Overdrive; Less PTO Provision, Less Retarder, With 33,000-lb GVW & GCW Max. School Bus

Includes

: OIL FILTER, TRANSMISSION Mounted on Transmission
: TRANSMISSION OIL PAN Magnet in Oil Pan

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

TRANSMISSION OIL Synthetic; 20 thru 28 Pints

AXLE, REAR, SINGLE {Dana Spicer 19060S} Single Reduction, 19,800-lb Capacity, With 190 Wheel Ends, . Gear Ratio: 5.29

Includes

: REAR AXLE DRAIN PLUG (1) Magnetic, For Single Rear Axle

SUSPENSION, RR, SPRING, SINGLE Two Stage, Vari-Rate; 19,800-lb Capacity

SHOCK ABSORBERS, REAR (2)

FUEL TANK Top Draw; Rectangular Steel, 65 U.S. Gal., 246 L With Protective Cage, Mounted Right Side

COWL Flat Back

GAUGE CLUSTER English With English Electronic Speedometer

Includes

: GAUGE CLUSTER (5) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter

: ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout

: WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)

GAUGE, OIL TEMP, ALLISON TRAN

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

WHEELS, FRONT DISC; 22.5" Painted Steel, 2 Hand Hole, 10 Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs.

Includes

: PAINT IDENTITY, FRONT WHEELS Black

: WHEEL SEALS, FRONT Grease Lubricated, Includes Wheel Bearings

WHEELS, REAR DUAL DISC; 22.5" Painted Steel, 2 Hand Hole, 10-Stub (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs

Includes

: PAINT IDENTITY, REAR WHEELS Black

: WHEEL SEALS, REAR Oil Lubricated, Includes Wheel Bearings

WHEEL SEALS, FRONT {International} Oil-Lubricated Wheel Bearings

BODY, BUS Conventional; 78" Headroom, 23'8" Body Length, +9 Section Front, 47 Passenger, 193 WB

Includes

: HEADER BUMPER Padded, Mounted Over All Doors; Upholstered to Match Passenger Seat Color

BODY CERTIFICATION TAG Metal

BODY TAG, METAL

STEP, FRONT ENTRANCE DOOR 27 1/4" Depth; 14ga Steel

Includes

: STEP, FRONT ENTRANCE DOOR OPENING, 35 Inch Width; Continuous Bottom to Top

SWITCH, LOCATION Omit; To be used for Multi Functional School Activity Bus or Commercial Models Only, Non Route Use

HEADLINER, BODY Conventional; 16'02"-25'02" Body Length, Perforated Full Length With Sound Insulation Full Length

STEP RISER, SLIDING DOOR (4) for Prison Bus Partition Sliding Door

FASTENERS, HEADLINER Screws

BOWS, ROOF 14 ga., One Piece Construction

LIGHT BARS Plastic

SKIRT, BODY for Conventional, 14 1/2", 16ga

Includes

: SKIRT, BODY Extra Smooth Steel Supported by Floor Gussets

PARTITION, BODY Wire Mesh; (01) Prison Bus, Includes Sliding Door and Lock

TIE DOWNS, BODY Grade 8 Bolts, Every Body Section

Includes

: TIE DOWNS, BODY with Formed Tab that Fits into Floor Structure to Prevent Turning

RUB RAILS, BODY (4) Conventional; Steel, 22'2", 22'11", 23'8", 24'5" Body Length, Includes Snow Rail

Includes

: RUB RAILS Full Length, Primer Coated (Both Sides), Attached to Body without Cuts or Splices

BODY, REAR Includes Emergency Door

SIDE SHEET, BODY, EXTERIOR Conventional, 16ga., Smooth, 22'2", 22'11", 23'8", 24'5", Body Length

FLOOR, BODY With Wheel Wells

SUPPORTS, REAR BUMPER Bolted to Frame

BUMPER, REAR Painted; 12" High, 3/16" Thick, With 7" Hole for Exhaust

TOW HOOK, LEFT REAR (01)

TOW HOOK, RIGHT REAR (01)

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

LINING, SIDE INTERIOR, LOWER Embossed Steel, Clear Coated
HANDLE, ASSIST, OVER WINDSHLD Body Color
CONTROL, ENTRANCE DOOR Manual Pull Type, Black
COVER, REAR DOOR INSIDE HANDLE Partial Coverage
FASTENERS, REAR DOOR Bolts and Nutserts, Rear Door To Body
DOOR, ENTRANCE, FRONT Manual, Outward Opening, With Split Pane Glass

Includes

: DOOR, ENTRANCE, FRONT Aluminum Frame with Pin Style Hinges, Ball Bearing Assisted, Interchangeable Top and Bottom Glass
HANDLE, ASSIST, ENTRANCE DOOR Outside Entrance
HOLD BACK, REAR DOOR Stationary, No Cables, With Plastic Cover
LATCH, REAR DOOR One Point Slide Bar, Cam Operated, With One Inch Stroke
LOCK, VANDAL, ENTRANCE DOOR for Manual, Electric Control, With Key Switch
LOCK, VANDAL, REAR DOOR With Ignition Starter Interlock
COMPARTMENT, BATTERY Mounted Behind Left Front Wheel Pocket, 13" x 15" x 25.5"

Includes

: BATTERY TRAY 14-1/2" x 24-3/4" Slide Out Tray with Nylon Rollers and Stops
: DOOR - COMPARTMENT with Pin Style Hinge
HOLD DOWN, BATTERY For (2) Standard Size Batteries
NOISE REDUCTION, DRIVER FLOOR Insulation Covering Complete Driver Floor Area
NOISE REDUCTION, ROOF BOW Conventional; Insulation, 22'2", 22'11", 23'8", 24'5" Body Lengths
INSULATION, ROOF AND SIDES 1.50", All Models
UNDERCOAT, FLOOR/STEPWLL/SIDES for Engine Noise Reduction
UNDERCOAT, BODY Fire Resistant, Water Based, TT-C-730 Spec
LETTERS, DOOR, REAR Decals; "EMERGENCY DOOR", 2" Black Letters Inside and Outside
ARROW, RR DOOR, INSIDE Decal; Black, .75" Stroke, Indicating Handle Direction
STRIPING, PERIMETER, REAR Emergency Door; White, Reflective
WIRING DIAGRAM Schematic, Electrical
LETTERS, HEADER Decal; "WATCH YOUR STEP", 1" Black, Above Windshield
LETTERS, STEPWELL Decal, "WATCH YOUR STEP", 2.5" Black, Behind Door on Step Riser
MONITOR, POST TRIP INSPECTION Omit
PAINT RUB RAILS 9219 Winter White
LETTERS, FUEL I.D. Paint; "DIESEL FUEL", 2" Black, Adjacent to Fuel Filler Door
PAINT HOOD AND FENDER 9219 Winter White
PAINT COLOR, BODY EXTERIOR 9219 Winter White
PAINT COLOR, BUMPER Rear; 0001 Canyon Black
PAINT, RUB RAIL Flange to Flange
PAINT COLOR, BODY INTERIOR 9384 Spring White
HANDLE, EXTERIOR, REAR Emergency Door; White
OPERATING INSTR, REAR Decal, Inside Rear Emergency Door
LOGO, ROOF LINE Decal; "IC CORPORATION", Wing and Shield, Above First Passenger Window Both Sides
PAINT FLASHER BACKGRD To Match Body Color
SUB FLOOR, PLYWOOD Conventional; B-B Marine Grade, Less Sealed Edges, 5/8", 5 Ply, for 22'2", 22'11", 23'8" or 24'5" Body Lengths
WINDOW, DRIVER Laminated, Clear
WINDOW, STOPS 12" Opening, Only With 78" Headroom
WINDOW, SASH (26) 27" Sections, 9"x 23" Opening
COLOR, WINDOW FRAME, PASS Passenger Window, Natural Aluminum Finish
WINDOW, PASSENGER, TINT Clear, Tempered Glass
SHIELD, COURTESY, AFT/DRIVER Padded, 36", Mounted Under Stanchion
SHIELD, COURTESY, AFT ENTR DR Padded, 30", Mounted Under Stanchion
STANCHION, AFT DRIVER Stainless Steel, 36"
STANCHION, AFT ENTRANCE DOOR Stainless Steel, 30"
WHEEL POCKET COVER Plastic, ABS
AISLE POSITION Center, for balanced seating
WINDSHIELD 3 Flat Pieces, 73% Light
FLOOR COVERING, COLOR Black
SEAT BACK, PASSENGER Standard Back
FLOOR COVERING, TYPE {IC Corporation} Rubber, All Body Lengths
STEP TREADS {IC Corporation} Rubber, With White Nosing

Vehicle Specifications
2010 INTEGRATED CE C BUS (PC105)

March 16, 2009

Description

FLOOR COVERING, TRIM Aluminum
CLAMPS, HEATER HOSE Constant Torque for Heater System
FAN, DEFOG FAR RIGHT (01) Mounted Right Above Windshield, Forward Entrance Door, 2-Speed Switch in Panel
FAN, DEFOG RIGHT CENTER 6.50" Diam., Mounted Over Windshield, 15" Right of Centerline, 2-Speed Switch in Panel
FILTER, HEATER AIR, DRIVER Heater, Conventional
FILTER, HEATER AIR, LEFT REAR For Passenger Heater, 50,000 BTU
HEATER, DRIVER 90,000 BTU, and Defroster Hot Water Type

Includes

: CLAMPS, HEATER HOSE Mubea Constant Tension Clamps
: HEATER HOSES Premium
HEATER, PASS, LT REAR 50,000 BTU
HEATER, WATER PUMP (2MPU 12) Self Priming, With Plastic Housing
HEATER CUT OFF, VALVE Ball, With Butterfly Handle
HEATER CUT OFF, VALVE INSIDE Brass Ball, Inside Forward of Driver Heater
ROOF VENT, FRONT Static
SEAT BELT, DRIVER 3 Point, With Adjustable D-Loop, With Suspension Seat
NUTS, BELT MOUNTING Standard Nuts For Seat Belt Mounting
UPHOLSTERY, DRIVER SEAT, STYLE Plain, With Cloth Insert
UPHOLSTERY, DRIVER SEAT, COLOR Drivers Seat, Gray
UPHOLSTERY, PASS SEATS, COLOR Gray, for Seats, Barriers and Head Bumpers
UPHOLSTERY, DRIVER SEAT, TYPE Vinyl, 42 oz.
UPHOLSTERY, BARRIER, TYPE (1-2) Prevaill, 42 oz.
BARRIER, CRASH, LT, 1ST Position; 30", 1 Leg
PANEL, MODESTY, LT 1ST POS Mounted Under Barrier
HAND RAIL, ENTRANCE DOOR, AFT Stainless Steel, 4", Above Step
SEAT CLIPS Positive Type
CUSHION, SEAT 15" Depth
UPHOLSTERY, SEAT, STITCHING Single
SEAT, DRIVER {National 2000} Air Suspension, High Back With Integral Headrest, Cloth, Isolated, With 2 Position Front Cushion Adjustment, 6 to 17 Degree Seat Back Adjustment, Mechanical Lumbar Support, Includes Additional Back Padding For School Bus Use
LIGHT, ENTRY DOOR Light Mounted in Skirt Behind Entrance Door, Wired To Step Light
LIGHTS, BACK UP (2) 7" Diameter, Clear
LIGHTS, DIRECTIONAL, REAR (2) 7" Amber, Without Arrow
LIGHTS, TAIL, LICENSE PLATE (2) 4" Red With Light Window
LIGHTS, MARKER, FRONT, REAR (4) Two Amber Front and Two Red Rear, Armor Type Single 1500 Hour 2cp Bulb Each Light
LIGHTS, STOP (2) and Tail, 7" dia., Red
LIGHT, STROBE, REAR Low Profile, Self Contained, Double Flash 2nd Section from Rear
WIRE, FEED 4 Gauge, Chassis To Body
SWITCH, DRIVER PANEL, TYPE Rocker
ALARM, BACKING {Ecco #575} 107 db
SWITCH, REAR DOOR BUZZER Rear Door With Knob, for State of Texas
CIRCUIT, PROTECTION Breakers, Manual Reset in Lieu of Fuses

Includes

: ACCESS PANEL for Body and Chassis Fuses/Circuit Breakers Located on Body Exterior; Below Driver Window
SWITCH, MAGNETIC, DISCONNECT Master, Ignition Operated, All Body Circuits
SOURCE, POWER 12 Volt DC, Mounted On Dash
LIGHT, DRIVER Mounted in Wiring Access Panel Left of Driver, Switch Located in Switch Panel
LIGHTS, DOME Conventional; Two Full Rows Rectangular Recessed Dome Lights, 22'2", 22'11", 23'8", 24' 5" Body Length
SWITCH, DOME LIGHTS, RHEOSTAT For All Dome Lights
LIGHT, STEP Wired to Clearance Lights
LIGHT, EXTERIOR, CHECK Automatically Activates Lights for Pre Trip Inspection
LIGHTS, CLUSTER Recessed in Cap; Amber in Front and Red in Rear
FLASHER SYSTEM Omit; To be Used for Multi Functional School Activity Bus or Commercial Models Only, Non Route Use
LIGHTS, MARKER, SIDE Intermediate, Single Bulb, Centered, 3cp, 1500 HR Bulb, Required for Units 30 Foot or Longer
KIT, FIRST AID Plastic; 24 Unit, Spec State
MIRROR, INSIDE 6" x 30", Clear Safety Glass, Metal Back, Round Corners
MIRROR, REAR VIEW, EXTERIOR {Rosco} Suspended, Black, With Breakaway Bracket, Motorized Head
VISOR, INTERIOR, LEFT FRONT 6" x 30", Transparent, For Left Windshield