

## FORM 213 - Resource Request

<b>1. Incident Name</b>	COVID-19				
<b>2. To</b>	RICARDO SALDANA, EMC				
<b>3. From</b>	MONICA HINOJOSA, EMERGENCY MANAGAEMENT EXT 5021				
<b>4. Message:</b>	Emergency Purchase Notification	<b>5. Date</b>	08/21/20	<b>6. Time</b>	0800 HRS

**7. State the reason for your emergency request**


Requesting purchase of a a mobile command unit to maintain communication and information management capabilities in response to COVID operations. Operational needs for a command unit include but not limited to operations such as testing sites, food distrubtions and community assitance.

**8. List and describe the items and quantities (supplies/resources) being requested to procure**

(1) MOBILE COMMAND CENTER  
 \$410,715.00  
  
 REQ # 419920

*APPROVED*

**9. Acknowledged by**

<b>Name</b>	RICARDO SALDANA
<b>Signature</b>	
<b>Position/Title</b>	EMERGENCY MANAGEMENT COORDINATOR
<b>Date</b>	08/24/20





180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 767-2529  
Direct: +1 (262) 763-0147  
[www.ldvusa.com](http://www.ldvusa.com)

**PRODUCTION  
SPECIFICATIONS FOR:**

**HILDAGO COUNTY (TX)  
MOBILE COMMAND CENTER**

**LDV MODEL # 607303  
SS36FC1S-18SV**

**DATE  
AUGUST 18, 2020  
AUGUST 20, 2020 REV1**



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 767-2529  
Direct: +1 (262) 763-0147  
www.ldvusa.com

**TABLE OF CONTENTS**

CHASSIS: .....4

BODY: .....6

PAINT / GRAPHICS: .....8

DRIVER / PASSENGER CAB AREA: .....9

WALLS, CEILING AND FLOOR: .....9

GALLEY / LAVATORY: ..... 10

SEATING: ..... 10

CABINETS: ..... 10

HVAC SYSTEM: ..... 11

AC ELECTRICAL SYSTEM: ..... 11

DC ELECTRICAL SYSTEM: ..... 14

EMERGENCY LIGHTING / SIRENS: ..... 15

AUDIO / VIDEO: ..... 15

MAST AND MAST MOUNTED EQUIPMENT: ..... 17

RADIOS: ..... 17

COMPUTER NETWORK AND EQUIPMENT: ..... 17

MISCELLANEOUS ELECTRONICS: ..... 17

EXTERIOR STORAGE COMPARTMENTS: ..... 18

MISCELLANEOUS OTHER: ..... 18



180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 767-2529  
Direct: +1 (262) 763-0147  
www.ldvusa.com

**PRICING PAGE:**

HGAC discounted price \$409,715.00

LDV HGAC Contract # AM10-18

Contract Administration Fee - HGAC \$1,000.00

HGAC discounted price with Contract Admin Fees \$410,715.00

Delivery charge: Not included \$0.00

<b>Total price per unit</b>	<b>\$410,715.00</b>
-----------------------------	---------------------

Delivery terms: 100 DAYS AFTER RECEIPT OF PO

Payment Terms: Net 30

Quote is firm for 30 days from specification date.

Quoted price does not include any applicable FET, federal, state or local tax unless specified.



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
1.00		<p><b><u>CHASSIS/BODY DIMENSIONS:</u></b></p> <ul style="list-style-type: none"> <li>• 26' walk-in van</li> <li>• Wheelbase of chassis: 250"</li> <li>• Overall length of apparatus: 425"</li> <li>• Overall apparatus width, rub rail to rub rail: 96"</li> <li>• Overall height of apparatus (loaded): 134"</li> <li>• Interior walkway height raw body: 83"</li> <li>• Interior walkway height finished: 81.5"</li> <li>• Interior walkway length: 312"</li> <li>• Interior raw body width: 93"</li> <li>• Interior finished body width: 87"</li> </ul> <p>Final measurements are dependent on body builder, chassis components, axles, tires, frame, suspension, and roof-mounted equipment.</p>
2.00		<p><b><u>CHASSIS:</u></b></p>
2.01	1	<p>2020 Freightliner MT-55 forward control chassis. 26,000-lb GVWR with hydraulic brakes and air suspension</p> <p><b><u>ENGINE:</u></b></p> <ul style="list-style-type: none"> <li>• Cummins B6.7 260 HP @ 2400 RPM, 2600 GOV, 660 LB/FT @ 1600 RPM</li> <li>• 2008 CARB emission certification - clean idle</li> <li>• 12V 200 amp 28-SI Quadramount pad alternator</li> <li>• (2) model 1131, group 31, 12 volt maintenance free 1900 CCA threaded stud batteries</li> <li>• 18.7 CFM air compressor with internal safety valve</li> <li>• GVG, Fire and emergency service vehicles engine warning</li> <li>• Exhaust brake integral with variable geometry turbo with On/Off dash switch</li> <li>• Engine aftertreatment device, automatic over the road active regeneration and dash mounted single regeneration request/inhibit switch</li> <li>• 10 gallon DEF tank RH frame mtd</li> <li>• LH horizontal tailpipe, exit forward of rear tires</li> <li>• Antifreeze to -34F, OAT (nitrite &amp; silicate free) extended life coolant</li> <li>• Gates Blue Stripe coolant hoses or equivalent</li> <li>• 1000 watt/115 volt block heater</li> </ul> <p><b><u>TRANSMISSION:</u></b></p> <ul style="list-style-type: none"> <li>• Allison 2200 EVS automatic transmission with park pawl and PTO provision</li> <li>• Synthetic transmission fluid (TES-295 compliant)</li> </ul> <p><b><u>FRONT AXLE AND EQUIPMENT:</u></b></p> <ul style="list-style-type: none"> <li>• 10,000# single front axle</li> <li>• Front oil seals</li> <li>• Synthetic 75W-90 front axle lube</li> <li>• TRW TAS-65 power steering</li> </ul> <p><b><u>FRONT SUSPENSION:</u></b></p> <ul style="list-style-type: none"> <li>• 10,000# taperleaf front suspension</li> <li>• Front stabilizer bar</li> <li>• Front shock absorbers</li> </ul> <p><b><u>REAR AXLE AND EQUIPMENT:</u></b></p> <ul style="list-style-type: none"> <li>• 17,500# single rear axle</li> <li>• 5.13 rear axle ratio</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item Qty

- Synthetic 75W-90 rear axle lube
  - REAR SUSPENSION:**
    - 18,000# Airliner rear suspension
    - Manual dump valve for air suspension w/indicator light, w/o gauge
    - Dual instant response rear suspension leveling valves
    - Rear swaybar
    - Rear shock absorbers
  - BRAKE SYSTEM:**
    - Hydraulic brake package w/optional air supply
    - 4S/4M ABS without traction control
  - FRAME:**
    - 5/16" x 2.81" x 9-1/8" steel frame, 80ksi
  - FUEL TANKS:**
    - 60 gal. rectangular steel fuel tank - between rails
  - TIRES:**
    - Michelin XZE 255/70R22.5 16 ply radial front tires
    - Michelin XD2 255/70R22.5 16 ply radial rear tires
  - WHEELS:**
    - Maxion wheels 90262 22.5x8.25 10-hubpl 5-hand steel disc front wheels
    - Maxion wheels 90262 22.5x8.25 10-hubpl 5-hand steel disc rear wheels
  - CAB EXTERIOR:**
    - Dual electric horns
    - Daytime running lights
  - CAB INTERIOR:**
    - Compact air conditioner compressor
    - Auto self-reset circuit breakers and fuses
    - Tilt / telescopic steering column with foot actuated pedal
  - INSTRUMENTS & CONTROLS:**
    - Green gauge backlighting
    - Driver message center W/LCD display, 24 warning lamps, data linked, AMI
    - Electronic MPH speedometer with secondary KPH scale, without odometer
    - Electronic 3500 RPM tachometer
    - Electric engine oil pressure gauge w/warning lamp and alarm
    - Electric engine coolant Temp gauge w/warning lamp and alarm
    - Digital voltage display integral with driver display
    - Elec fuel gauge & low fuel indicator lamp
    - Automatic transmission oil temp gauge w/warning lamp
    - Engine hour meter, integral to message center LCD
    - Intake mounted air restriction indicator with graduations
    - 97 dB backup alarm
    - Cruise control switches
    - Programmable RPM ctrl w/low voltage auto high idle & RPM ctrl switches
    - Wagner 7212 turn signal flasher
- Note: chassis specifications are from freightliner custom chassis and are subject to change without notice.



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
2.02		<p><b>CHASSIS WARRANTY:</b></p> <ul style="list-style-type: none"> <li>• Three (3)-year/50,000 mile <i>Freightliner</i> MT-55 chassis warranty.</li> <li>• Three (3)-year/unlimited miles <i>Cummins</i> engine warranty.</li> <li>• Five (5)-year/unlimited miles <i>Allison EVS</i> transmission warranty.</li> </ul>
2.03	1	<p>Block heater shall be wired to AC electrical distribution.</p> <p><b>NOTE:</b> Button on Intel-I-Touch</p>
2.04	1	US DOT triangle reflector kit with three (3) triangles, for compliance with FMCSA regulations. Includes plastic storage case. Kit will be shipped loose in the vehicle.
2.05	1	Stainless steel wheel liners with braided stainless steel valve stem extenders.
3.00		<b>BODY:</b>
3.01	1	<p>Load space area shall be 83" high x 93" wide x 26' long all aluminum step van body.</p> <ul style="list-style-type: none"> <li>• Driver sedan door with slider window, door skin shall be chemically bonded to door frame structure reducing the amount of rivets required. Door shall have continuous stainless steel piano hinge and two (2) nylon straps.</li> <li>• Passenger sedan door with slider window, door skin shall be chemically bonded to door frame structure reducing the amount of rivets required. Door shall have continuous stainless steel piano hinge and two (2) nylon straps.</li> <li>• Sedan doors shall have a 0.125" aluminum tread plate step well for 18" skirt depth.</li> <li>• Sedan doors shall have black non-skid tape on all door entry sills.</li> <li>• Sedan doors shall have polished aluminum TriMark flush mounted locking hardware with self-aligning rotary latch and matching key locks. Outside door handles not to exceed 50" from ground.</li> <li>• Aluminum alloy double H wall beam, 6005-T5 alloy, 3" x 3" wide at the base, 1.5" wide at the top, 0.125 wall thickness. Studs feature machined wire pass-throughs, and raised adhesive control features on base.</li> <li>• I-beams shall be chemically bonded to sidewalls eliminating the need for additional rivets. Buck-rivets will be used to fasten the top, bottom and rub rail. Use of two-sided tape is not acceptable.</li> <li>• Body shall have 0.125" strain-hardened aluminum alloy 5052-H36 side panels. The upper panels shall be free of rivets allowing for smooth graphics application.</li> <li>• Skirt supports, 1.5 x 1.5 x 0.125 angle to reinforce skirt edge and hold bottom edge in a straight line. 0.188 x 1.00" flat braces placed at 4' intervals and riveted to lower wall angle and floor to maintain sidewall skirt rigidity.</li> <li>• Fender flares, 1.38" x 2.25" x 0.090" roll formed and radiused 5052-H32 aluminum sheet, mechanically fastened to wheel opening. Edges sealed against moisture.</li> <li>• NFPA 1901 embossed 0.125" aluminum tread plate roof attached to 3" x 1 1/2" x 0.125" extruded aluminum roof bows on 16" centers. Bows are 2" skip welded every 12". Tread plate seams shall be continuous welded. Perimeter of roof shall be chemically sealed.</li> <li>• Lift-up molded fiberglass hood with chrome grill insert. Hood shall have integrated headlamps and turn signal indicators and dual assist gas charged lift shocks. The use of mechanical assist springs is not acceptable.</li> <li>• Extruded aluminum floor with interlocking planks, 1.88" high x various widths, 0.125" top surface. 6005-T5 alloy and temper. Heavy-duty thick-wall extruded planks fore and aft of all</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
		<p>floor cutouts and every 5th plank in all other areas. Planks made of 6005-t5 alloy and temper, 0.250" thick top surface.</p> <ul style="list-style-type: none"> <li>• Bright polished front bumper.</li> <li>• Tinted safety plate glass windshield with driver and passenger sun visors.</li> <li>• Full width 12" deep heavy-duty aluminum rear bumper with center step, painted to match the body.</li> <li>• Integral cab air conditioning and heating system with dash controls.</li> <li>• <i>Velvac</i> heated remote control rear view mirrors with dash controls. Upper mirror has 62-sq.in. of flat surface and lower mirror has 30-sq.in. of convex surface. Mirror has a fold-away arm.</li> <li>• Driver seat shall be <i>Seats Inc.</i> Magnum 200 mechanical suspension seat on fixed pedestal. Seat shall be covered in black cloth and have arm rests, lumbar support, tilt back and 3-point seat belt.</li> <li>• Passenger seat to be a black vinyl jump seat with 2-point seat belt.</li> </ul> <p>Intermittent windshield wiper/washer with single heavy-duty windshield wiper motor.</p> <ul style="list-style-type: none"> <li>• Custom front wheel cutouts for tires.</li> <li>• Aluminum engine box cover with acoustical and thermal insulation. Black molded ABS composite engine box overlay.</li> <li>• Acoustical and thermal insulation with heat shield on exterior fire-wall.</li> <li>• Full length skirting. Skirt shall extend 18" down from the bottom of floor extrusions.</li> <li>• Dash shall be vacuum formed ABS composite with integrated control pod located left of dash.</li> <li>• All clearance and side marker lights to be LED.</li> <li>• Standard structural warranty of 5 years or 50,000 miles and standard component warranty of 12 months or 12,000 miles.</li> <li>• The vehicle shall be fully sanded on all exterior surfaces with no more than 150 grit to assure removal of imperfections in metal surface. All aluminum shall be chemically etched and primed prior to painting. Base body color shall be oven baked and painted to commercial truck standards.</li> </ul> <p><i>Note:</i> Specifications are from body manufacturer and are subject to change without notice.</p>
3.02	1	<p>32" wide x 82" high 0.125" aluminum sedan door with 21.5" wide x 25.5" high fixed window. Door shall have continuous stainless steel piano hinge, two (2) nylon door straps and an aluminum drip rail.</p> <p><b>NOTE:</b> Interior window covering will be a mini blind.</p>
3.03	3	Exterior heavy-duty fluted aluminum grab handle with rubber inserts and chrome plated stanchions installed at entry door.
3.04	1	Interior heavy-duty fluted aluminum grab handle with rubber inserts and chrome plated stanchions installed at entry door.
3.05	3	Automatic LED courtesy light at entry door.
3.06	1	Courtesy light defeat in Intel-I-Touch™ multiplex control screen. Each entry door courtesy light will be automatically deactivated where the corresponding room has the overhead lighting set to night mode.



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
3.07	1	<p>Lippert Treadlite 24" wide - single - automatic electric steel entry step with LED ground light. Step mounted under entry door.</p> <p><b>NOTE:</b> Step light will be tied into courtesy light defeat.</p>
3.08	1	<p>Lippert Treadlite 30" wide - single - automatic electric steel entry step with LED ground light. Step mounted under entry door.</p> <p><b>NOTE:</b> Step light will be tied into courtesy light defeat.</p>
3.09	1	<p>Whelen Stop/Turn/Tail/Backup light set. Includes two of each of the following:</p> <ul style="list-style-type: none"> <li>• Whelen M6FCV4 polished chrome vertical housings for four M6 series lighthoods. The fourth light head will be an emergency flasher as specified in the DC Emergency Lighting section.</li> <li>• Whelen M6 series LED arrow shaped amber turn signal, model number M6T.</li> <li>• Whelen M6 series LED brake/tail light heads, model number M6BTT.</li> <li>• Whelen M6 series LED back-up light heads, model number M6BUW.</li> </ul>
3.10	1	Entire underside shall be undercoated. Includes chassis, floor extrusions, step wells and aluminum compartments.
3.11	1	LDV rear mud flaps. Includes anti-sail brackets when required.
3.12	1	<p>Flat floor slide-out room extension fabricated with a structurally rigid welded aluminum tube design with a fully bonded aluminum shell. During deployment an electronic control system automatically expands the room extension and lowers the floor to flush position.</p> <p>Features:</p> <ul style="list-style-type: none"> <li>• Electric over hydraulic control system programmed to lower the slide out to floor height after full extension.</li> <li>• Awning that automatically extends and retracts over the top of the room to protect from weather and debris.</li> <li>• Full perimeter double rubber bulb seal with an additional seal in the fully extended and fully retracted positions.</li> <li>• No track or hardware shall be attached to the ceiling of the body.</li> </ul> <p><b>NOTE:</b> Slide out up to 98" length</p>
3.13		Ignition Interlock to prevent vehicle from starting when any of the external extension devices are deployed.
4.00		<b>PAINT / GRAPHICS:</b>
4.01		Body base color shall be white.
5.00		<p><b>INDEPENDENCE ONYX INTERIOR:</b></p> <ul style="list-style-type: none"> <li>• Wall Covering Front/Rear rooms: Chrome carpet</li> <li>• Wall Covering Middle room: Wilsonart laminate Satin Stainless 483</li> <li>• Bulkheads - Wilsonart laminate Satin Stainless 483</li> <li>• Control console cabinet – Black laminate</li> <li>• Ceiling: <ul style="list-style-type: none"> <li>◦ Center (ductwork) #HAT2-C0111 Charcoal Gray Texture Powder Coated</li> <li>◦ Outside Silver Mist carpet</li> </ul> </li> <li>• Trim: #HAT2-C0111 Charcoal Gray Texture Powder Coated</li> <li>• Floor Covering: #150 Onyx PVC Flooring</li> <li>• Office Chairs: Black</li> <li>• Cabinets: #HAT2-C0111 Charcoal Gray Texture Powder Coated Aluminum</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
		<ul style="list-style-type: none"> <li>• Powdercoat color for slideout valance and interior door panel               <ul style="list-style-type: none"> <li>◦ #HAT2-C0111 Charcoal Gray Texture Powder Coated</li> </ul> </li> <li>• Vinyl/fabric coverings:               <ul style="list-style-type: none"> <li>◦ Seat bottom to be stock Black Vinyl.</li> <li>◦ Seat back to be Ultraleather Dwell 570-5635 Basalt back</li> </ul> </li> <li>• Counters and Tables: #4879-38 Steel Mesh Laminate with GRAY T-molding</li> </ul> <p>Note: Manufacturer reserves the right to substitute equivalent materials.</p>
6.00		<b><u>DRIVER / PASSENGER CAB AREA:</u></b>
6.01	1	<ul style="list-style-type: none"> <li>• Walk-in van custom cab area finishing.</li> <li>• Cover cab doors with aluminum panels powder coated black.</li> <li>• Heavy-duty rubber grab handle on each door.</li> <li>• Panels covered with vinyl or fabric above driver and passenger doors.</li> <li>• Vehicle height sign on dash.</li> <li>• Insulated black rubber mat in driver and passenger toe plate area.</li> <li>• Insulate walls in kick plate area and install black carpeted panels.</li> <li>• Vehicle shall have a Final Stage Vehicle Certification and Altered Vehicle Certification as required by Federal Motor Vehicle Safety Standards (FMVSS) 49 CFR Part 567.5 and 567.7</li> <li>• Payload sticker in cab area with vehicle axle load ratings and available axle payload as built.</li> </ul>
6.02	1	Work area on passenger side covered with laminate to match rear countertops and trimmed with vinyl T-molding.
6.03	1	Custom fabricated console to house Intel-I-Touch™ Control electrical distribution components and control panels. Console shall be located in the overhead console above the windshield. The entire console shall be constructed of 3/4" plywood. The face shall be finished with laminate the bottom shall be covered with vinyl.
6.04	1	Red/Clear LED dome light with 3-position switch, red/off/white.
6.05	1	Zone Defense color back up camera system with 7" LCD monitor and day/night camera. Camera includes a microphone for audio commands from a spotter to the driver during backing operations.
6.06	1	AM/FM stereo with Bluetooth and one (1) pair of 6" x 9" speakers.
7.00		<b><u>WALLS, CEILING AND FLOOR:</u></b>
7.01		Insulate walls with a minimum of 2-1/2" of fiberglass insulation. Cover interior body side posts with 1/2" plywood sub wall.
7.02		Cover sub wall with Wilsonart laminate.
		<b>NOTE:</b> Galley
7.03		Cover sub wall with ribbed loop pile carpet.
		<b>NOTE:</b> Front/Rear rooms
7.04		<ul style="list-style-type: none"> <li>• Insulate ceiling with a minimum of 2-1/2" of fiberglass with an R-11 rating.</li> <li>• Cover interior roof beams with 1/2" plywood.</li> <li>• Modular panel design allows for manageable future additions and repairs.</li> <li>• Plywood Panels covered in acoustical fabric.</li> </ul>
7.05		Floor underlayment to be 5/8" exterior grade tongue and groove structural plywood, 6 ply, face veneer plugged and sanded.
7.06		Lonseal Loncoin II Flecks non-skid commercial grade PVC flooring. The flooring shall be continuous, one piece full length, full width, no seams.



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
7.07		Vinyl cove molding (mop board) at base of wall, 2-1/2" high. Installed where required.
7.08	1	Flush pocket door installed on heavy-duty aluminum track with two (2) four-wheel roller trucks. Pocket door shall have recessed handle and magnetic closure to keep the door open/closed.
7.09		All bulkheads shall be covered with Wilsonart laminate. Trim exposed edges of bulkheads with rounded anodized aluminum trim where applicable.
7.10	1	Cover load space door with powder coated aluminum panel with heavy-duty rubber grab handle.  <b>NOTE:</b> Interior window covering will be a mini blind. Powder coat color will be Gray color.
7.11	1	Hehr street side mounted 30" wide x 19" high flush mount deep-tint horizontal sliding egress window with screen.  <b>NOTE:</b> Interior window covering will be a mini blind.
8.00		<b><u>GALLEY / LAVATORY:</u></b>
8.01	1	GE 1.1 cu.ft. 1000-watt microwave oven. Model JES1145SHSS
8.02	1	Keurig Coffee maker.
8.03	1	Norcold NR751B AC and DC powered refrigerator with the following features: <ul style="list-style-type: none"> <li>• 2.7 cu. ft. capacity.</li> <li>• Freezer shelf for ice cube tray.</li> <li>• Door bin holds 2-liter containers.</li> <li>• Integrated door latch.</li> <li>• 120/230Vac 50/60 Hz and 12/24 Vdc</li> </ul> <b>NOTE:</b> Flush mount
9.00		<b><u>SEATING:</u></b>
9.01	7	Space Air Grid office chair 5560 black with armrests, five caster spider base, and adjustable height.  <b>NOTE:</b> One (1) per workstation and three (3) in front conference room.
9.02		Fabricate and install fixed bench seating with removable cushions as shown on drawing. Bench seat cushions shall be covered in heavy-duty vinyl.
9.03		Fabricate and install flip-down bench seating as shown on drawing. Bench seat cushions shall be covered in heavy-duty vinyl. Bottom seat cushion will be installed on Zico Quic-Seat® fold down spring loaded seat brackets.
9.04		<b><u>BENCH SEAT REQUIREMENTS:</u></b> <ul style="list-style-type: none"> <li>• Foam for seat backs and bottoms shall be firm density.</li> <li>• All bench seating material must meet Federal Motor Vehicle Safety Standards part 571.302 Flammability of Interior Materials.</li> <li>• Material corners shall be squared or angled to fit precise cut of foam.</li> <li>• Foam shall be bonded to plywood backer with industrial grade adhesive.</li> <li>• Attachment of fabric/vinyl to backer shall utilize industrial grade upholstery staples.</li> </ul>
10.00		<b><u>CABINETS:</u></b>
10.01		Custom fabricated aluminum cabinets located as shown on drawing. Cabinet specifications: <ul style="list-style-type: none"> <li>• Base cabinets constructed of 0.080" powder coated aluminum with anodized aluminum frames.</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
		<ul style="list-style-type: none"> <li>• Base cabinet doors are double shell, formed from a single sheet of 0.080" aluminum, with a 0.040" aluminum door back attached.</li> <li>• Overhead cabinets constructed of 0.064" powder coated aluminum with anodized aluminum frames.</li> <li>• Overhead cabinet doors are double shell, formed from a single sheet of 0.064" aluminum, with a 0.040" aluminum door back attached.</li> <li>• Overhead cabinet doors swing up.</li> </ul>
10.02	6	Dry erase writing surface on overhead cabinet door.
10.03	5	Gas spring lift supports on overhead cabinet door.
10.04	5	LED light under overhead cabinet.
10.05		Gusset support for counter top open areas.
10.06	2	Magnetic dry erase board framed in aluminum. Includes aluminum clip frame for easy board replacement, sized as required.
10.07		Countertops shall be covered in 0.040" <i>Wilsonart</i> laminate. All exposed edges shall be covered with heavy duty flexible PVC T-molding.
10.08		Conference table covered in 0.040" <i>Wilsonart</i> laminate. All exposed edges shall be covered with heavy duty flexible PVC T-molding.
10.09	1	Powder coated 0.125" aluminum conference table base.
10.10	1	Folding leaf for conference table.
11.00		<b><u>HVAC SYSTEM:</u></b>
11.01	1	<i>Fan-tastic</i> Vent model 1250 3-speed reversible 12" power roof ventilator.
11.02	3	Ducted Coleman Polar Mach 8 series low profile air conditioner with thermostat. Includes: <ul style="list-style-type: none"> <li>• High Capacity Air Duct manufactured from polystyrene foam laminated with 99% pure polished aluminum inside and out, internally mounted in ceiling</li> <li>• 13,500 nominal Btu/hr air conditioner with condensate pump.</li> <li>• Chill Grille Assembly with 6,000 Btu/hr heat strip</li> <li>• Wall mounted thermostat</li> <li>• Louvered Ceiling Vents, as required</li> </ul>
11.03	2	<i>Broan</i> model 174 wall mount 5,120 Btu/hr electric heater. Located as shown on drawing.
12.00		<b><u>AC ELECTRICAL SYSTEM:</u></b>
12.01	1	<i>Power Tech</i> 20-kW 120/240Vac liquid-cooled diesel generator with air bag mounts installed in a custom fabricated compartment. (17010049) Generator features: <ul style="list-style-type: none"> <li>• Tier 4F Emissions</li> <li>• USTC Certified Manufacturer</li> <li>• Warranty: 2 years from date of purchase, or 3000 hours whichever comes first, or 36 months from the date of manufacture.</li> <li>• Four point air bag mounting system</li> <li>• Four-cycle water cooled diesel engine</li> <li>• Radiator cooled, direct mounted</li> <li>• High-coolant temp and low oil pressure shutdown sensors</li> <li>• Spin-on fuel and oil filter</li> <li>• Single side service</li> <li>• Typical Gallon Per Hour fuel consumption: 25% load = 0.45, 50% load = 0.90, 100% load = 1.80</li> </ul> <p><b>NOTE:</b> Generator exhaust shall be routed to the street side of the vehicle.</p>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
12.02	1	<p><b>ACData</b> surge suppressor for protection of entire AC power system.</p> <p>Product features:</p> <ul style="list-style-type: none"> <li>• UL listed: UL1449 3rd Edition</li> <li>• LED visual verification of status</li> </ul>
12.03	1	<p>LDV exclusive Intel-I-Touch™ vehicle automation control system.</p> <p>A multiplexed vehicle automation system must be incorporated into a common touch screen(s) that is custom programmed to monitor and control onboard systems as described throughout the specifications. The automation system software must allow simultaneous distribution of information to multiple onboard control/monitoring stations and the software must be updateable and configurable as required. This system is mandatory as it simplifies start up procedures, contains fewer operating components, reduces operational start-up time, reduces the total amount of wiring in the vehicle and includes error detection protocols and troubleshooting features.</p> <p>Features include:</p> <ul style="list-style-type: none"> <li>• One (1) 10" LCD touch screen with custom graphics for control and monitoring systems</li> <li>• AC power distribution control and monitoring for the generator with power management</li> <li>• DC power distribution control and monitoring</li> <li>• Manual or automatic generator control</li> <li>• HVAC and temperature control.</li> <li>• Interior and exterior lighting control</li> <li>• Automatic power transfer switches</li> <li>• Automated startup and shutdown procedures</li> <li>• Seamless control of generators, lighting, awnings and additional devices</li> <li>• Mast control</li> <li>• Safety interlocks</li> </ul> <p>The system must be completely upgradeable with power modules located throughout vehicle. Additional components may be added to system with a simple software modification System capability is not to be achieved with use of multiple monitoring systems designed for specific use i.e. water monitors, battery monitors etc.</p>
12.04	1	<p>3" Touch panel for dedicated local control and monitoring of specific vehicle automation system features. Includes control layout and indicators where applicable.</p> <p><b>NOTE:</b> Exterior TV compartment</p>
12.05	1	<p>3" Touch panel with numeric display for dedicated local control and monitoring of specific vehicle automation system features including room HVAC. Display shows current room temperature and HVAC setpoint when adjusted. Includes control layout and indicators where applicable.</p> <p><b>NOTE:</b> Rear room</p>
12.06		<p><b>Night Time (Red) Lighting Mode</b> turns the ceiling lighting in each room from white to red lights.</p>
12.07		<p><b>Reduced Lighting Mode</b> is white ceiling lighting in each room have the option of All-On or Half-On.</p>
12.08	1	<p><i>Kussmaul</i> Auto Eject 20, 20A-120Vac shore power inlet with 25-ft. 20A-120Vac shore power cord. #091-20WP-120RD.</p>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
12.09	1	<p><i>Marinco</i> 50A-125/250Vac shore power package including:</p> <ul style="list-style-type: none"> <li>• Waterproof shore power inlet with cap</li> <li>• 50-ft. 50A-125/250Vac shore power cord</li> <li>• 6-ft. 50A-125/250Vac pigtail</li> </ul>
12.10	2	<p>20A-125Vac duplex receptacle. Receptacle is not dedicated to any installed equipment.</p> <p><b>NOTE:</b> One (1) Comms closet One (1) Electronics rack</p>
12.11	7	<p>20A-125Vac duplex receptacle with dual USB charging ports. Receptacle is not dedicated to any installed equipment.</p> <p><b>NOTE:</b> One (1) Per workstation [qty.4] Two (2) Conference table base One (1) Front passenger workstation</p>
12.12	1	<p>20A-125Vac GFCI duplex receptacle. These receptacles are not dedicated to any installed equipment.</p> <p><b>NOTE:</b> Galley</p>
12.13	2	<p>20A-125Vac exterior GFCI duplex receptacle.</p> <p><b>NOTE:</b> Receptacle will be installed with a weatherproof cover.</p>
12.14	1	<p>30A-120 Vac receptacle in electronics rack for future installed UPS.</p>
12.15		<p>Wire chase wire management raceway system located as shown on drawing. Product features:</p> <ul style="list-style-type: none"> <li>• Satin anodized finish. The finish resists rust, corrosion and fading. Material extruded from 6063-T5 aluminum alloy.</li> <li>• Removable dual cover. Makes wiring easy and accessible and provides maximum flexibility for adding or relocating outlets and circuits. The cover retention is 45 lbs. straight pull for one minute.</li> <li>• UL Listed multioutlet assemblies. File E68073 Guide PVGT, Fittings: File E121188 Guide RJPR. Meets Article 380 of NEC and meets Section 12-3032 of CEC.</li> <li>• UL and cUL Listed component raceways. File E73943 Guide RJBT, Fittings: File E74343 Guide RJPR. Meets Article 386 of NEC and meets Section 12-600 of CEC.</li> <li>• UL5 and ADA compliant. Raceway and fittings meet UL5 specifications and can be installed in conformance with ADA requirements</li> </ul>
12.16		<p><b><u>AC WIRING REQUIREMENTS:</u></b></p> <ul style="list-style-type: none"> <li>• All AC main wiring shall be stranded THHN wire and run in non-metallic <i>Carlton</i> Carflex liquid tight conduit.</li> <li>• All AC branch circuit wiring shall be stranded THHN wire (AWG 12 minimum) and run in non-metallic <i>Carlton</i> Carflex liquid tight and <i>Carlton</i> Flex-Plus blue ENT conduit.</li> <li>• All electrical circuits and appliances shall conform to applicable national electrical codes.</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
13.00		<b>DC ELECTRICAL SYSTEM:</b>
13.01	1	<ul style="list-style-type: none"> <li>• Six (6) Lead acid deep-cycle 6Vdc batteries. Batteries shall be installed underbody in slide out weather resistant compartment. Four (4) batteries will be separated for auxiliary equipment and two (2) batteries will be for communications equipment.</li> <li>• Three (3) electronic converter/chargers, 80 amp minimum output each.</li> </ul> Converter/charger features: <ul style="list-style-type: none"> <li>• Charges three banks of batteries at the same time.</li> <li>• UL listed for safety.</li> <li>• Manual reset circuit breaker.</li> <li>• Reverse battery protection.</li> <li>• Electronic current limiting.</li> <li>• High voltage protection.</li> </ul> <ul style="list-style-type: none"> <li>• All DC electrical and metering switched and monitored through the multiplex system.</li> </ul>
13.02	18	Light, Orion 6" LED, neutral white with polished bezel.
13.03	7	Light, Orion 6" LED, neutral white / red with polished bezel.
13.04	6	Whelen M6ZC Gradient LED Scene Light.  <b>NOTE:</b> Two (2) per side and two (2) rear
13.05		<b>12VDC WIRING REQUIREMENTS:</b> <ul style="list-style-type: none"> <li>• 2-gauge minimum copper stranded battery cable shall be used for 12Vdc main supply lines. All cable runs shall be full length, no splices. All cable terminals shall be staked and soldered. All cable shall be enclosed in convoluted polyethylene tubing and the ends of the cable shall be sealed with color-coded shrink-wrap identifying the function of the cable.</li> <li>• All added electrical branch circuits shall be protected from over-current by resettable circuit breakers appropriately rated for the load. Only circuit breakers shall be used in the installation of added electrical branch circuit wiring (plug type fuses are unacceptable).</li> <li>• Circuit breaker functions shall be identified by engraved or printed labels.</li> <li>• All added wiring for load runs of AWG 10, 12, 14, and 18, shall conform to MIL-W-16878/2 and/or UL1007/1569"</li> <li>• All added wiring for load runs of AWG 8, shall conform to MIL-W-16878/3 and/or UL1028</li> <li>• Wire terminals for added circuits must conform to MIL-T-7928. Terminals shall be insulated, insulation grip, TYPE II, CLASS 2 and shall be crimped with tooling recommended by the terminal manufacturer.</li> <li>• All wiring shall be numbered or lettered on 6" centers minimum.</li> <li>• Wiring shall be protected from chafing and abrasion with convoluted polyethylene tubing (wire loom) as required.</li> <li>• Where wire passes through sheet metal, bulkheads and structural supports, plastic grommets shall be used to protect both wiring and wire looms.</li> <li>• All wire bundles shall be tied with trimmed nylon ties.</li> <li>• Extreme care shall be exercised to provide for easy serviceability of the system in future years.</li> <li>• Extreme care must be taken in the installation to avoid the engine manifold, engine exhaust, and muffler, which could expose the wiring to severe overheating during long periods of operation. Proper insulation and heat deflection panels must be installed in such areas.</li> <li>• A high-current 12Vdc system wiring schematic shall be provided.</li> <li>• These are the minimum acceptable 12Vdc wiring requirements.</li> </ul>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
14.00		<b><u>EMERGENCY LIGHTING / SIRENS:</u></b>
14.01	1	Whelen 295SLSA6 siren with 9 low current lighting control switches. California Title 13 compliant.  <b>NOTE:</b> Slide Bar Positions Control: 1. Rear (Upper and Lower) 2. Rear (Upper and Lower), All Upper, Front Wall or "Light bar" 3. All
14.02	1	Whelen SA315P high performance speaker, with SAK9 bracket.
14.03	2	Whelen TLIR ION-T- Series™ Linear Super-LED® Red with clear outer lens & TIONFC chrome flange.  <b>NOTE:</b> Grill
14.04	2	Whelen TLIB ION-T- Series™ Linear Super-LED® Blue with clear outer lens & TIONFC chrome flange.  <b>NOTE:</b> Grill
14.05	7	Whelen M6 series, M6RC (or current model), Linear Super-LED lighthouse with internal flasher, RED LED's with CLEAR outer lens. Includes M6FC chrome flange.  <b>NOTE:</b> Three (3) front, above windshield One (1) rear, tail light housing
14.06	7	Whelen M6 series, M6BC (or current model), Linear Super-LED lighthouse with internal flasher, BLUE LED's with CLEAR outer lens. Includes M6FC chrome flange.  <b>NOTE:</b> Three (3) front, above windshield One (1) rear, tail light housing
14.07	1	Custom fabricated bracket to mount emergency lights above windshield, painted to match body.  <b>NOTE:</b> Whelen M6 lighthouse
15.00		<b><u>AUDIO / VIDEO:</u></b>
15.01	1	28"-32" Name Brand LED HDTV with tuner and wall mount bracket.  <b>NOTE:</b> Size and brand to be determined.
15.02	1	Samsung UN40MU7100 40-Inch 4K Ultra HD Smart LED TV with wall mount bracket. Features: Motion Rate: 120 Backlight: LED Smart Functionality: Yes- built in Wi-Fi Dimensions (W x H x D): TV w/o stand: 36.1 x 21.1 x 2.5 Inputs: 3 HDMI, 2 USB  <b>NOTE:</b> Exterior TV



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
15.03	1	<p>Samsung UN49NU8000FXZA - 49" LED TV (or current model) with wall mount bracket.</p> <p>Product features:</p> <ul style="list-style-type: none"> <li>• Resolution 1920 x 1080</li> <li>• Component , Composite</li> <li>• (2) HDMI, (1) USB</li> <li>• Sound Output (2) Speakers</li> <li>• DTV Tuner/ATSC / Clear QAM</li> <li>• DirecTV Ready, Wi-Fi Ready, Smart TV</li> <li>• Dimensions: 43" x 25" x 2.2" (W x H x D), weight 22.7 lbs</li> </ul> <p><b>NOTE:</b> Front conference room</p>
15.04	1	<p>Weatherproof single door exterior work station and TV/monitor compartment. Constructed from 0.125" aluminum with all welded seams and hinged at the top.</p> <p>Includes:</p> <ul style="list-style-type: none"> <li>• Internal flip down work surface</li> <li>• LED strip light (illuminates when door is opened)</li> <li>• Gas charged lift support and locking latch</li> </ul> <p><b>NOTE:</b> Surface mount, curbside</p>
15.05	1	Sony BDP-S1700 Blu-Ray disc player.
15.06	1	<p>Prewire and make installation provisions for customer installed DSS/Satellite Broadband system. Includes:</p> <ul style="list-style-type: none"> <li>• Roof mounted weather proof junction box with two (2) 3/4" <i>Carlton Carflex</i> ENT conduit runs terminated in equipment rack/cabinet.</li> <li>• Additional roof support structure as required.</li> </ul>
15.07	1	JACK® model OA8500 Digital HDTV Antenna + Mount with SureLock™ DTV Signal Meter. No crank up, built in Amplifier and 360° rotation for improved reception.
15.08	1	<p>Kramer VS-44UHD 4X4 HDMI Matrix Switcher.</p> <p><b>NOTE:</b> Inputs:</p> <ul style="list-style-type: none"> <li>• Blu-ray player</li> <li>• Input at conference table</li> </ul> <p>Outputs:</p> <ul style="list-style-type: none"> <li>• Three (3) TV's</li> </ul>
15.09	3	<p>HDMI run to TV.</p> <p><b>NOTE:</b> Matrix switcher to TV</p>
15.10	1	<p>HDMI run from Matrix switcher.</p> <p><b>NOTE:</b> Front conference room table leg to matrix switcher. HDMI input jack at table leg.</p>
15.11		All RF cable for DSS antenna systems (when specified) shall be Belden #9116 series 6 broadband coaxial cable. All other video cabling shall be Belden #1505A RG-6/U precision video cable.



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
16.00		<b><u>MAST AND MAST MOUNTED EQUIPMENT:</u></b>
16.01	1	Prewire and make installation provisions for customer installed mast on rear of vehicle. Includes: <ul style="list-style-type: none"> <li>• <i>Carlton</i> Carflex ENT conduit routed from mast location to equipment rack cabinet for camera wiring (camera not included).</li> <li>• Internal support structure for future mast install on rear of truck</li> <li>• Receptacle for mast compressor on dedicated circuit (compressor not included).</li> </ul>
17.00		<b><u>RADIOS:</u></b>
17.01		Primary 12Vdc power leads for communications radios shall be minimum 2-gauge copper stranded wire with soldered crimp-on end connectors (gauge based on radio requirements). Cables shall be enclosed in convoluted tubing and function identified with colored shrink-wrap. Power to radios shall be controlled by a continuous-duty switch actuated by the auxiliary battery disconnect switch.
17.02	5	Prewire and make installation provisions for communications radio. Installation includes: <ul style="list-style-type: none"> <li>• NMO-style base on the roof or antenna raceway, as applicable.</li> <li>• LMR195 antenna cable routed to radio transceiver location in <i>Carlton</i> Carflex ENT conduit.</li> <li>• 12Vdc power routed to radio transceiver location.</li> </ul> <p><b>NOTE:</b> One (1) per workstation [qty,4] and one (1) at driver position</p>
18.00		<b><u>COMPUTER NETWORK AND EQUIPMENT:</u></b>
18.01	16	RJ-45 Cat6 computer network jack with Cat6 cable routed through <i>Carlton</i> Flex-Plus ENT conduit or raceway (as applicable).  <p><b>NOTE:</b> Locations: Two (2) per workstation [qty. 8] Four (4) conference table base Two (2) exterior TV compartment Two (2) passenger front workstation</p>
18.02	1	<i>Leviton</i> 69270-U24 24-port Cat6 rack mount patch panel.
18.03	1	Cable Certification Report confirming that network wiring complies with Cat6 specifications.
18.04	1	Pre-wire and make installation provisions for customer supplied printer/copier/scanner.
18.05	1	Make installation provisions for customer installed Satellite broadband system. Includes: <ul style="list-style-type: none"> <li>• Roof mounted weather proof junction box with two (2) 3/4" <i>Carlton</i> Carflex ENT conduit runs terminated in equipment rack/cabinet.</li> <li>• Additional roof support structure as required.</li> </ul>
18.06	1	Prewire and make installation provisions for customer owned 4G wireless router with single modem. Includes two (2) roof mounted NMO antenna base with rain caps. <p><i>Note:</i> Roof mounted antennas, service contract, activation and configuration not included.</p>
19.00		<b><u>MISCELLANEOUS ELECTRONICS:</u></b>
19.01	1	<i>Middle Atlantic Products, Inc.</i> MRK-4026 forty-space 19" wide x 26.5" depth (24" useable depth) open framed electronics equipment rack with caster base. Rack can easily slide out from its fixed position to allow side access to rack equipment.
19.02	1	<i>Middle Atlantic</i> VFD-40 vented front door.  <p><b>NOTE:</b> Door is secured closed with thumb lock (key lock option for future).</p>



CUSTOM SPECIALTY VEHICLES

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
19.03	1	Middle Atlantic PD-815SC-NS 15 amp power strip with eight (8) outlets. Includes PB-XS rack mounting bracket.
20.00		<b><u>EXTERIOR STORAGE COMPARTMENTS:</u></b>
20.01	1	Single door underbody storage compartment with approximate interior dimensions of 15" high x up to 60" wide x 25" deep constructed from 0.125" aluminum with all welded seams.
20.02		<p>Compartments listed above will be constructed to the following specifications:</p> <ul style="list-style-type: none"> <li>• Sweep out type bottoms with 1/2" drain holes.</li> <li>• 2" box pan doors and door frames fabricated from 0.125" aluminum.</li> <li>• Door frames shall be riveted to the body and welded to the compartments.</li> <li>• Compartments shall have an LED light that illuminates when the door is opened.</li> </ul> <p>Compartment doors will be constructed to the following specifications:</p> <ul style="list-style-type: none"> <li>• Stainless steel hinges attached with stainless machine screws.</li> <li>• Slam latches and flush mounted handles.</li> <li>• 0.100" bright polished aluminum diamond plate on interior surfaces fastened with stainless hardware.</li> <li>• All doors shall be sealed with industrial grade neoprene gasket.</li> </ul>
21.00		<b><u>MISCELLANEOUS OTHER:</u></b>
21.01	1	15" wide roof access ladder mounted on rear. Ladder features: <ul style="list-style-type: none"> <li>• All welded construction for maximum strength</li> <li>• 1" diameter X 0.083" brush finished tubular aluminum rails</li> <li>• Aluminum grip-strut rungs</li> </ul>
21.02	1	Heavy-duty <i>Quadra Mfg.</i> Bigfoot® four point fully automatic one-touch leveling system. Includes: <ul style="list-style-type: none"> <li>• Four (4) QEII-24 jacks with 17,000-lb. capacity each, 24" long with 18" stroke</li> <li>• Air ride dump valve</li> <li>• Fully automatic control panel with manual feature</li> <li>• Safety interlock when jacks are deployed</li> </ul>
21.03	2	5 pound dry chemical fire extinguisher.
21.04	2	Battery powered combination Carbon Monoxide and Smoke alarm.
21.05	1	Complete manual set, including the following (as applicable): <ul style="list-style-type: none"> <li>• As-built specifications with interior and exterior drawings as used for production of the vehicle.</li> <li>• Chassis and body owner's manuals.</li> <li>• 12Vdc and 120Vac legends showing wire gauge, color, number and function.</li> <li>• 12Vdc high current wiring diagram illustrating the battery system, isolators, power converters, alternator, disconnect switches and control panels.</li> <li>• Roof top antenna placement drawing and legend identifying antenna placements and termination points.</li> <li>• Audio/Video cabling diagram.</li> <li>• Warranty and Return Authorization procedures.</li> <li>• Chassis and generator maintenance and service logs.</li> <li>• Battery maintenance information.</li> <li>• All individual component manuals and warranty registration cards as provided by component manufacturers. Customer is responsible for completing warranty cards and mailing them to manufacturers.</li> </ul>



**CUSTOM SPECIALTY VEHICLES**

180 Industrial Drive  
Burlington, WI 53105 USA

Phone: 800-558-5986  
Fax: (262) 763-0156  
Direct: +1 (262) 763-0147  
www.ldvusa.com

Item	Qty	
21.06	1	<p>At time of delivery to customer's facility an LDV representative will provide up to eight (8) hours of orientation on LDV provided systems, as applicable:</p> <ul style="list-style-type: none"> <li>• Generator start up and shut down procedure</li> <li>• Leveling system operation</li> <li>• AC and DC electrical systems operation</li> <li>• HVAC systems operation</li> <li>• Audio/Video system operation, does not include programming VCR's, TV's, etc.</li> </ul>
21.07		<p>Note: Project scope does not include certain tasks or costs that are the responsibility of the customer unless clearly specified as LDV supplied. These items include, but are not limited to:</p> <ul style="list-style-type: none"> <li>• Radio and telephone system programming.</li> <li>• Activation and service fees for cellular telephones, satellite telephones, satellite TV, satellite internet access.</li> <li>• Loading and configuring computer software.</li> </ul> <p>In the event of a discrepancy between the drawing and specification, the specification will supersede. LDV reserves the right to make substitutions of equal quality and specifications of those listed in this document.</p> <p>Some component models change frequently. In the event that a specified component model becomes unavailable at the time LDV attempts to source it, LDV will provide a replacement model with equivalent or better features, as agreed upon with the customer.</p>



2812 S. Bus. Hwy 281  
Edinburg, Texas 78539  
Phone: (956) 318-2626  
Fax: (956) 318-2629  
[www.co.hidalgo.tx.us/purchasing](http://www.co.hidalgo.tx.us/purchasing)

---

## AGENDA ITEM BRIEFING

Commissioners Court – August 25, 2020

AI Number: 77003

Project Number: 2020-464

**Information:** [Requesting approval to purchase One (1) Mobile Command Unit, for Hidalgo County Emergency Management [to maintain complete communication and information management]

**Description of AI:** (A) Discussion, consideration, and action to approve a necessary CARES Act Relief Fund expenditure to cover cost of purchase); (B) Exemption from competitive bidding requirements, pursuant to Texas LGC 262.024(a)(1)&(2); (C) Requesting approval to purchase

**Funding Source:** CARES Act Relief Fund (TBD)

**Acct. #** 0-1287-441-42-115-096-0-752

**Requested by:** Chief Ricardo Saldana

**Department:** County Judge's

**Prepared by:** Jaime Rivas, Contract Specialist I

**Department:** Purchasing Department

---

### BACKGROUND

On March 17, 2020, pursuant to the authority under Texas Government Code Section 418.108, Hidalgo County Judge Richard Cortez issued a Declaration of Local Disaster for Public Health Emergency due to the imminent threat arising from the Coronavirus (COVID-19). On March 22, 2020, in accordance with Texas Government Code Section 418.108(b), the Commissioners Court of Hidalgo County issued an Order of Continuance of Declaration of Local Disaster for Public Health Emergency that affirmed the activation of the Hidalgo County Emergency Management Plan and extends the Declaration of Local Disaster.

---

### COMPLIANCE

Under the Presidential Policy Directive/PPD-8: National Preparedness, "it is aimed at strengthening the security and resilience of the United States through systematic preparation for the threats that pose the greatest risk to the security of the nation, including acts of terrorism, cyber-attacks, pandemics, and catastrophic natural disasters," and in compliance with the Homeland Security Presidential Directive 5 (HSPD-5), and the Center for Disease Control and Prevention, Public Health Emergency Preparedness and Response Capability 9 (Medical Materiel

Management and Distribution), and pursuant to the Order of Continuance of Declaration of Local Disaster for Public Health Emergency that affirmed the activation of the Hidalgo County Emergency Management Plan and extends the Declaration of Local Disaster, we request the courts approval for the purchase One (1) New 2020 Mobile Command Unit to maintain complete communication and information management capabilities.

## **ADMINISTRATION**

When operating testing sites, responding to food distribution locations and otherwise coordinating the Hidalgo County COVID-19 response it is critical that Office of Emergency Management maintains complete communication and information management capabilities.

## **AGENDA ITEM CAPTION**

A. Discussion, consideration, and approval of a necessary CARES Act Relief Fund expenditure to cover costs not accounted for in the current budget and cannot be lawfully funded by a line item, allotment or allocation, for the purchase of Mobile Command Unit, while operating testing sites, responding to food distribution locations and otherwise coordinating the Hidalgo County COVID-19 response it is critical that Office of Emergency Management maintains complete communication and information management capabilities; the Court having reviewed the Agenda Item Briefing, herein finds that such expenditure is reasonable and necessary for the intended use;

B. Requesting exemption from competitive procurement requirements pursuant to Texas Local Government Code 262.024(a) (1)&(2).

C. Requesting approval to purchase One (1) Mobile Command Center through distributor LDV Custom Specialty Vehicles in the total amount of \$410,715.00 through HC membership/participation in the HGAC Cooperative Program under awarded Contract No. AM10-18.

### **RECOMMENDATIONS:**

Approval of the item will allow the Hidalgo County Emergency Management to efficiently operate testing sites, while responding to food distribution locations and otherwise coordinating the Hidalgo County COVID-19 response. It is critical and crucial that our Office of Emergency Management maintains complete communication and information management capabilities. Recommending that Commissioners Court authorize the purchase for said Mobile Command Unit, as it is a reasonable and necessary expenditure related to the County's COVID-19 Public Health Response. Expenditures will be charged to the Coronavirus Aid, Relief, and Economic Security (CARES) Relief Grant Fund and/or other grant assistance available to address the COVID-19 public health emergency.

Attachments:

- Agenda Item Briefing
- TXLGC 262.024(a) 1,2

AI-77003

Purchasing Department 19. D. 1.

CC REGULAR AGENDA REGULAR MTG

County Judge's Office

Meeting Date: 08/25/2020

Submitted For: Marty Salazar, PURCHASING DEPT.

Submitted By: Jaime Rivas, PURCHASING DEPT.

Department: PURCHASING DEPT.

**CAPTION**

A. Discussion, consideration, and approval of a necessary CARES Act Relief Fund expenditure to cover costs not accounted for in the current budget and cannot be lawfully funded by a line item, allotment or allocation, for the purchase of Mobile Command Unit, while operating testing sites, responding to food distribution locations and otherwise coordinating the Hidalgo County COVID-19 response it is critical that Office of Emergency Management maintains complete communication and information management capabilities; the Court having reviewed the Agenda Item Briefing, herein finds that such expenditure is reasonable and necessary for the intended use;

B. Requesting exemption from competitive procurement requirements pursuant to Texas Local Government Code 262.024(a) (1)&(2).

C. Requesting approval to purchase One (1) Mobile Command Center through distributor LDV Custom Specialty Vehicles in the total amount of \$410,715.00 though HC membership/participation in the HGAC Cooperative Program under awarded Contract No. AM10-18.

**BACKGROUND**

Commodity Code: 071-77.

**Fiscal Impact**

CALENDAR YEAR: ACCT. #:

FUNDS AVAILABLE Y/N?: MATCHING FUNDS Y/N?:

BUDGETARY IMPACT:

Fiscal impact will be an expenditure for CARES Act Relief Funds.

CALENDAR YEAR: 2020 ACCT. #: 0-1287-441-42-115-096-0-752

FUNDS AVAILABLE Y/N?: Y MATCHING FUNDS Y/N?: Y

BUDGETARY IMPACT:

-

**Attachments**

1295

1295 ACKNOWLEDGMENT

SAM.GOV

Agenda Briefing

---

## Form Review

Inbox	Reviewed By	Date
Purchasing - Internal	Marty Salazar	08/21/2020 05:38 PM
Final Approval	Monica Salinas	08/21/2020 05:52 PM
Form Started By: Jaime Rivas		Started On: 08/20/2020 01:03 PM
Final Approval Date: 08/21/2020		



A NEW WAY TO SIGN IN - If you already have a SAM account, use your SAM email for login.gov.

Log In

Login.gov FAQs

ALERT: SAM.gov will be down for scheduled maintenance Saturday, 09/12/2020 from 8:00 AM to 1:00 PM.

ALERT: CAGE is experiencing intermittent service interruptions. SAM registrants may encounter an error validating a CAGE Code. If this happens, please try again later.

### Entity Dashboard

LDV, INC.  
DUNS: 089845598 CAGE Code: 0TYS3  
Status: Active  
Expiration Date: 04/28/2021  
Purpose of Registration: All Awards

180 INDUSTRIAL DR  
BURLINGTON, WI, 53105-2307,  
UNITED STATES

Entity Overview

Entity Registration

Core Data

Assertions

Reps & Certs

POCs

Exclusions

Active Exclusions

Inactive Exclusions

Excluded Family Members

RETURN TO SEARCH

#### Entity Overview

##### Entity Registration Summary

**Name:** LDV, INC.  
**Business Type:** Business or Organization  
**Last Updated By:** Frank Solofra  
**Registration Status:** Active  
**Activation Date:** 04/28/2020  
**Expiration Date:** 04/28/2021

##### Exclusion Summary

Active Exclusion Records? No



IBM-P-20200814-1154  
WWW1

- Search Records
- Data Access
- Check Status
- About
- Help
- Disclaimers
- Accessibility
- Privacy Policy
- FAPIS.gov
- GSA.gov/IAE
- GSA.gov
- USA.gov

This is a U.S. General Services Administration Federal Government computer system that is "FOR OFFICIAL USE ONLY." This system is subject to monitoring. Individuals found performing unauthorized activities are subject to disciplinary action including criminal prosecution.



## MOBILE COMMAND UNIT (PURCHASE)

08/21/20

As per Chief, create 213 request for purchase of mobile command unit. (Left early)

08/24/20

Contacted Jaime Rivas @ purchasing regarding quote info, provided agenda item. Also advised quote was not confirmed and needed to be resubmitted to HGAC. Notified him we could not submit 213 and req until quote has been confirmed. Vendor has not been setup, Jaime already submitted new vendor application to auditors. Once vendor is setup and quote is confirmed, 213 with req can be submitted.

Agenda item for approval under cares act is pending approval Tuesday, August 25th.

vendor # 488623

Req # 419920