

Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

S P E C I F I C A T I O N P R O P O S A L

Description	Weight Front	Weight Rear
Price Level		
M2 PRL-05M (EFF:03/8/13)		
Data Version		
SPECPRO21 DATA RELEASE VER 012		
Vehicle Configuration		
M2 106 CONVENTIONAL CHASSIS	5,735	3,485
2014 MODEL YEAR SPECIFIED		
SET BACK AXLE - TRUCK		
STRAIGHT TRUCK PROVISION		
LH PRIMARY STEERING LOCATION		
General Service		
TRUCK CONFIGURATION		
DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)		
FIRE SERVICE		
EMERGENCY VEHICLES BUSINESS SEGMENT		
FIXED LOAD COMMODITY		
TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS		
MAXIMUM 8% EXPECTED GRADE		
SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE		
MEDIUM TRUCK WARRANTY		
EXPECTED FRONT AXLE(S) LOAD : 16000.0 lbs		
EXPECTED REAR DRIVE AXLE(S) LOAD : 31000.0 lbs		
EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 47000.0 lbs		



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
Truck Service		
FIRE TANK/PUMPER - MAIN DRIVELINE DRIVEN SPLIT-SHAFT PTO/PUMP EXPECTED TRUCK BODY LENGTH : 0.0 ft EXPECTED BODY/PAYLOAD CG HEIGHT ABOVE FRAME "XX" INCHES : 32.0 in		
Engine		
CUM ISL 350 HP @ 2000 RPM, 2200 GOV RPM, 1000 LB/FT @ 1400 RPM	640	30
Electronic Parameters		
60 MPH ROAD SPEED LIMIT CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT PTO MODE ENGINE RPM LIMIT - 1100 RPM PTO MODE BRAKE OVERRIDE - SERVICE BRAKE ONLY ENABLED PTO RPM WITH CRUISE SET SWITCH - 700 RPM PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM PTO MODE CANCEL VEHICLE SPEED - 5 MPH PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND PTO MINIMUM RPM - 700 REGEN INHIBIT SPEED THRESHOLD - 0 MPH		
Engine Equipment		
2013 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG14 NO 2008 CARB EMISSION CERTIFICATION NO ESCALATOR ENGINE MOUNTED OIL CHECK AND FILL ONE PIECE VALVE COVER SIDE OF HOOD AIR INTAKE WITH NFPA COMPLIANT EMBER SCREEN AND FIRE RETARDANT DONALDSON AIR CLEANER DR 12V 275 AMP 40-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLTAGE SENSE (2) ALLIANCE MODEL 1231, GROUP 31, 12 VOLT MAINTENANCE FREE 2250 CCA THREADED STUD BATTERIES BATTERY BOX FRAME MOUNTED STANDARD BATTERY JUMPERS	10	



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
SINGLE BATTERY BOX FRAME MOUNTED LH SIDE UNDER CAB		
WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN		
NON-POLISHED BATTERY BOX COVER		
POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT	8	
CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE		
STANDARD AIR COMPRESSOR GOVERNOR		
AIR COMPRESSOR DISCHARGE LINE		
GVG, FIRE AND EMERGENCY SERVICE VEHICLES ENGINE WARNING		
CUMMINS EXHAUST BRAKE INTEGRAL WITH VARIABLE GEOMETRY TURBO WITH ON/OFF DASH SWITCH		
RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE EXITING FORWARD OF REAR TIRES	10	5
ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH		
STANDARD EXHAUST SYSTEM LENGTH		
RH HORIZONTAL TAILPIPE, EXIT FORWARD OF REAR TIRES	20	20
6 GALLON DIESEL EXHAUST FLUID TANK		
STANDARD DIESEL EXHAUST FLUID PUMP MOUNTING		
LH UNDER CAB DIESEL EXHAUST FLUID TANK LOCATION		
STANDARD DIESEL EXHAUST FLUID TANK CAP		
HORTON DRIVEMASTER ON/OFF FAN DRIVE		
AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED		
CUMMINS SPIN ON FUEL FILTER		
COMBINATION FULL FLOW/BYPASS OIL FILTER		
1100 SQUARE INCH ALUMINUM RADIATOR	20	
ANTIFREEZE TO -34F, ETHYLENE GLYCOL PRE- CHARGED SCA HEAVY DUTY COOLANT		
GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT		



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES		
AUXILIARY ENGINE COOLING USING WATER FROM FIRE PUMP	10	
LOWER RADIATOR GUARD		
NO FRONT ENGINE PTO		
ALUMINUM FLYWHEEL HOUSING		
ELECTRIC GRID AIR INTAKE WARMER		
DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH	10	
Transmission		
ALLISON 3000 EVS AUTOMATIC TRANSMISSION WITH PTO PROVISION	200	60
Transmission Equipment		
NO AUXILIARY TRANSMISSION		
WTEC CALIBRATION - 5 SPEED EVS WITH AUTO NEUTRAL (PACKAGE 198)		
VEHICLE INTERFACE WIRING WITH BODY BUILDER CONNECTOR MOUNTED END OF FRAME		
ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR MOUNTED BACK OF CAB		
(2) CUSTOMER INSTALLED MUNCIE CS10 SERIES PTO'S		
PTO MOUNTING LH SIDE AND TOP RH SIDE OF MAIN TRANSMISSION		
MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN		
PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED		
TRANSMISSION PROGNOSTICS - ENABLED 2013		
WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK		
TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK		
SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)		
Front Axle and Equipment		
DETROIT DA-F-16.0-5 16,000# FL1 71.0 KPI/3.74 DROP SINGLE FRONT AXLE	190	
MERITOR 16.5X6 Q+ CAST SPIDER HEAVY DUTY CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES		



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
FIRE AND EMERGENCY SEVERE SERVICE, NON-ASBESTOS FRONT LINING		
CONMET CAST IRON FRONT BRAKE DRUMS		
SKF SCOTSEAL PLUS XL FRONT OIL SEALS		
VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL		
STANDARD SPINDLE NUTS FOR ALL AXLES		
MERITOR AUTOMATIC FRONT SLACK ADJUSTERS		
TRW TAS-85 POWER STEERING	40	
POWER STEERING PUMP		
2 QUART SEE THROUGH POWER STEERING RESERVOIR		
ORGANIC SAE 80/90 FRONT AXLE LUBE		
Front Suspension		
16,000# TAPERLEAF FRONT SUSPENSION	200	
GRAPHITE BRONZE BUSHINGS WITH SEALS - FRONT SUSPENSION		
FRONT SHOCK ABSORBERS		
Rear Axle and Equipment		
RS-30-185 31,000# U-SERIES FIRE/EMERGENCY SERVICE SINGLE REAR AXLE		300
5.38 REAR AXLE RATIO		
IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING		
MXL 176T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	60	60
MERITOR 16.5X7 P CAM REAR BRAKES, DOUBLE ANCHOR, CAST SHOES		50
FIRE AND EMERGENCY SEVERE SERVICE NON-ASBESTOS REAR BRAKE LINING		
BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S)		
WEBB CAST IRON REAR BRAKE DRUMS		50
REAR OIL SEALS		
HALDEX GOLDSEAL LONGSTROKE 1-DRIVE AXLE SPRING PARKING CHAMBERS		
HALDEX AUTOMATIC REAR SLACK ADJUSTERS		
ORGANIC SAE 80/90 REAR AXLE LUBE		
Rear Suspension		
31,000# FLAT LEAF SPRING REAR SUSPENSION WITH HELPER AND RADIUS ROD FOR FIRE/EMERGENCY SERVICE		180



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
SPRING SUSPENSION - NO AXLE SPACERS STANDARD U-BOLT PAD FORE/AFT CONTROL RODS		
Brake System		
AIR BRAKE PACKAGE WABCO 4S/4M ABS WITH TRACTION CONTROL REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES FIBER BRAID PARKING BRAKE HOSE STANDARD BRAKE SYSTEM VALVES STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM STD U.S. FRONT BRAKE VALVE RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE BW AD-9 BRAKE LINE AIR DRYER WITH HEATER AIR DRYER FRAME MOUNTED STEEL AIR BRAKE RESERVOIRS, NO TRIPLE OR TORPEDO TANKS BW DV-2 AUTO DRAIN VALVE WITHOUT HEATER ON ALL TANK(S)	40	
Trailer Connections		
UPGRADED CHASSIS MULTIPLEXING UNIT UPGRADED BULKHEAD MULTIPLEXING UNIT		
Wheelbase & Frame		
6750MM (266 INCH) WHEELBASE 7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI 1975MM (78 INCH) REAR FRAME OVERHANG FRAME OVERHANG RANGE: 71 INCH TO 80 INCH CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 153.2 in CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 150.2 in CALC'D FRAME LENGTH - OVERALL : 373.39 CALC'D SPACE AVAILABLE FOR DECKPLATE : 153.2 in FRAME SPACE LH SIDE : 10166.86 in FRAME SPACE RH SIDE : 10199.76 in SQUARE END OF FRAME	560 -30	360 110



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
FRONT CLOSING CROSSMEMBER		
LIGHT WEIGHT HEAVY DUTY ALUMINUM ENGINE CROSSMEMBER	-12	
STANDARD MIDSHIP #1 CROSSMEMBER(S)		
STANDARD REARMOST CROSSMEMBER		
STANDARD SUSPENSION CROSSMEMBER		
Chassis Equipment		
THREE-PIECE 14 INCH CHROMED STEEL BUMPER WITH COLLAPSIBLE ENDS	30	
FRONT TOW HOOKS - FRAME MOUNTED BUMPER MOUNTING FOR SINGLE LICENSE PLATE	15	
NO MUDFLAP BRACKETS		
NO REAR MUDFLAPS		
FENDER AND FRONT OF HOOD MOUNTED FRONT MUDFLAPS		
CLEAR FRAME RAILS FROM BACK OF CAB TO FRONT REAR SUSPENSION BRACKET, BOTH RAILS OUTBOARD		
GRADE 8 THREADED HEX HEADED FRAME FASTENERS		
NO TIRE CARRIER		
TANK BODY 1501 TO 3000 GALLONS		
Fuel Tanks		
50 GALLON/189 LITER SHORT RECTANGULAR ALUMINUM FUEL TANK - LH	20	
RECTANGULAR FUEL TANK(S)		
PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS		
FUEL TANK(S) FORWARD		
PLAIN STEP FINISH		
FUEL TANK CAP(S)		
ALLIANCE FUEL FILTER/WATER SEPARATOR		
EQUIFLO INBOARD FUEL SYSTEM		
HIGH TEMPERATURE REINFORCED NYLON FUEL LINE		
FUEL COOLER MOUNTED LEFT HAND IN RAIL	10	
Tires		
MICHELIN XZY-3 315/80R22.5 20 PLY RADIAL FRONT TIRES	80	



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
MICHELIN XDY-3 315/80R22.5 20 PLY RADIAL REAR TIRES TIRE QTY - PUSHER AXLE: 0 TIRE QTY - TAG AXLE: 0		160
Hubs		
CONMET PRE-SET BEARING IRON FRONT HUBS WEBB IRON REAR HUBS		70
Wheels		
ACCURIDE 29039 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS	50	
ACCURIDE 29300 22.5X9.00 10-HUB PILOT 5-HAND STEEL DISC REAR WHEELS FRONT WHEEL MOUNTING NUTS REAR WHEEL MOUNTING NUTS		120
Cab Exterior		
154 INCH BBC HIGH-ROOF ALUMINUM CONVENTIONAL CREW CAB AIR CAB MOUNTS LH AND RH EXTERIOR GRAB HANDLES WITH SINGLE RUBBER INSERT HOOD MOUNTED CHROMED PLASTIC GRILLE CHROMED HOOD MOUNTED AIR INTAKE GRILLE FIBERGLASS HOOD SINGLE ELECTRIC HORN DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME REAR LICENSE PLATE MOUNT END OF FRAME INTEGRAL HEADLIGHT/MARKER ASSEMBLY WITH CHROME BEZEL (5) AMBER MARKER LIGHTS DAYTIME RUNNING LIGHTS INTEGRAL STOP/TAIL/BACKUP LIGHTS STANDARD FRONT TURN SIGNAL LAMPS DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LH AND RH REMOTE DOOR MOUNTED MIRRORS 102 INCH EQUIPMENT WIDTH LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS STANDARD SIDE/REAR REFLECTORS	430	250



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
NO CAB MOUNTED STEPS		
63X14 INCH TINTED REAR WINDOW		
TINTED DOOR GLASS LH AND RH WITH TINTED NON-OPERATING WING WINDOWS		
MANUAL DOOR WINDOW REGULATORS		
TINTED WINDSHIELD		
2 GALLON WINDSHIELD WASHER RESERVOIR WITHOUT FLUID LEVEL INDICATOR, FRAME MOUNTED		
Cab Interior		
OPAL GRAY VINYL INTERIOR		
MOLDED PLASTIC DOOR PANEL		
MOLDED PLASTIC DOOR PANEL		
BLACK MATS WITH SINGLE INSULATION		
FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS WITHOUT NETTING		
IN DASH STORAGE BIN		
(2) CUP HOLDERS LH AND RH DASH		
GRAY/CHARCOAL FLAT DASH		
HEATER, DEFROSTER AND AIR CONDITIONER	70	
STANDARD HVAC DUCTING		
MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH		
STANDARD HEATER PLUMBING		
DENSO HEAVY DUTY AIR CONDITIONER COMPRESSOR		
BINARY CONTROL, R-134A		
PREMIUM INSULATION		
SOLID-STATE CIRCUIT PROTECTION AND FUSES		
12V NEGATIVE GROUND ELECTRICAL SYSTEM		
DOOR ACTIVATED DOME/RED MAP LIGHTS, FORWARD LH AND RH AND REAR LH, RH AND CENTER		
CAB DOOR LATCHES WITH MANUAL DOOR LOCKS		
SEATS INC 911 UNIVERSAL SERIES HIGH BACK NON SUSPENSION DRIVER SEAT WITH FORE/AFT ADJUSTMENT, UNDERSEAT STORAGE AND NFPA 1901-2009 COMPLIANT SEAT SENSOR	60	



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
SEATS INC 911 UNIVERSAL SERIES SCBA NON SUSPENSION PASSENGER SEAT WITH UNDERSEAT STORAGE AND NFPA 1901-2009 COMPLIANT SEAT SENSOR	40	15
SEATS INC 911 UNIVERSAL SERIES SCBA NON SUSPENSION LH, RH AND CENTER REAR PASSENGER SEATS WITH UNDER SEAT STORAGE AND NFPA 1901-2009 COMPLIANT SEAT SENSOR	60	25
LH AND RH INTEGRAL DOOR PANEL ARMRESTS		
BLACK CORDURA PLUS CLOTH DRIVER SEAT COVER		
BLACK CORDURA PLUS CLOTH PASSENGER SEAT COVER		
BLACK CORDURA PLUS CLOTH REAR PASSENGER SEAT COVER		
3 POINT HIGH VISIBILITY ORANGE RETRACTOR DRIVER, RH FRONT AND LH, CENTER AND RH REAR PASSENGER SEAT BELTS WITH NFPA 1901-2009 COMPLIANT SENSOR AND DASH HARNESS		
FIXED STEERING COLUMN		
4-SPOKE 18 INCH (450MM) STEERING WHEEL		
DRIVER AND PASSENGER INTERIOR SUN VISORS		

Instruments & Controls

GRAY DRIVER INSTRUMENT PANEL
 GRAY CENTER INSTRUMENT PANEL
 ENGINE REMOTE INTERFACE WITH PARK BRAKE AND NEUTRAL INTERLOCKS
 BLACK GAUGE BEZELS
 LOW AIR PRESSURE LIGHT AND BUZZER
 2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES
 ENGINE COMPARTMENT MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS, WITH WARNING LIGHT IN DASH
 ELECTRONIC CRUISE CONTROL WITH SWITCHES IN LH SWITCH PANEL
 KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY
 ODOMETER/TRIP/HOUR/DIAGNOSTIC/VOLTAGE DISPLAY: 1X7 CHARACTER, 26 WARNING LAMPS, DATA LINKED, ICU3
 DIAGNOSTIC INTERFACE CONNECTOR, 9 PIN, SAE J1939, LOCATED BELOW DASH



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
2 INCH ELECTRIC FUEL GAUGE		
ENGINE REMOTE INTERFACE NOT CONFIGURED		
ENGINE REMOTE INTERFACE CONNECTOR AT BACK OF CAB		
NO CUSTOMER DEFINED WIRING FUNCTION		
ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE		
2 INCH TRANSMISSION OIL TEMPERATURE GAUGE		
ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY		
CUSTOMER FURNISHED AND INSTALLED PTO CONTROLS		
ENHANCED STABILITY CONTROL		
ELECTRIC ENGINE OIL PRESSURE GAUGE		
OVERHEAD INSTRUMENT PANEL		
NO RADIO		
ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER		
STANDARD VEHICLE SPEED SENSOR		
ELECTRONIC 3000 RPM TACHOMETER		
IDLE LIMITER, ELECTRONIC ENGINE		
DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY		
SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY		
MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH		
ONE VALVE PARK BRAKE SYSTEM WITH DASH VALVE CONTROL AUTONEUTRAL AND WARNING INDICATOR		
SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, WASHER/WIPER AND HAZARD IN HANDLE		
INTEGRAL ELECTRONIC TURN SIGNAL FLASHER WITH HAZARD LAMPS OVERRIDING STOP LAMPS		

Design

PAINT: ONE SOLID COLOR

Color

CAB COLOR A: L2225EB CANDY APPLE RED
 ELITE BC



Prepared for:
 Steve Harris
 Rosenbauer Minnesota
 5181 260th Street
 Wyoming, MN 55092
 Phone: 651-462-1000

Prepared by:
 Jan Konop
 I-STATE TRUCK CENTER
 2901 WEST 60TH STREET N.
 SIOUX FALLS, SD 57107

Description	Weight Front	Weight Rear
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT		
FRONT WHEEL PAINT: N2225EA CANDY APPLE RED ELITE SS		
REAR WHEEL PAINT: N2225EA CANDY APPLE RED ELITE SS		

Certification / Compliance

U.S. FMVSS CERTIFICATION

T O T A L V E H I C L E S U M M A R Y

Weight Summary

	Weight Front	Weight Rear	Total Weight
Factory Weight ⁺	8576 lbs	5350 lbs	13926 lbs
Dealer Installed Options	2 lbs	0 lbs	2 lbs
Total Weight⁺	8578 lbs	5350 lbs	13928 lbs

Dealer Installed Options

	Weight Front	Weight Rear
WELDON VDR AND DISPLAY INSTALLED AT ISTATE TRUCK CENTER	2	0
Total Dealer Installed Options	2 lbs	0 lbs

(+) Weights shown are estimates only.
 If weight is critical, contact Customer Application Engineering.

