

Symbol	Label	QTY	Manufacturer	Catalog	Description	Number Lamps	Lamp Output	LLF	Input Power
○	G	10	Lithonia Lighting	VCPG LED P3 40K TSM MVOLT	VCPG LED WITH P3 - PERFORMANCE PACKAGE, 4000K, TSM OPTIC TYPE	1	6253	0.9	43.37
□	K	2	CAMMAN LIGHTING, INC.	OW915-24-LN-T3	WALL MOUNT	1	1329	0.9	23.36
○	RD	0	Lithonia Lighting	WF6 LL LED 30K40K50K 90CRI 4000K	6" low lumen Matte White Wafer Selectable White LED 30K40K50K - 4000K	1	923	0.9	9.77
□	S1	3	Lithonia Lighting	RSX2 LED P2 40K R4	RSX Area Fixture Size 2 P2 Lumen Package 4000K CCT Type R4 Distribution	1	17427	0.9	114.07
□	S2	1	Lithonia Lighting	RSX2 LED P2 40K R5	RSX Area Fixture Size 2 P2 Lumen Package 4000K CCT Type R5 Distribution	1	17660	0.9	228.14
□			Lithonia Lighting	RSX2 LED P2 40K R5	RSX Area Fixture Size 2 P2 Lumen Package 4000K CCT Type R5 Distribution	1	17660	0.9	114.07
□			Lithonia Lighting	RSX2 LED P2 40K R5	RSX Area Fixture Size 2 P2 Lumen Package 4000K CCT Type R5 Distribution	1	17660	0.9	114.07
□	W	1	Lithonia Lighting	WPX0 LED ALO-4 40K MVOLT	WPX0 LED, 1650 Lumen setting, 4000K Setting, 120-277V	1	1645	0.9	12.4511

Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
Parking and Drives	X	6.0 fc	28.8 fc	1.0 fc	28.8:1	6.0:1
Total Area Calculated @ Grade	+	2.0 fc	28.8 fc	0.0 fc	N/A	N/A

Note
 1. Davis and Associates, Inc does not assume responsibility for the interpretation of this calculation, or compliance to local or state lighting codes and ordinances.
 2. All readings/calculations are shown @ grade.
 3. Fixture heights are shown on plan.



Plan View
Scale - 1" = 20ft