



Unit #:
XX-XXXXXX

DEALER: SWAS
CUSTOMER: City of Roswell
 Street or P.O. Box: 425 N Richardson
 City, State, Zip: Roswell NM 88201
 Customer Contact: Randy Bunch
 Customer Email: r.bunch@roswellnm.gov
 Customer Phone #:
 Sales Associate: Bobby Davis
 Sales Engineer:

VIN#:

Chassis Model Yr		2025
MEDIX Model		Metro Express 153 Type I
CHASSIS		Chevy K-3500, 6.0L Vortec Gas, 171" WB, 14,000 GVWR 84.5 CA, 4x4
BODY		153"L x 94" W x 72" Interior Headroom
QTY	STD/OPT	Description
1	15-1000-CD	Chassis & Conversion
		Model Year Adjustment
	-	2025 New Sales Model w/Drop Skirt Curbside & Wider Compartment #1
		-
	01-	Flooring & Interior Colors
1	STD	Cabinets: Laminated Wood Laminate Color: GREY
1	STD	Upholstery: (Specify Color)
1	STD	Color: Gunmetal Brand: EVS
1	STD	Flooring: Lonseal - Lonspeck Topseal Twilight Zone SX111
		-
	02-	Body & Chassis
1	STD	This chassis is equipped with a Gasoline Exhaust System to meet the EPA standards for Gasoline exhaust emissions
	Note Weld Shop	See special front wall print for front wall condenser location
	NOTE Weld Shop	Delete standard static vent over curbside entry door due to interior glove boxes - do not cut hole.
1	STD	Anti-Theft Device: IdleLock Ignition Security System, for C/K 3500 Series Chassis Only. Locate activation button to the right side of the steering wheel.
1	STD	Camera System: RVS Systems RVS-MV3619N-NM-02- Includes (1) 7" rear view mirror monitor, Surface Mount back-up camera and (1) 33' camera cable. Locate: (1) Camera mounted off lower RH corner of center rear Amber light, Monitor mounted on cab windshield rear view mirror.
1	STD	All Exterior compartments coated with light gray colored rubberized polyurethane material.

1	STD	Pass-Thru: With accordion boot. Sliding, latching polycarbonate window.
1	99-2289	Chassis: Air Horns, Buell dual horns, (1) 10" and (1) 12" to be mounted through the front bumper. There will be a momentary switch on the front console. A Buell "Fast Recovery System" air compressor to be mounted in compartment #2 with the tank mounted under the body. NOTE: Type III Chevy G-Series only
1	STD	Compartment Lights: Optronics ILL36CB LED Compartment lights- ALL Models Locate: (1) Ceiling of Compt #1; (2) in Compt #2- (1) URH, (1) LLH; (1) in ceiling of Compartment #3; (2) in Compt #4/5; (1) in Compt #6 (if applicable).
1	MODIFIED	Compartment #1 SS Forward: Smooth Aluminum body, ADP interior door panel, O2 Universal Lift for STEEL tank, Door w/gas-strut hold-open. NOTE: See option in oxygen section for O2 lift.
1	99-0334-C1	Compartment #2: SS center, Drop Floor, 5" for Stair Chair storage PN: 33-10-4865 NOTE: ME-153 Type I Chevy Models Only. *not for use on the 2024 models with wider #1
1	99-3344	Compartment #3: SS Rear, 3/4 Height, Smooth Aluminum body to have an offset in upper, inboard portion of the compartment tub for interior cabinetry with backer plate from right below the offset on down. Compartment will have (1) adjustable aluminum shelf in lower section. Door w/gas strut hold-open. Sealed access to paddle handles in door panel. See special tub print: 41-117997, ILOS mid height compartment.- (must select an interior cabinet option from the cabinet section) NOTE: ME153 TYPE I Models Only.
2	STD	Rear Entry Doors: Single piece laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels.
1	STD	Compartment #4/5 CS Forward: NO body <u>above floor</u> , <u>ADP interior door panel</u> , ALS Cabinet w/ Inside/Outside access, Full-height, single Door w/gas strut hold-open. Bottom section aluminum body open storage standard. (Optional location for additional battery with roll-out battery tray and removable, latching door.) NOTE: Compt #5 will house electrical components
1	STD For 2024 Model	Drop Skirt - 4" on Curbside forward of the rear wheelwell. Taller front stone guard on passenger side.
1	STD For 2024 Model	Curbside Entry Door: Taller for 4" drop skirt. Door handle to remain aligned with Compt #4/5 handle; Single door system w/exterior/interior, locking paddle handles; window w/fixed glass; Gas strut hold-open. Sealed access to paddle handles in door panel. LED Step well light. Two-piece interior door panel.
1	STD For 2024 Model	Curbside Entry Door Stepwell: Dual, smooth aluminum steps welded into the floor structure and coated with a rubberized urethane liner material. There will be a Dri-Dek insert on each step surface.

1	STD	Compartment #6 CS Rear: Smooth Aluminum, Vertical backboard storage w/2 belts. Door w/nylon strap hold-open.
1	STD	All Entry Door paddle handle and rotary latching components will include emergency door releases located top and bottom of each door and shall meet the FMVSS 206 30G Test Requirement
1	200200C	Power Door Locks: Chevy Type I, All Entry and Compartment Doors, wired to OEM door lock system. (Does not include additional lock switches inside module) NOTE: See option 99-0404 for adding on lock switches at the entry doors
1	99-0804	Switching: Power Door Locks, Lock/Unlock rocker switch PN: MX09145 located in the front switch panel to unlock and lock the module doors from inside the cab. NOTE: Chevy Type I Models.
1	99-0404	Switching: Momentary Disable for Scene/Load Lights PN: MX09144 and Power Doors Locks PN: MX09145. Locate: (1) horizontal, 4-position Positron panel on Curbside Wall at head of bench and (1) stacked, 2-position Positron switch panel on wall at curbside rear entry door in standardized position.
1	99-0678C	Power Door Locks: Stealth Switch, Chevy Type I Only, Power Door Lock System, Push Button Switch (Grille brackets: no bracket required on Chevy Cab/Chassis)
1	STD	Rear Bumper: ADP corner pods w/Dock bumper pads, Center grip-strut flip-up step, powder coated steel frame
2	STD	IV Hangers: (2) Cast black rubber fold-down over knee area of Cot and Squad Bench
3	STD	Mirrors, OEM: (1) each cab door, (1) on interior windshield
1	STD	OEM Chrome wheel covers
4	STD	Stone Guards: (3) Lower body corners, ADP; (1) 4" taller ADP on Curbside front
1	STD	Kick Plate, Rear: ADP, below rear doors across to corner posts.
1	STD	Rub Rails: C-Channel, tapered ends, Lower Body off-set mount with neoprene spacers.
2	STD	Running Boards: Diamond Plate, Type I w/starburst pattern
1	STD	Fender Flares: Black rubber
2	STD	Fuel Fill: Cast aluminum fuel fill bezel.
1	STD	Insulation: Pink, double sided radiant barrier/acoustic material, installed on curbside and streetside rear wheel wells.
1	STD	Insulation: Spray in place foam applied to curbside entry step well and both rear wheel wells
1	STD	Undercoating: Per OEM Guidelines
		-
	03-	Brake, Turn & Back-Up Lights
1	STD	Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 600 Series LED.
1	STD	DOT Marker Lights: TecNiq LED, rubber grommet bezels; (7) S34-AC09-1 Amber- (5) on front of body as Marker lights, (2) side facing on rear extrusions as Turn Signals; (7) S34-RC90-1 Red- (5) on rear of Body as Marker lights, (2) side facing as Turn Signals.
		-
	04-	Electrical, Power Distribution, Control Center & Interior Lighting

1	STD	Battery Switch, Automatic: TST CDR-400. Located in Electrical Cabinet.
2	STD	Batteries: OEM, under hood
1	STD	Front Console/ Switch Panel: Formed Aluminum body powder coated black and attached to chassis floor. Switch panel: Engraved black plastic with LED lighted switches for Emergency Master, Primary/Secondary Modes, Siren/Horn, Left, Rear and Right Floods, Back-Up Alarm, Module Disconnect. Siren mounted in engraved panel below switches.
1	99-0747	Electrical: Antenna, (2) 25' Coax with 3/8" through-hole antenna bases prewired to roof ILOS standard coaxial cables. NOTE: <u>MEDIX</u> to drill hole and complete mount. Terminate coax with standard Power/Ground (1) behind driver's seat and (1) Behind Action Area. Note: Modular Units Only.
8	STD	Lights: Dome, Whelen LED, 18-diodes w/chrome flange MX80EHZA , switched separately with Hi/Lo functions.
1	STD	Action Area Light: 12 VDC LED light, with On/Off switch on rear control panel
1	99-0617	Electrical: Shoreline, 125VAC, 20-Amp, Kussmaul SUPER Auto Eject P/N: 091-55-20-120 side wired with hinged, yellow, weatherproof cover, Located above Compartment #2 on Streetside. Will have to be mounted on a Kussmaul Stainless Steel E-Z mounting plate P/N: 091-185-009 with green indicator light for ease of access. Mating Connector to be shipped loose. ILOS
1	STD	Timer: 5-minute check-out, wired to CS High mode dome lights
1	99-0550-A	Switching: Timer, Momentary 15-Minute timer switch for patient compartment dome lights. Locate switch in 4-position Positron switch panel in standard position on curbside wall. (PNs: MX09150 switch, MX09151 Timer) NOTE: A-Line Models Only
1	99-3022	Inverter: Vanner LSC12-2000- 2000 watt Pure Sine Wave with battery charger and built in GFI. Remote controlled with switch in rear panel. (This option deletes the GFI in the A/A wall). ILOS NOTE: OPTION 99-1955 IS REQUIRED WHEN ANY INVERTER IS MOUNTED IN ANY BULKHEAD or INTERIOR ENCLOSED CABINET. OPTION 99-2899 DUAL FANS REQUIRED ON RP-90ES and 150 MODELS.
1	400150	Electrical: Battery Charger, DELETE STANDARD (when adding Inverter with integral charger)
1	MODIFIED	Breaker Box: 125 VAC w/20-Amp Breaker located in Compartment #5 . GFI receptacle located on the Action Area wall.
2	STD	12 VDC Outlets: (1) in Action Area, (1) in ALS Cabinet NOTE: (1) in Extended action area is included in cabinet option below.
2	STD	125 VAC Outlets: Duplex, located (1) in Action Area, (1) in ALS. NOTE: (1) in Extended action area is included in cabinet option below.

1	99-1241	Electrical: 125VAC, Weatherproof Duplex Outlet. IATS Specify Location(s): #2 Compartment - Recess in ceiling to the right toward front of compartment.
1	STD	Rear Switch Panel: Engraved black plastic panel with (10) LED lighted switch positions for Dome Lights (2), Vacuum (1), Vent (1), A.A. Light (1), Inverter (1), Spare switches and digital clock w/Mode Buttons. MX01517.
1	STD	Electrical Cabinet: Located over cabin-module connection w/latching, recessed, vented door
1	99-1558	Lights: Spotlight, 300,000 CP handheld, hard wired, with momentary On/Off switch, located in cab. Able 2 PN: 06-300
		-
	05-	Warning Lights & Sirens
1	STD	Lights: Warning, Whelen LED EMERGENCY Lighting Package- Ford, Chevy Type I and Type III- Models ONLY. NOTE: Does not include LED Scene Lights.
		All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.
		Front of Body: Add (7) Whelen 900 Series Super-LEDs- Specify pattern by LED Color (4) Red and (3) White: R-W-R-W-R-W-R Outer (2) lights and (1) Center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.
		Sides of Body: (4) Whelen 900 Series Red Super-LEDs: (2) each side in upper corners
		Rear of Body: (4) Whelen 900 Series Red Super-LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level; (1) Whelen 900 Series Amber Super-LED in the center position over the rear doors.
		Brake, Turn & Back-Up Lights: Whelen 600 Series LEDs
		Lights, Warning, Intersection Lights: (2) Whelen LINZ6R Series Red Super-LEDs on front fenders
2	STD	Lights, Warning, Grille: Whelen WIONSMCR Red LED, on center grille bar, w/Clear lenses and flanges.
2	99-0405	Lights: Warning, (1) Whelen ION Series Wide Angle Super LED WIONSMCR Red LED with chrome flange. IATS NOTE: to flash in X-Pattern w/ upper red leds
6	500127	Lights: Scene/Load, Whelen 900 Series Super-LED 9SC0ENZR Gradient Opti-Scenelight™ with chrome flange- ILOS Halogen Specify Locations: (2) Each Side of Module & (2) over rear entry doors
1	STD	Flasher: Dual mode flasher for Warning Light system, Vanner 9860GCPE
2	STD	Siren Speakers: Dual 100 Watt drivers mounted through the front bumper
1	STD	Siren: Whelen 295 SLA1, 200 Watt
		-
	06-	Oxygen, Vacuum & Miscellaneous Items
3	STD	Oxygen Outlets: Quick-connect style, (2) in Action Area, (1) over Squad Bench

1	600100	Oxygen: O2 Outlets, Single OHMEDA Z-QD0101MO outlet, IATS Specify Location(s): ceiling, standard position
1	MODIFIED	Suction Aspirator System: SSCOR with SS Bracket for container and vacuum outlet mounted in RECESS BELOW Action Area, gauge will be mounted on the Action Area Panel: SSCOR Vacuum pump ounted in Compartment # 5
1	99-0639	Suction System: SSCOR with SS Bracket for container, electric pump-ILOS Rico System NOTE: Locate gauge and Vacuum outlet on action area wall. ILOS Locate vacuum outlet and suction canister in recessed pocket per option 99-1144
1	99-1144	Cabinets: Add recessed pocket below A/A countertop for SSCOR suction canister and Vacuum outlet ILO mounting canister on the A/A panel.
1	99-3652	Oxygen: O2 Cylinder Mount, Universal Lift Zico QR-OTSL-US for H-Cylinder, LH Drive, LH Remote Control; Mounting Bracket and Can Cover required: assembly and offset cover, ILOS O2 bracket. Specify Location(s): #1 STANDARD LOCATION NOTE: ME-153 and 166 Models Only.
1	STD	O2 Regulator: Amvex, 50psi, pre-set
1	99-3062	Oxygen: O2 Cylinder Mount, (1) CPI OA1205-DUAL-D-1 oxygen bottle holder with mounting plate, for two "D" cylinders. Specify Location(s): under squad bench on top of wheel well cover
		-
	07-	AC / Heat
1	99-3364	HVAC System: Valeo, PN: 11148732A High capacity, horizontal blow combination Heat-AC system to include a front wall mounted external condenser Valeo PN: 25062 on painted aluminum shelf PN: 33-113943. The Valeo high performance evaporator unit will have a brush type motor fan. There will be a digital thermostat control on the action area wall and an inline booster pump to enhance the rear heater performance. The HVAC unit will be mounted in the front bulkhead cabinet over the pass-through. NOTE: Type I 2020 and later C/K 3500 Gas and Diesel RP90 153 Models Only.
		-
	08-	Cabinets, Hardware & Miscellaneous Items
1	STD	Main Streetside Wall Cabinets: Specify desired configuration-
1	99-3648	Cabinets: Main Cabinet Wall, Extended Action Area with 2nd full depth Overhead cabinet and (1) adjustable shelf. Extended action area to provide 20" clearance mininum above A/A countertop. Upper (2) forward overheads to be the same height as the third upper rear main cabinet but not as deep. NOTE: Will include (1) 125VAC and (1) 12VDC outlet located at left end of panel.

		Main Wall Cabinets will have (1) adjustable shelf in each and sliding polycarbonate doors with full height extruded handles. See Prints for Configuration.
5	99-0540	Cabinets: Main Cabinet Wall, Restocking Feature, Interior Cabinet, Under 40" Width- Sliding Acrylic door with hinged, keyed frame with (2) Titan 15-pound gas struts and (2) spring-loaded elbow catches. Location: BOTH ACTION AREA OVERHEAD CABINETS, A1, A2 and F
1	STD	Action Area Overhead Cabinet: Single cabinet full-height/full-depth of Action Area with sliding polycarbonate doors and full height extruded handles.
1	MODIFIED	Extended Action Area and Switch Panel: Laminated, sealed countertop and vertical ALUMINUM panel with Suction system collection canister, Vacuum gauge, (2) Oxygen outlets, (1) Manual Bypass (1) USB, (1) 12VDC Outlet, (1) 125VAC Outlet and digital Thermostat. Switch panel MX01517 includes (10) switch positions and digital clock w/Mode Buttons. NOTE: Will have (1) add'l 12v & (1) add'l 125v outlet on left side of panel.
1	600070	Oxygen: Electric O2 with manual bypass and switch mounted on A/A panel
1	99-1077	Mounting Plate: 0.25"x17.5"x 21.25" mounting plate PN: 33-104404 installed beneath the 2nd action area countertop for future installation of customer supplied monitor mount.
1	STD	Bulkhead Wall Cabinets: Electrical Cabinet above cabin-module connection w/hinged, latching, vented door.
1	99-1839	Lock: (1) LifeDefender CW-LOCKASSY-545 tumbler lock to work with LifeDefender cabinet door or drawer latch. Note: this key is different than the standard LifeDefender lock keys. Specify Location(s): CABINET NEXT TO ELECTIRCAL
1	STD	Bulkhead Cabinets: Upper cabinet- general storage w/hinged, latching door; Lower cabinet general storage w/hinged, latching, vented door.
1	99-3185	ALS Cabinet: Combine Lower and Middle to create a single opening with dual, full height 1/2" Acrylic doors, non-locking doors with Two Point Paddle Latches, one per door, and (2) Adjustable Shelves. ILOS NOTE: RP-90ES, ME-150/153 and 166 Models Only.
1	99-0511	Cargo Net: Head of squad bench- Type I / III 150/153 Models. Squad Bench to accommodate mounting plate and cover secured to wall structure.
1	99-0798	Glove Box Holders: (3) with hinged, black 11ga steel powder-coated door, above Curbside Entry Door. NOTE: DELETES STATIC VENT OVER SIDE ENTRY DOOR

1	99-3650	Squad Bench: Wood squad bench with wood lid shortened on rear end by same amount as front, ILOS Aluminum. NOTE: The distance at the foot of the squad bench from the shortened lid to the wall should be a minimum of 10". There will be (2) EVS Pro-4 seat belt system seating positions that include a custom contoured seat back, a single click Pro-4 seat belt, custom pads on the upper straps for shoulder comfort, a custom retractor for securing a secondary patient and a heat embossed Medix LOGO at the heat area. The head of the squad bench will include sharps/waste drop-in style storage with aluminum, powder coated red, hinged lid and standard containers. ILOS Aluminum bench. NOTE: For Type I 153 models only
1	99-3653	Cabinets: Squad Bench Overhead, with (2) flip-up 1/2" Acrylic doors with (1) Defender Latch on each door and Austin constant torque hinges installed, ILOS NOTE: 153 Type I Models Only
1	99-3138	Cabinets: Rear Overhead, Cabinet over rear doors opening with (1) flush mount, flip-up 1/2" acrylic door, (3) constant torque hinges and (1) Life-Defender latch ILOS. NOTE: ME-153 Type I Models Only.
1	99-2777	Seating: EVS 1880 Child Safety Seat, (1) Technician's Seat MDX-1880S4B with 10° back. Rear facing automotive style seat to include a Pro-4 black belt system, comfort shoulder padding with heat embossed Medix LOGO at the head area of the backrest and the child safety seat system. -ILOS Pro-4 seat. NOTE: Must specify seat base in separate line item. NOTE: Medix Modular Models Only (Not for use on RP90 models).
1	99-0411	Seating: EVS Seat Base, EVS CBWD reinforced cabinet base with door to storage and latch- ILOS
1	STD	Assist Rail: overhead off-center toward Streetside of unit.
3	STD	Grab handles: 12" x 1.25" dia. stainless steel mounted on each rear entry and curbside entry door
1	STD	Reflective Striping, Door Open Protection: .50" Red reflective striping around interior door pan of all body doors.
		-
	09-	Cots & Miscellaneous Items
1	99-0726	Cot Mount: Stryker, PowerLoad Systems, install floor plate "Only". ILOS 175-4. LOCATION: CENTER Mounting Location NOTE: ME-153, ME-166, MSV-II Models Only.
		-
	10-	Paint & Lettering
1	STD	Paint: Body all OEM White
1	OPT	Grayson Graphics to supply and inatall graphics package With Rear Chevrons. See Quote.
1	1000100	Roof Star ONLY, INSTALLED
1	99-1098	Windows: Privacy tint, dark vinyl applied to all three entry module entry door windows. NOTE: Module application only.
		SHIP LOOSE

2	STD	Fire Extinguisher: (2) 5 lb- Ship Loose is Standard
2	99-1362	Seat Belt: Automotive Style, (1) 2"W x 45"L female strap side and (2) footman loops. IATS Location: SHIP LOOSE
TOTAL ORDER \$235,984.00		

I have reviewed this Order and find it to be acceptable and ready to build.

Dealer Signature

Date: _____

I have reviewed this Order and find it to be acceptable and ready to build with the addition of the attached, approved changes.

Dealer Signature

Date: _____

NEW!

Please click the link below to complete the Medix Purchase Agreement Standard Terms & Conditions.

Please note, your order will not be accepted without receipt of the signed Terms & Conditions.

[Medix Purchase Agreement Standard Terms & Conditions for Sale](#)

Due to on-going product improvements and the changing requirements of the ambulance industry, MEDIX Specialty Vehicles, Inc. reserves the right to change product specifications and related products without prior notice and without any obligation to change prior products or parts. ALL PATENTS RIGHTS RESERVED.

Product quotes are subject to change. Purchase Price will be the published price list within Quote/Order Entry System on the date of order acceptance by Company