



Unit #:  
XX-XXXX

**DEALER:** Republic EVS  
**CUSTOMER:** City of San Luis  
 Street or P.O. Box: 1165 N. McCane ave.  
 City, State, Zip: San Luis, AZ 85349  
 Customer Contact: Angel Ramirez  
 Sales Associate: Garrett Adelman  
 VIN#: To be assigned by MEDIX

Received  
 Sent for Approval  
 Rec'd Approved  
 Scheduled  
 GPC Number: 00YX6

Form Revised 1/18/2019

<b>Chassis Model Yr</b>		<b>2019</b>	
<b>MEDIX Model</b>		Metro Express 153 Type I	
<b>CHASSIS</b>		RAM 3500, 6.7L DIT Diesel, 168" WB, 14,000 GVWR	<b>4x2</b>
<b>BODY</b>		153"L x 94" W x 70" Interior Headroom	
<b>QTY</b>	<b>STD/OPT</b>	<b>Description</b>	
<b>1</b>	<b>16-1000-FD</b>	<b>Chassis &amp; Conversion w/o Liquid Springs</b>	
	<b>01-</b>	<b>Flooring &amp; Interior Colors</b>	
<b>1</b>	<b>100040</b>	<b>Cabinet Laminate: Gloss Gray</b>	
1	STD	Upholstery: (Specify Color)	
		Color: Gunmetal Brand: EVS	
<b>1</b>	<b>100015</b>	<b>Lonseal- LonDeck (Tic-Tac-Toe)</b> <b>Specify Color: Onyx</b>	
	<b>02-</b>	<b>Body &amp; Chassis</b>	
<b>1</b>	<b>STD</b>	<b>This chassis is equipped with a Diesel Exhaust Fluid (DEF) System to meet the EPA Diesel Emissions Standards.</b>	
<b>1</b>	<b>99-2137</b>	<b>Wheels: Aluminum Wheels on Dodge-3500 Series Chassis.</b>	
1	STD	All Exterior compartments coated with a light gray rubberized urethan material.	
1	STD	Pass-Thru - No sliding polycarbonate, just OEM P/T	
<b>1</b>	<b>200130</b>	<b>Fender Flares: Roll formed stainless steel, ILOS rubber.</b>	
<b>1</b>	<b>99-0423</b>	<b>Lights: Compartment, TecNiq Flexible LEDs: 9", 27", 36" 45", 54", ILOS compartment lights.</b> <b>Locate: Compartment #1- (1) 45" E44-W010V-1</b> <b>Locate: Compartment #2- (2) 27" E44-W06V-1</b> <b>Locate: Compartment #3- (2) 45" E44-W010V-1</b> <b>Locate: Compartment #4- (1) 36" E44-W08V-1</b> <b>Locate: Compartment #6- (2) 54" E44-W012V-1</b> <b>Locate: Compartment #7- (1) 9" E44-W02V-1 (if ordered)</b>	
1	STD	Compartment #1 SS Forward: Smooth Aluminum body, ADP interior door panel, O2 "M" cylinder storage for STEEL tank, Door w/rubber socket/nylon ball hold-open.	
1	STD	Compartment #2 SS Center: Smooth Aluminum body, ADP interior door panel, Open Storage, Door w/gas strut hold-open and Seat Belt Strap.	
<b>2</b>	<b>200280</b>	<b>Shelf: Adjustable, Aluminum Diamond Plate, Exterior Compartment</b> <b>Specify Location: Comp 2 and 3.</b>	
<b>1</b>	<b>99-1363</b>	<b>Compartment #3: On 153 Body, 3/4 Height, Smooth Aluminum body, ADP interior door panel, SS Rear, with NO Inside/Outside Access, No shelf and offset for interior 2nd Action Area. See print 41-104586.</b>	

2	STD	Rear Entry Doors: Single piece laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels.		
1	STD	Compartment #4/5 CS Forward: NO body above floor, ADP interior door panel, ALS Cabinet w/ Inside/Outside access, Full-height, single Door w/gas strut hold-open. Bottom section smooth aluminum body, Open storage.		
1	STD	Curbside Entry Door: Single piece, laminated smooth aluminum door liner w/stainless steel center panel for black paddle handles; ADP kick panels. Gas strut door hold-open. Smooth aluminum stepwell w/Dri-Dek insert.		
1	99-0795	<b>Entry Doors: Lower Kick Panels, smooth aluminum w/reflective chevron installed ILOS ADP. NOTE: Red/Lime Green</b>		
1	STD	Compartment #6 CS Rear: Smooth Aluminum, Vertical backboard storage w/2 belts. Door w/ rubber socket/nylon ball hold-open.		
1	99-1104	<b>Dividers: Backboard Compartment, lined with light gray rubberized urethane material- coating on both dividers ILOS smooth aluminum finish.</b>		
1	200100-153	<b>Compartment #7: Aft of curbside wheel well on 153 body, IATS. Smooth aluminum body w/rubberized urethane coating, open storage, single door w/gas strut hold-open. (1) LED light in ceiling.</b>		
1	STD	All Entry Door paddle handle and rotary latching components will include emergency door releases located top and bottom of each door and shall meet the FMVSS 206 30G Test Requirement		
1	200200A	<b>Power Door Locks: All Entry and Compartment Doors, wired to OEM door lock system.</b>		
1	99-0678E	<b>Power Door Locks: Stealth Switch, Power Door Lock System, Push Button Switch (Grille brackets: Ford 33-102402, no bracket required on F-series) LOCATION:</b>		
1	STD	Rear Bumper: ADP corner pods w/ rubber Dock bumper pads, Center grip-strut flip-up step, powder coated steel frame		
2	STD	IV Hangers: (2) Cast black rubber fold-down over knee area of Cot and Squad Bench		
3	STD	Mirrors, OEM: (1) each cab door, (1) on interior windshield		
1	STD	<b>Stainless steel wheel covers w/valve extenders</b>		
4	STD	Stone Guards, lower body corners, ADP		
1	STD	Rub Rails, C-Channel, tapered ends, Lower Body off-set mount with neoprene spacers.		
2	STD	Aluminum Running Boards: "Starburst" Grip Punched, Diamond Plate, Type 1		
1	STD	Cast aluminum fuel fill bezel		
1	STD	Formed SS DEF fill cover		
1	99-1098	<b>Windows: Privacy tint, dark vinyl applied to all three entry module entry door windows. NOTE: Module application only. Tint to be dark as possible.</b>		
1	STD	<b>Insulation: Pink, double sided radiant barrier/acoustic material, installed on curbside and streetside rear wheel wells.</b>		
1	STD	<b>Insulation: Spray in place foam, FR 2-Part Spray Foam, CP-1000 Kit 200, applied to curbside entry step well and both rear wheel wells</b>		
1	STD	Undercoating: Per QVM Guidelines		
	<b>03-</b>	<b>Brake, Turn &amp; Back-Up Lights</b>		

1	STD	<b>Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 600 Series LED.</b>		
1	STD	DOT Marker Lights: TecNiq LED, rubber grommet bezels; (7) S34-AC09-1 Amber- (5) on front of body as Marker lights, (2) side facing on rear extrusions as Turn Signals; (7) S34-RC90-1 Red-(5) on rear of Body as Marker lights, (2) side facing as Turn Signals.		
1	300100	<b>Lights: DOT, Brake and Turn, Interior, LED, Under rear overhead cabinet, Two (2) amber wired to turn signals; One (1) red wired to brake circuit</b>		
	<b>04-</b>	<b>Electrical, Power Distribution, Control Center &amp; Interior Lighting</b>		
1	STD	Battery Switch, Automatic: TST CDR-357. Located in Electrical Cabinet.		
2	STD	Antenna, Radio Coax Cable terminated behind driver's seat w/Power & Ground for each		
2	99-1456	<b>Electrical: Pre-wire 8AWG - 12VDC power and ground from battery to a Blue Sea PN: 5025B six circuit fuse block w/cover. NOTE: Both behind driver seat and one shall be "Battery Hot" and the other "Ignition Hot".</b>		
8	STD	<b>Lights: Dome, Whelen LED, 18-diodes w/chrome flange MX80EHZA , switched separately with Hi/Lo functions.</b>		
1	STD	Action Area Light: Whelen PSC0ADCR, 12 VDC LED Strip light, 6 diodes and On/Off switch on rear control panel		
1	STD	USB Port: Vanner VSS-USB dual port 2Amp mounted on A/A wall		
1	99-0988	<b>USB Port: Kussmaul 091-219-N dual USB port mounted in switch panel. Fits into standard switch slot. IATS LOCATION: Drivers side switch panel.</b>		
1	99-1084	<b>Shoreline: 125 VAC, 30-Amp, Kussmaul SUPER Auto Eject IATS. Kussmaul P/N: 091-159-30-120-081 wired w/hinged, BLUE/weatherproof cover, located above Compartment #2 on streetside. Will have to be mounted on the Kussmaul stainless steel E-Z mounting plate PN: 091-159-081-120 w/indicator light for access. Kussmaul P/N: 091-159-CON-3P-120 mating female connector to be shipped loose. IATS NOTE: Must specify function.</b>		
1	STD	Inverter: Pre-Wire w/switch on rear panel. Pre-wire located in lower pass-thru cabinet		
1	400160	<b>Inverter: Vanner 20-1050CUL- 1000watt w/battery charger and built in GFI. Remote controlled w/switch in rear panel. (This option deletes the GFI in the A/A wall). ILOS NOTE: OPTION 99-1955 IS REQUIRED WHEN ANY INVERTER IS MOUNTED IN ANYBULKHEAD or INTERIOR INCLOSED CABINET. Location: Must specify location.</b>		
1	99-1955	<b>Fan: Ventilation. (1) Mechantronics Fan Axial 120x25MM 12VDC fan PN: E1225E12AB-FSR mounted on cabinet door or side wall when any inverter is mounted in an interior, enclosed cabinet.</b>		
1	STD	Timer: 5-minute check-out, wired to CS Hight mode dome lights		
2	STD	12 VDC Outlets: (1) in Action Area, (1) in ALS Cabinet		
2	STD	125 VAC Outlets, Duplex: (1) in Action Area, (1) in ALS Cabinet		
1	STD	Breaker Box: 125 VAC w/20-Amp Breaker located on the rear wall of interior cabinet E. GFI receptacle located on the Action Area wall.		

1	STD	Rear Switch Panel: Engraved black plastic panel with (14) LED lighted switch positions for Dome Lights (2), Vacuum (1), Vent (1), A.A. Light (1), Inverter (1), <u>Spare switches</u> , <u>Thermostat and digital clock w/Mode Buttons</u> . MX01517.		
1	99-2056	<b>Front Console: Formed Aluminum, Gray Hammertone powder coated, attached to floor. Cup holders and map pocket at rear. Top forward area shall be flat and .250 thick for MDT. Switch panel with siren panel to rear. Customer Approval prior to build.</b>		
1	STD	Electrical Cabinet: Located over pass-thru w/latching, recessed, vented door		
	<b>05-</b>	<b>Warning Lights &amp; Siren</b>		
1	STD	<b>Lights: Warning, Whelen LED EMERGENCY Lighting Package- Ford, Chevy Type I and Type III- Models ONLY. NOTE: Does not include LED Scene Lights.</b>		
		<b>All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.</b>		
		<b>Front of Body: Add (7) Whelen 900 Series Super-LEDs- Specify pattern by LED Color (Red or White:R-R-R-W-R-R-R Outer (2) lights and (1) Center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.</b>		
		<b>Sides of Body: (4) Whelen 900 Series Red Super-LEDs: (2) each side in upper corners</b>		
		<b>Rear of Body: (4) Whelen 900 Series Red Super-LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level; (1) Whelen 600 Series Amber Super-LED in the center position over the rear doors.</b>		
		<b>Brake, Turn &amp; Back-Up Lights: Whelen 600 Series LEDs</b>		
		<b>Lights, Warning, Intersection Lights: (2) Whelen LINZ6R Series Red Super-LEDs on front fenders</b>		
1	500210	<b>Lights: Warning, (2) Whelen 700 Series Red Super LED 70R02FCR w/ clear lens and chrome bezel 7EFLANGE, IATS above rear wheel wells as rear intersection lights. Wire to Primary circuit only.</b>		
2	STD	Lights, Warning, Grille: WIONSMCR Red LED w/clear lenses & chrome flanges on center grille bar		
4	500127	<b>Lights: Scene/Load, Whelen 900 Series Super-LED 9SC0ENZR Gradient Opti-Scenelight™ with flange included- ILOS Halogen</b> <b>Specify Locations:</b>		
2	STD	<b>Lights, Load: Whelen 600 Series LED 6SC0ENZR, (2) on rear</b>		
1	99-0106	<b>Lights: Scene/Load, Rear side scene lights on each side to come "ON" in Reverse</b>		
1	STD	Flasher- For Warning Light System, Vanner 9860GCPE		
2	STD	Siren Speakers: Dual 100-watt drivers mounted through front bumper		
1	STD	Siren- Whelen 295 SL5A1, 200 Watt		
1	99-0706	<b>Lights: Warning, GTT 794H LED Opticom Emitter (Supplier P/N: 151-794H) with on/off switch in front console. Must be wired to de-activate when the vehicle is in park/neutral.</b> <b>Location: TBD</b>		

5	99-0567	<b>Lights: Ground, TecNiq E10-WS00-1, LED w/angled SS mounting bracket</b> <b>Location: standard locations. Appropriate light to come on when compartment/door or scene light is activated.</b>		
	<b>06-</b>	<b>Oxygen, Vacuum &amp; Miscellaneous Items</b>		
3	STD	Oxygen Outlets: Quick-connect style, (2) in Action Area, (1) over Squad Bench		
1	STD	Suction Aspirator System: Rico disposable container, mounted in Action Area w/gauge and quick-connect; GAST vacuum pump mounted in lower pass-thru cabinet		
1	STD	Oxygen Cylinder Retention: For "M" cylinder, black steel w/3-spring buckle straps and top collar, located in Compartment #1		
1	STD	O2 Regulator, Amvex, 50psi, pre-set		
	<b>07-</b>	<b>AC/Heat</b>		
1	STD	DELETE: HVAC System: High capacity Free Blow combination Heat-AC system and thermostat control in Action Area. HVAC unit is mounted in bulkhead at top of ALS		
1	99-1554	<b>HVAC System: ACC 125VAC/12VDC, Model #39660. High capacity free-blow combination Heat/AC system w/multi-speed fan, roof mounted condenser and thermostatic control on action area panel. Dodge Ram 4500/5500 Series Type 1 conversion with Super Tie-In to compressor mounted on OEM engine and 30Amp shoreline (separate line item) service to power 125VAC System.</b> <b>Installation performed by A.C.C. technicians. Wire to 30-Amp shoreline (separate line item) for power and battery charger. Install black control box on right hand wall in compt. #2. Install the charger/converter on the ceiling in compt. #2 towards right wall. NOTE: Dodge Ram 3500/4500/5500 Type I Only.</b>		
1	STD	Thermostat: Digital, A.C.C. PN-27058742A digital thermostat installed on A/A wall ILOS		
	<b>08-</b>	<b>Cabinets, Hardware &amp; Miscellaneous Items</b>		
1	STD	Main Streetside Wall Cabinets: Specify desired configuration-		
1	OPT	<b>Cabinet Configuration- CPR Seat w/EVS V-4 seat belt system and 2nd Action Area; includes (1) 125VAC and (1) 12VDC outlet in 2nd Action Area</b>		
		Main Wall Cabinets will have (1) adjustable shelf in each and sliding polycarbonate doors with full height extruded handles. See Prints for Configuration.		
2	99-0540	<b>Main Wall Cabinets: Restocking Feature, Interior Cabinet, Under 40" Width- Sliding Plex door w/hinged, keyed frame w/(2) Titan 15-pound gas struts and (2) spring-loaded elbow catches.</b> <b>Location(s): A and C</b>		
1	STD	Action Area Overhead Cabinet: Single cabinet full-height/full-depth of Action Area with sliding polycarbonate doors and full height extruded handles.		
1	STD	Action Area and Switch Panel: Laminated, sealed countertop and vertical panel with Suction system collection canister, Vacuum gauge, (2) Oxygen outlets, (1) USB, (1) 12VDC Outlet, (1) 125VAC Outlet and digital Thermostat. Switch panel MX01517 includes (10) switch positions and digital clock w/Mode Buttons.		


1	99-2010	<b>Action Area: Countertop, HDPE, Gray with Black accent bands, front and rear action area countertops. (On-line measuring.)</b>		
2	STD	Bulkhead Wall Cabinets: Electrical Cabinet above walk-thru w/hinged, latching, vented door.		
2	STD	Pass-Thru Cabinets: Upper cabinet- general storage w/hinged, latching door; Lower cabinet- general storage w/hinged, latching, vented door and location for inverter and vacuum pump on floor		
1	STD	DELETE: ALS Cabinet: Lower section- Locking storage for 747 box; Middle Section- General storage with hinged, non-locking doors and 1-adjustable shelf		
1	99-2149	<b>Cabinet: Custom ALS - Delete pull out drawer and combine lower ALS and drawer area into (1) section for installation of Mermaid MK-747 SS. Middle cabinet to have dual, 1/2" Acrylic doors with a 2-Point pinch latch on each door.</b>		
1	99-2089	<b>Refrigerator: Medi-Kool Stainless Steel model 747 SS w/back-mounted compressor and 1" mounting flange w/controls. Faceplate will be installed at top of Medi-Kool cabinet and compressor will be located directly behind it. Order with door hinged on right side. Unit to have Code lock and handle. Install per manufacturer's instructions regarding power supply (two individually fused power sources), fan and ventilation! (See option in cabinet section for cabinet modification charge). Unit to be installed in lower portion of AL on MSV-II models only. Must have a disconnect switch in the electrical cabinet for shutting unit off when out of service or for maintenance. <b>NOTE: Make sure cabinet build prints have the ventilation on back wall and outboard side wall of ALS cabinet.</b></b>		
1	STD	<b>Squad Bench:</b>		
		1 Full length hinged lid w/TriMark latch for access to interior storage		
		2 Full length upholstered seat cushion except over Sharps/Waste Area; formed upholstered back rest cushions and head pad for each seated position.		
		3 (2) EVS V-4 Belted seating positions w/progressive foam back and head pads and (3) short bottom straps for 2nd Patient restraint		
		4 Backer plate included in squad bench assembly at head end		
1	STD	Sharps/Waste: Drop-in style w/Red polycarbonate hinged lid with standard containers, located at head of squad bench.		
1	99-0511	<b>Cargo Net: Head of squad bench- Type I / III 153 Models ONLY. Squad Bench to accommodate mounting plate and cover secured to wall structure. (153 PNs: 86-101702, 33-101868, 33-101869) Requires squad bench assembly print different than standard.</b>		
1	99-0798	<b>Glove Box Holders: (3) w/hinged, black 11ga steel powder-coated door, in pad above Curbside Entry Door</b>		
1	800170-3	<b>Glove Box Holders: (3) w/hinged, black 11ga steel powder-coated door, in cabinet above rear entry door</b>		
1	800140	<b>Seating: EVS Swivel Base SB-2 two position swivel base for EVS Child seat, ILOS cabinet base</b>		
1	99-0613	<b>Assist Rail: 72" Powder Coated Safety Yellow SS 1.25" w/Radius Ends, ILOS -All Models</b>		
1	99-0614	<b>Grab Handles: (3) V-Style, Powder Coated Safety Yellow 1.25: SS w/Radius Ends- ILOS -All Models All Interior grab handles to be powder coated yellow.</b>		

8	STD	Reflective Striping, Door Open Protection: .50" Red reflective striping around interior door pan of all body doors.		
	<b>09-</b>	<b>Cots &amp; Miscellaneous Items</b>		
1	900065	<b>Cot Mount: Stryker 6377, Dual Position, Removable Mounting Locations: Center and streetside.</b>		
1	900075	<b>Cot Safety Hook: Install at rear threshold Specify for Stryker</b>		
	<b>10-</b>	<b>Paint &amp; lettering</b>		
1	1000082	<b>Paint: Type 1, Body and Chassis, Custom Color Color: Red Color Code: FLNA 30009 Configuration: Red entire cab and body red except for top of box to remain white. See photos. NOTE: Requires Paint Color and Code Prior to submitting order. Paint spray samples must be approved prior to scheduling.</b>		
1	1000100	<b>Roof Star ONLY, INSTALLED</b>		
		<b>SHIP LOOSE</b>		
2	STD	5 lb. Fire Extinguisher- Ship Loose		
		<b>FEES &amp; MISCELLANEOUS</b>		
1		Doc Fee		\$80.00
1		HGAC Fee Contract # AM10-18		\$1,000.00
1		Included - Flatbed transportation to San Luis, AZ		
1		Included - Final inspection for two at Medix Ambulance in Elkhart Indiana.		
<b>TOTAL ORDER PRICE BASED OFF OF HGAC AM10-18</b>				<b>\$158,832.00</b>

I have reviewed this Order as well as Pricing and approve the purchase.

Build time shall be 120 days after approved work order and drawings from the preconstruction meeting.

\_\_\_\_\_ Date: \_\_\_\_\_  
Customer Signature

 Date: **8-19-19**  
\_\_\_\_\_ Dealer Signature

Due to on-going product improvements and the changing requirements of the ambulance industry, MEDIX Specialty Vehicles, Inc. reserves the right to change product specifications and related products without prior notice and without any obligation to change prior products or parts. ALL PATENTS RIGHTS RESERVED.

I

|

