



DATE: September 10, 2018

QUOTE #:216959-03

**WILLIAMSON COUNTY FLEET**

Ron Roberts

3151 SE INNER LOOP STE B  
GEORGETOWN, TEXAS 78626-6343

**One (1) New Caterpillar Inc. Model: 120M2 Motor Graders with all standard equipment in addition to the additional specifications listed below:**

**STOCK NUMBER: HLK034187**

**YEAR: 2018**

SELL PRICE	\$246,839.00
EXT WARRANTY	Included
<b>TOTAL PRICE</b>	<b>\$246,839.00</b>
<hr/>	
SUB TOTAL	\$246,839.00
HET (0.216%)	\$533.17
<b>TOTAL TAXES</b>	<b>\$533.17</b>
TOTAL PURCHASE PRICE	\$247,372.17

**WARRANTY**

Standard Warranty:

Extended Warranty: 120-48 MO/6000 HR POWERTRAIN + HYDRAULICS + TECH


**Buy Board # 515-16**

In stock Holt

**NOTES**

**Rear Ripper**

Jeff Kell

  
Holt Cat 9-12-18

**MACHINE SPECIFICATIONS****STOCK NUMBER: HLK034187****SERIAL NUMBER: 0M9C00939****YEAR: 2018****HOURS: 6**

DESCRIPTION	REF.#
120M2 MOTOR GRADER	353-2916
LANE 2 ORDER	0P-9002
GLOBAL ARRANGEMENT	353-2886
MOLDBOARD, 14' PLUS	349-3048
RIPPER/SCARIFIER	332-2305
TOOTH, STRAIGHT	8J-1434
DRAWBAR, 4 SHOE CIRCLE GUIDES	253-4626
WEATHER, STANDARD	353-2891
ACCUMULATORS, BLADE LIFT	365-2203
PRECLEANER	356-1436
INSTALLATION ARRANGEMENT	365-2196
BASE + 1 (RIP)	309-9846
LIGHTS, FRONT HEADLIGHTS, LOW	309-9879
STARTING, (50 MT)	325-6335
CAB, PLUS	390-6789
INSTALLATION, ACCUGRADE READY	462-6388
JOYSTICK CONTROLS, ADVANCED	458-8701
TIRES, 17.5R25 BS VKT * D2A MP	252-0775
PUSH PLATE, COUNTERWEIGHT	367-6842
LANGUAGE, ENGLISH	310-0685
COMFORT PACKAGE	391-8968
SCREEN AS	360-0116
CONVERTER GP	361-3136
RADIO GP - AM/FM	477-1257
LIGHTS, WORKING, PLUS, HALOGEN	353-2895
CAMERA, REAR VISION	391-2914
MIRRORS, OUTSIDE MOUNTED	233-3295
GUARD, TRANSMISSION	366-2462
DRAIN, HIGH SPEED, ENGINE OIL	501-1160
PRODUCT LINK, CELLULAR PLE641	464-6443
TIER 4 FINAL AB&T CREDIT USING	477-3438
COOLANT, 50/50, -35C (-31F)	447-0898
ANTIFREEZE WINDSHIELD WASHER	0P-1939
ROLL ON-ROLL OFF	0P-2265
FUEL ANTIFREEZE, -25C (-13F)	0P-3978

## STANDARD EQUIPMENT

---

### CONSIST NOTE

The standard equipment list includes key components necessary for an operable

machine.

### POWERTRAIN

Air cleaner, dual stage dry type radial seal with service indicator through messenger and automatic dust ejector  
Air-to-air after cooler (ATAAC)  
Brakes, oil disc, four-wheel, hydraulic  
Demand fan, hydraulic  
Differential, lock/unlock, Automatic  
Drain, engine oil, ecology  
Engine, C7.1 with ACERT technology, diesel, with automatic engine derate

and idle control  
Meets U.S. EPA Tier 4 and EU Stage IIIb emission standards  
Fuel-water separator  
Parking brake, multi-disc, sealed and Oil cooled  
Priming pump, fuel  
Transmission, 8 speed forward and 6 speed reverse, power shift, direct drive  
VHP (Variable Horsepower)

### ELECTRICAL

Alarm, back-up  
Alternator, 150 ampere, sealed  
Batteries, maintenance free, heavy duty, 1125 CCA  
Electrical system, 24 volt  
Grade Control Ready  
-cab harness -software

-bosses -brackets  
-electrical hydraulic valves  
Lights, reversing  
Lights, roading, roof-mounted  
Lights, stop and tail, LED  
Product Link ready  
Starter, electric

### OPERATOR ENVIRONMENT

Air Conditioning with heater  
Display, digital speed and gear  
Gauge, machine level  
Gauges (analog) inside the cab  
Includes -fuel  
-articulation -engine coolant temp  
-engine RPM -hydraulic oil temp  
-regeneration  
Joystick, adjustable armrests  
Joystick gear selection  
Joystick hydraulic controls  
-right/left blade lift w/float position  
-front wheel lean and articulation  
-blade sideshift and tip -circle drive  
-centershift -steering  
Joystick hydraulic power steering

Ladders, cab, left and right side  
Messenger operator information system  
Meter, hour, digital  
Mirror, inside rearview, wide angle  
ROPS cab, sound suppressed  
70dB(A)  
ISO 6394  
Seat, cloth-covered, comfort suspension  
Seat belt, retractable 3"  
Throttle control, electronic  
Windows: laminated glass  
- fixed front with intermittent wiper  
- side and rear (3)

### TIRES, RIMS, AND WHEELS

A partial allowance for tires on 10"x24"  
is included in the base machine

price and weight.

## FLUIDS

Antifreeze

Extended Life Coolant to -35C/-30F

## OTHER STANDARD EQUIPMENT

Accumulators, brake, dual certified  
Bumper, rear, integrated with hitch  
CD ROM Parts Book  
Clutch, circle drive slip  
Cutting edges, 6" x 5/8" (152mm x 16mm)  
curved DH-2 steel, 3/4" mounting bolts  
(19mm)  
Doors, 4, engine compartment, (two left  
hand, two right hand,) locking  
Drawbar, 4 shoe with replaceable wear  
strips  
Endbits, 5/8" (16mm) DH-2 steel, 3/4"  
(19mm) mounting bolts

Fuel tank, 110 gallon (416 L)  
Ground level engine shutdown  
Hammer (emergency exit)  
Moldboard, 12'x 24" x 7/8" (3658mm x  
610mm x 22mm)  
Pump, hydr, high capacity (98cc/6cu in)  
Radiator, cleanout access (both sides  
with swing doors)  
Secondary steering  
SOS ports, engine, hydraulic  
transmission, coolant, fuel  
Tow hitch