



DATE: September 11, 2018

QUOTE #:225540-02

WILLIAMSON COUNTY FLEET

3151 SE INNER LOOP STE B
GEORGETOWN, TEXAS 78626-6343

One (1) New Caterpillar Inc Model: 120M2 BR Motor Graders with all standard equipment in addition to the additional specifications listed below:

SALE PRICE	\$248,633.00
EXT WARRANTY	Included
TOTAL PRICE	\$248,633.00
<hr/>	
SUB TOTAL	\$248,633.00
HET (0.216%)	\$537.05
TOTAL TAXES	\$537.05
TOTAL PURCHASE PRICE	\$249,170.05

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
Extended Warranty: 120-60 MO/5000 HR POWERTRAIN + HYDRAULICS + TECH

Buy Board # 515-16

Delivery February/March 2019

NOTES

Mid Mount Scarifier

Jeff Kell


Holt Cat 9-12-18

MACHINE SPECIFICATIONS

DESCRIPTION	REF.#
120M2/SPEC CHECK J.KELL 09/18	353-2916
TIRES, 17.5R25 BS VKT * D2A MP	252-0775
ACCUMULATORS, BLADE LIFT	365-2203
GUARD, TRANSMISSION	366-2462
MOLDBOARD, 14' PLUS	349-3048
CAMERA,REAR VISION	391-2914
CAB, PLUS	390-6789
JOYSTICK CONTROLS, ADVANCED	458-8701
COMFORT PACKAGE	391-8968
LIGHTS, ARM, FOLD DOWN	560-9017
LIGHTS, WORKING, PLUS, HALOGEN	353-2895
HEADLIGHTS,FRONT, LOW, HALOGEN	308-9370
MIRRORS, OUTSIDE MOUNTED	233-3295
STARTING, (50 MT)	325-6335
DRAIN, HIGH SPEED, ENGINE OIL	501-1160
PRODUCT LINK, CELLULAR PLE641	464-6443
TIER 4 FINAL AB&T CREDIT USING	477-3438
COOLANT, 50/50, -35C (-31F)	447-0898
ANTIFREEZE WINDSHIELD WASHER	0P-1939
LIGHTS, ROADING, HALOGEN	421-7810
LANGUAGE, ENGLISH	310-0685
DRAWBAR, 4 SHOE CIRCLE GUIDES	253-4626
WEATHER, STANDARD	353-2891
PRECLEANER	356-1436
INSTALLATION ARRANGEMENT	365-2196
LANE 3 ORDER	0P-9003
GLOBAL ARRANGEMENT	353-2886
MID MOUNT SCARIFIER PACKAGE	365-1336
DOMESTIC TRUCK	0P-0251
BASE + 1 (MMS)	309-9849
NO HITCH	393-4882
ROLL ON-ROLL OFF	0P-2265
FUEL ANTIFREEZE, -25C (-13F)	0P-3978
PUSH PLATE, COUNTERWEIGHT	367-6842

STANDARD EQUIPMENT

CONSIST NOTE

The standard equipment list includes key components necessary for an operable

machine.

POWERTRAIN

Air cleaner, dual stage dry type radial seal with service indicator through messenger and automatic dust ejector
Air-to-air after cooler (ATAAC)
Brakes, oil disc, four-wheel, hydraulic
Demand fan, hydraulic
Differential, lock/unlock, Automatic
Drain, engine oil, ecology
Engine, C7.1 with ACERT technology, diesel, with automatic engine derate

and idle control
Meets U.S. EPA Tier 4 and EU Stage IIIb emission standards
Fuel-water separator
Parking brake, multi-disc, sealed and Oil cooled
Priming pump, fuel
Transmission, 8 speed forward and 6 speed reverse, power shift, direct drive
VHP (Variable Horsepower)

ELECTRICAL

Alarm, back-up
Alternator, 150 ampere, sealed
Batteries, maintenance free, heavy duty, 1125 CCA
Electrical system, 24 volt
Grade Control Ready
-cab harness -software

-bosses -brackets
-electrical hydraulic valves
Lights, reversing
Lights, roading, roof-mounted
Lights, stop and tail, LED
Product Link ready
Starter, electric

OPERATOR ENVIRONMENT

Air Conditioning with heater
Display, digital speed and gear
Gauge, machine level
Gauges (analog) inside the cab
Includes -fuel
-articulation -engine coolant temp
-engine RPM -hydraulic oil temp
-regeneration
Joystick, adjustable armrests
Joystick gear selection
Joystick hydraulic controls
-right/left blade lift w/float position
-front wheel lean and articulation
-blade sideshift and tip -circle drive
-centershift -steering
Joystick hydraulic power steering

Ladders, cab, left and right side
Messenger operator information system
Meter, hour, digital
Mirror, inside rearview, wide angle
ROPS cab, sound suppressed
70dB(A)
ISO 6394
Seat, cloth-covered, comfort suspension
Seat belt, retractable 3"
Throttle control, electronic
Windows: laminated glass
- fixed front with intermittent wiper
- side and rear (3)

TIRES, RIMS, AND WHEELS

A partial allowance for tires on 10"x24"
is included in the base machine

price and weight.

FLUIDS

Antifreeze

Extended Life Coolant to -35C/-30F

OTHER STANDARD EQUIPMENT

Accumulators, brake, dual certified
Bumper, rear, integrated with hitch
CD ROM Parts Book
Clutch, circle drive slip
Cutting edges, 6" x 5/8" (152mm x 16mm)
curved DH-2 steel, 3/4" mounting bolts
(19mm)
Doors, 4, engine compartment, (two left
hand, two right hand,) locking
Drawbar, 4 shoe with replaceable wear
strips
Endbits, 5/8" (16mm) DH-2 steel, 3/4"
(19mm) mounting bolts

Fuel tank, 110 gallon (416 L)
Ground level engine shutdown
Hammer (emergency exit)
Moldboard, 12'x 24" x 7/8" (3658mm x
610mm x 22mm)
Pump, hydr, high capacity (98cc/6cu in)
Radiator, cleanout access (both sides
with swing doors)
Secondary steering
SOS ports, engine, hydraulic
transmission, coolant, fuel
Tow hitch