



DATE: September 12, 2018
QUOTE #:225609-01

WILLIAMSON COUNTY FLEET

3151 SE INNER LOOP STE B
GEORGETOWN, TEXAS 78626-6343

One (1) New Caterpillar Inc. Model: 416F Backhoe Loaders with all standard equipment in addition to the additional specifications listed below:

STOCK NUMBER: HCT010450

| | |
|----------------------|---------------------|
| SALE PRICE | |
| EXT WARRANTY | \$116,804.00 |
| TOTAL PRICE | Included |
| | \$116,804.00 |
| <hr/> | |
| SUB TOTAL | \$116,804.00 |
| HET (0.216%) | \$252.30 |
| TOTAL TAXES | \$252.30 |
| TOTAL PURCHASE PRICE | \$117,056.30 |

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
Extended Warranty: 48 MO/3000 HR POWERTRAIN + HYDRAULICS + TECH


Buy Board #515-16

Cab, 4x4, E-Stick, Quick Coupler Rear Bucket

NOTES

Includes: Front Quick Coupler, Bucket, and Forks
Added: Ride Control. Hydraulics 8 BNK MP for front Quick Coupler

Jeff Kell


Holt Cat 9-12-18

MACHINE SPECIFICATIONS**STOCK NUMBER: HCT010450**

| DESCRIPTION | REF.# |
|--------------------------------|----------|
| 416F2 BHL ST, TIER 4 HRC, 70KW | 450-8445 |
| CAB, STANDARD | 450-8680 |
| ENGINE, 70KW, C4.4 ACERT, T4F | 450-8754 |
| STICK, EXTENDABLE, 14FT, MECH | 450-8727 |
| AIR CONDITIONER, T4 | 450-8711 |
| TIRES, 12.5 80/19.5L-24, FS | 380-8961 |
| SEAT, FABRIC | 433-4805 |
| COUPLING,QD,THREADED WITH CAPS | 456-3390 |
| STABILIZER PADS, FLIP-OVER | 9R-6007 |
| RUST PREVENTATIVE APPLICATOR | 462-1033 |
| PACK, DOMESTIC TRUCK | 0P-0210 |
| BELT, SEAT, 2" SUSPENSION | 206-1747 |
| CONTROLS, BACKHOE PATTERN | 398-2496 |
| LANE 3 ORDER | 0P-9003 |
| SHIPPING/STORAGE PROTECTION | 461-6839 |
| INSTRUCTIONS, ANSI | 430-9944 |
| SERIALIZED TECHNICAL MEDIA KIT | 421-8926 |
| BUCKET, LOADER (NONE) | 325-5100 |
| LINES,HYD COUPLER 14FT E-STICK | 450-8578 |
| PT, 4WD, STD SHIFT, MECH | 450-8604 |
| LINES, COMBINED AUX, E-STICK | 398-2851 |
| HYDRAULICS, MP, 6FCN/8BNK | 450-8515 |
| RIDE CONTROL | 398-2680 |
| WORKLIGHTS (8) HALOGEN LAMPS | 491-6734 |
| PRODUCT LINK, CELLULAR, PL641I | 447-0049 |
| COUNTERWEIGHT, 1015 LBS | 337-9696 |
| BUCKET-SD, 24" 6.2 CFT | 219-3381 |
| COUPLER, PIN LOCK, BL F | 544-1901 |

STANDARD EQUIPMENT

CONSIST NOTE

THIS LISTING IS A GENERAL DESCRIPTION
OF A 416F2 BACKHOE LOADER EQUIPPED WITH

THE LOWEST CHARGE ITEMS.

BOOMS, STICKS AND LINKAGES

14'4" Center pivot excavator style
backhoe with 2-lever control
Boom transport lock
Swing transport lock
Street type stabilizer shoes
Bucket level indicator
Lift cylinder brace

Return-to-dig
(automatic bucket positioner)
Self-leveling loader with single lever
control
Transmission neutralizer switch
Single Tilt Loader

POWERTRAIN

Cat C4.4, 70KW (Net 87HP / 65kW)
- Direct Injection Turbo Charged Engine,
- with ACERT technology.
- US EPA Tier4 Final Emissions Compliant
- Selective Catalytic Reduction (SCR)
Water separator
Thermal starting aid system
A dry type axial seal air cleaner with
- integral precleaner
- automatic dust ejection system
- filter condition indicator
Hydraulically boosted multi-plate wet
disk brake with

- dual pedals & interlock
Differential lock
Drive-line parking brake
Torque converter
Transmission-four speed synchro mesh inc
- power shuttle
- neutral safety switch
Spin-on filters for
- fuel
- engine oil
- transmission oil
Outboard Planetary Rear Axles

HYDRAULICS

Load sensing, variable flow system with
- 35 gpm axial piston pump
6 micron hydraulic filter
O-ring face seal hydraulic fittings

Caterpillar XT-3 hose
Hydraulic oil cooler
Flow-Sharing Hydraulic Valves
Hydraulic suction strainer

ELECTRICAL

12 volt electrical start
150 ampere alternator
Horn
Backup alarm
Hazard flashers/turn signals
Halogen head lights (2)
Halogen rear flood lights (2)

Stop and tail lights
Audible system fault alarm
Key start/stop system
880 CCA maintenance free battery
Battery disconnect switch
External Power Receptacle (12v)
Remote jump start connector

OPERATOR ENVIRONMENT

Lighted gauge group
Interior rearview mirror
Rear fenders
ROPS canopy

2-inch retractable seat belt
Hand and foot throttle
Air suspension seat
Coat Strap

FLUIDS

Antifreeze - Extended Life Coolant

-30C (-20F)

OTHER STANDARD EQUIPMENT

Hydrostatic power steering
Standard Storage Box
Transport tie-down points
Ground line fill fuel tank with
44 gallon capacity
Ground line fill diesel exhaust fluid
tank with 5 gallon capacity

Rubber impact strips on radiator guards
Bumper
CD-ROM Parts Manual
Backhoe Safety Manual
Operations and Maintenance Manual
Lockable hood
Tire Valve Stem Protection