



CE - #515-16, GM - #529-17

KX057-4R1A WEB QUOTE #1243669

Date: 2/5/2019 5:47:44 AM

-- Customer Information --

Geer, Keith

Williamson County Parks & Rec

kgeer@wilco.org

512-364-8336

Quote Provided By  
EWALD KUBOTA, INC.  
Justin DeSpain  
2650 N AUSTIN AVE  
GEORGETOWN, TX 78626  
email: justin.d@ewaldkubota.com  
phone: 5128688686

-- Standard Features --

-- Custom Options --



**Kubota**

K Series

KX057-4R1A

\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**FEATURES**

Eco Plus System  
Auto Idler  
Rubber Track Model  
ROPS/OPG (Top Guard, Level I) 4-Post Canopy  
Suspension Seat  
Kubota 3 Hydraulic Pump Load Sensing System  
1 Gear, 2 Variable Displacement Pumps  
All Controls Hydraulic Pilot Controls  
Two Operating Pattern Selection System  
Accumulator  
Digital Control Panel  
Attachment Flow Presets, Service Alerts  
Float Angle Blade w/ Bolt-on Cutting Edge  
360 Degree Full Rotation  
70 Degree Left, 55 Degree Right Boom Swing  
19.8 gpm Adjustable Auxiliary Hydraulics Port 1  
Auxiliary Hydraulics Diverter Valve  
Thumb Bracket and Relief Valves  
Five Second Quick Preheat System  
Key Switch Stop System  
Half Pitch Rubber Tracks  
Self Bleed Fuel System  
Auto-Downshift Two Speed Travel System  
Swivel Negative Brake  
Travel Negative Brake  
Third Line

**ENGINE**

V2607 Kubota DI CRS Tier 4 Diesel Engine  
4 Cylinder, 4 Cycle  
45.2 Net HP @ 2200 rpm

**OPERATIONAL**

Max Digging Depth 12' 8.2"  
Max Digging Radius @ Ground Level 20' 0.5"  
Max Vertical Digging Depth 5' 7.3"  
Max Dumping Height 13' 8.6"

**DOZER BLADE**

**DIMENSIONS**  
Width 77.2"  
Height 16.1"  
Lift Above Ground 17.3"  
Drop Below Ground 16.1"

**PERFORMANCE**

Digging Force @ Bucket (K7919) 11,177 lbs.  
Digging Force @ Dipper Arm 5,644 lbs.  
Travel Speed (Low) 1.8 mph  
Travel Speed (High) 3.1 mph  
Climbing Ability 36% / 20°  
Lift Capacity 3,410 lbs.  
Over Front  
Blade Grounded  
4.0 Ft. Load Point Height  
12.0 Ft. Load Radius

**DIMENSIONS AND OPERATING WEIGHT**

KX057-4R1A, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Canopy,  
Angle Dozer Blade, Dipper Arm, Counterweight  
Overall Length 18' 1.3"  
Overall Width 6' 5.2"  
Overall Height 8' 4.4"  
Operating Weight 12,620 lbs.\*  
Ground Clearance 12' 0.2"  
\* Includes operator's weight, 175 lbs.

KX057-4R1A Base Price: \$72,000.00

(1) 18" QUICK ATTACH TRENCHING BUCKET \$1,184.00  
K7918A-18" QUICK ATTACH TRENCHING BUCKET

(1) QUICK COUPLER \$930.00  
K7915A-QUICK COUPLER

(1) HYDRAULIC THUMB KIT/U55/KX057-4 \$2,307.00  
K7937-HYDRAULIC THUMB KIT/U55/KX057-4

**Configured Price: \$76,421.00**

BUY BOARD Discount: (\$18,341.04)

**SUBTOTAL: \$58,079.96**

Dealer Assembly: \$85.00

Freight Cost: \$590.00

PDI: \$250.00

Total Unit Price: \$59,004.96

Quantity Ordered: 1

Final Sales Price: \$59,004.96

**Purchase Order Must Reflect the Final Sales Price**

To order equipment – purchase orders must be made out and returned to:

**Kubota Tractor Corporation**  
Attn: National Accounts  
1000 Kubota Drive  
Grapevine, TX 76051  
or email [NA.Support@kubota.com](mailto:NA.Support@kubota.com)  
or call 817-756-1171 or fax 844-582-1581

\*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.