



Please find a brief description of our Rock Asphalt.

PRODUCT DESCRIPTION & USE

Rock Asphalt is a naturally occurring asphalt material meeting TXDOT 330D specification, packaged for the purpose of permanently repairing damaged areas in asphalt surfaces (driveways, parking lots, and roads). By following three simple application steps, Rock Asphalt can be applied in hot and cold, wet or dry conditions with no mixing required and is ready for traffic immediately.

BENEFITS TO MUNICIPALITIES & STATES

- Natural, VOC Free Product
- Re-open roads to traffic immediately after application
- Product can be used in all weather conditions, hot/cold, wet/dry
- No special tools, machinery, or preparation required
- Easy application

SIZE & YIELD

- Bulk Truckload
- Approx 21-23 Cu Yds Per Truckload

APPLICATION

- **Sweep** the area to be filled to remove all loose debris.
- **Fill the hole** with Rock Asphalt to a height of ½ inch above the surrounding pavement surface.
- Drive over Rock Asphalt with a car, truck, or compactor to **compact** it into the hole.

CONTRACTS

BUYBOARD: 612-20 (Cold Mix Asphalt)

Purchasing Coop of America: 3-153-16 (Roadway Materials & Related Items)

TIPS USA: 181106 (Roadway & Site Control Products)





To: Williamson County

Attn: Shea Webb

Date: 12-7-21

Contract: Buyboard 612-20

Based on Blanket PO for 852 Cubic Yards

Delivery: 1400 NE Inner Loop
Georgetown, TX 78626

Item: RA-BLK Road Rescue Asphalt Repair, TXDOT Specification 330D

Qty: Approx 21-23 Cu Yds Per Load

Price: \$134.10

PRICING IS DELIVERED TO CUSTOMER
FULL TRUCKLOAD ONLY
REAR DUMP ONLY

