



DATE: Jan 24, 2023

QUOTE # [REDACTED]

**WILLIAMSON COUNTY FLEET**

**Kell, Jeffrey**  
512.917.3277

3151 SE INNER LOOP STE B  
GEORGETOWN, TEXAS 78626-6343

**One (1) New Caterpillar Inc Model: CB2.7GC Paving and Compaction with all standard equipment in addition to the additional specifications listed below:**

SALE PRICE	\$57,410.00
EXT WARRANTY	Included
<b>TOTAL PRICE</b>	<b>\$57,410.00</b>
<hr/>	
<b>SUB TOTAL</b>	<b>\$57,410.00</b>
<b>TOTAL PURCHASE PRICE</b>	<b>\$57,410.00</b>

**WARRANTY**

Standard Warranty: 12 Month/Unlimited Hours Total Machine

**Sourcewell # 032119-CAT**

**Price includes: Holt Cat New Machine Delivery Specialist providing full machine operation and maintenance demonstration at your site. Also train operators includes Safety.**

**Delivery: 3-6 months depending on time of Factory order. Subject to change**

**NOTES**

**Extended Warranty Powertrain, Hydraulics, Technology ADD:**  
**36 month/1500 hours - \$750.00**  
**48 months /2000 hours - \$1,375.00**  
**60 months//2000 hours - \$1,785.00**

DATE: Jan 24, 2023QUOTE #:Quote [REDACTED]

**MACHINE SPECIFICATIONS**

DESCRIPTION	REF.#
-------------	-------

DESCRIPTION	REF.#
TFR/QP1/ROPS/48"	547-4537
LANE 3 ORDER	0P-9003
ENGINE, CAT C1.7T	564-8160
HYDRAULICS, STD	559-1655
LIGHTS, WORKING, LED	568-5154
SWITCH, BATTERY DISCONNECT	565-3708
SEAT, WITH SAFETY SWITCH	573-5962
SUPPORT, FIXED FOR SEAT	364-2278
SEAT BELT, 3"	542-6995
ROPS, FOLDABLE, LOCKABLE	574-6088
TRAVEL CONTROL, COVER	432-8451
PRODUCT LINK, CELLULAR PL243	577-1414
SINGLE POINT LIFT	574-6034
GUARDS, BUMPER	569-8093
DRUM SCRAPER, FIXED	603-5914
OIL, HYD, STANDARD	574-6039
INSTRUCTIONS, ANSI	574-6030
SERIALIZED TECHNICAL MEDIA KIT	421-8926
LIGHTS, WARNING (W/O CANOPY)	575-4457
CERTIFICATE OF ORIGIN	0F-5109
ROLL ON-ROLL OFF	0G-0044
PREPARATION FOR INSPECTION	0P-2046
LANE 3 ORDER	0P-9003
ENGINE, CAT C1.7T	564-8160
HYDRAULICS, STD	559-1655
LIGHTS, WORKING, LED	568-5154
SWITCH, BATTERY DISCONNECT	565-3708
SEAT, WITH SAFETY SWITCH	573-5962
SUPPORT, FIXED FOR SEAT	364-2278
SEAT BELT, 3"	542-6995
ROPS, FOLDABLE, LOCKABLE	574-6088
TRAVEL CONTROL, COVER	432-8451
PRODUCT LINK, CELLULAR PL243	577-1414
SINGLE POINT LIFT	574-6034
GUARDS, BUMPER	569-8093
DRUM SCRAPER, FIXED	603-5914
OIL, HYD, STANDARD	574-6039
INSTRUCTIONS, ANSI	574-6030
SERIALIZED TECHNICAL MEDIA KIT	421-8926
LIGHTS, WARNING (W/O CANOPY)	575-4457
CERTIFICATE OF ORIGIN	0F-5109
ROLL ON-ROLL OFF	0G-0044
PREPARATION FOR INSPECTION	0P-2046

#### STANDARD EQUIPMENT

## POWERTRAIN

CAT C1.7T diesel engine  
-Turbocharged, EPA tier 4 final and EU stage IV certified engine with DOC/DPF aftertreatment  
-Gross power per ISO 14396 18.4 kW (24.7 hp) @2200 RPM  
-Liquid cooled, direct injection  
Aftercooler, air to air (ATAAC)  
Fuel filter/water separator/electronic priming pump and electronic water indicator

Dual element air cleaner with dust ejection  
3 Engine speeds - idle, med, high  
Engine belt guard  
Programable auto Idle Shutdown  
Aluminum bar plate cooling system  
Hydrostatic transmission  
Auto warmup cycle  
Hydraulic on demand cooling fan  
Service and parking brakes - spring applied hydraulically released

## ELECTRICAL

Engine start switch with auto preheat  
12-volt starting and charging system  
85-ampere alternator  
Maintenance free battery, 750 CCA  
Isolated and cooled battery compartment  
Backup alarm and front facing warning

horn  
Product Link ready  
Beacon ready  
Diagnostic connector  
CAT ET Compatible  
Labeled and sealed electrical connectors  
LED work lights (2 front, 2 rear)

## OPERATOR ENVIRONMENT

Gauge Cluster:  
-Water level gauge  
-Fuel level gauge  
-Engine coolant temperature gauge  
-Hour meter  
-Faults  
Simple rocker switches  
Emergency stop switch  
Operator warning system indicators:  
-Parking brake engaged  
-Operator out of seat  
-Hydraulic oil temperature high  
-Hydraulic oil restriction  
-Engine oil low pressure  
-Electrical system voltage low  
-Low fuel  
-Engine preheat

-Engine emission system  
-High/low vibe frequency  
-Beacon status  
Lockable, vandalism guard for instrument panel  
Travel control, single lever  
High Vis Orange retractable seatbelt, 76mm (3")  
2 platform handrails / single guardrail  
Steering wheel spinner  
12-volt power point  
ROPS  
Sealed storage compartment  
Isolated operator platform  
Vibration reducing, diesel resistant rubber floormat

## DRUMS

Two smooth drums: 1200 mm (47.2") wide x 720 mm (28.3") diameter and 14 mm (0.55") thick  
Single amplitude with dual frequency vibratory system  
Automatic vibration control to prevent vibration in neutral

Selection of front drum or both drum vibration  
Pressurized drum watering system with selectable continuous or intermittent flow  
4 nozzle spray bars  
Triple spray system filtration

## FLUIDS

Premixed 50% concentration of extended life coolant with freeze protection

to -37C (-35F)

## OTHER STANDARD EQUIPMENT

Lockable engine enclosure with safety hold open latch

Lockable external fuel fill

Sealed for life hitch bearings

Sight gauges:

-Hydraulic tank level

-Engine Coolant

Lockable hydraulic tank cap

Articulated frame with safety lock

3 point hitch

4 transport tie-down and 4 lift points

55L (14.5 gal) fuel tank capacity

200L (52.8 gal) water tank capacity

6 Quick connect hydraulic pressure test ports + 1 SOS port

Caterpillar o-ring face-seals couplings

Offset hitch with 50 mm (2") of manual adjustment

Ecology drains:

-Hydraulic Tank

-Radiator

-Engine Oil

