

-- Standard Features --



S Series SVL75-3HWC  
\*\*\* EQUIPMENT IN STANDARD MACHINE \*\*\*

**FEATURES**

Vertical Lift Path Loader Frame  
Standard Front Quick Coupler,  
Float Standard  
Hydraulic Quick Coupler  
Option, High Flow Hydraulics  
Loader Boom Lock  
Open ROPS & Air Conditioned  
ROPS/FOPS Cab Models  
High Back, Adjustable, Vinyl,  
Suspension Seat  
2" Retractable Seat Belt and 2-  
Piece Seat Bar  
12V Electric Outlet  
17.4 gpm Auxiliary Hydraulics  
standard, 29.3 gpm Option  
Direct To Tank Return Line  
Rigid Mounted Undercarriage, 4  
Lower Track Rollers  
Rubber Tracks, 12.6" Standard,  
15" Optional  
Two Speed Travel System  
Automatic Wet Disk Parking  
Brake  
Kubota 4 Hydraulic Pump Load  
Sensing System  
2 Gear, 2 Variable  
Displacement Pumps  
Hydraulic Joystick Controls  
ISO Operating Pattern  
Hand And Foot Throttle  
Controls  
Electronic Travel Torque  
Management  
Automatic Glow Plugs  
Key Switch Stop/Start System  
Self Bleed Fuel System  
2 Front and 2 Rear Working  
Lights  
Hour Meter, Engine  
Temperature and Fuel  
Gauges and Warning Lights  
Horn and Backup Alarm  
Lockable Fuel Cap  
Bolt On Grab Handles to enter  
machine

**BASIC UNITS**

SVL75-3, 15.0" Rubber Tracks,  
A/C ROPS/FOPS Cab  
Hydraulic Quick Coupler

**ENGINE**

V3307 Kubota CR-TE4, Tier 4  
Diesel Engine  
4 Cylinder, 4 Cycle, Turbo Charged  
74.3 Gross HP @ 2400 rpm

**DIMENSIONS**

Cab Height 82.0"  
Width (without attachment) 65.9"  
Width with wide track option  
(without attachment) 68.3"  
Length (without attachment) 109.0"  
Length of Track on Ground 56.5"

**OPERATIONAL**

**DIMENSIONS**

Operating Weight\*, SVL75H, 12.6"  
Rubber Tracks, Open  
ROPS/FOPS Cab, Mechanical  
Quick Coupler 9,039 lbs.  
Rated Operating Capacity (@ 35%  
of Tipping Load) 2,300 lbs.  
Rated Operating Capacity (ROC)  
@ 35% of Tipping Load complies  
with ISO 14397-1 and SAE J 818  
for crawler loaders  
Rated Operating Capacity (ROC)  
@ 50% of Tipping Load 3,285 lbs.  
Tipping Load 6,570 lbs.  
Auxiliary Hydraulics Flow 17.4  
gpm  
Travel Speed (Low / High) 4.7 / 7.1  
mph  
Reach @ Maximum Height 41.7"  
Height to Hinge Pin 119.1"  
Ground Pressure 5.6 psi.  
Traction Force 9,678 lbf.

\* Includes operator's weight, 175  
lbs.

-- Custom Options --

SVL75-3HWC Base Price: \$77,808.00

(1) HOSE STAY FOR SSV/SVL MODELS	\$106.00
S6763-HOSE STAY FOR SSV/SVL MODELS	
(1) 74" HEAVY DUTY LOW PROFILE LONG	\$2,490.00
FLOOR BUCKET (19.2 CU-FT) W/TEETH	
AP-HD74LLT-74" HEAVY DUTY LOW PROFILE LONG FLOOR	
BUCKET (19.2 CU-FT) W/TEETH	
(1) AIR RIDE SEAT SUSPENSION KIT	\$683.00
S6679-AIR RIDE SEAT SUSPENSION KIT	
(1) SVL75-3 TELEMATICS HARNESS	\$55.00
S6708-SVL75-3 TELEMATICS HARNESS	
(1) KubotaNOW TELEMATICS MODEM	\$444.00
DCU6700-KubotaNOW TELEMATICS MODEM	
<b>Configured Price:</b>	<b>\$81,586.00</b>
<b>Sourcewell Discount:</b>	<b>(\$19,580.64)</b>
<b>SUBTOTAL:</b>	<b>\$62,005.36</b>
<b>Dealer Assembly:</b>	<b>\$205.33</b>
<b>Freight Cost:</b>	<b>\$831.25</b>
<b>PDI:</b>	<b>\$400.00</b>

Total Unit Price: \$63,441.94  
Quantity Ordered: 1  
Final Sales Price: \$63,441.94

**Final pricing will be based upon pricing at the time of  
final delivery to Sourcewell members.  
Purchase Order Must Reflect Final Sales Price.**

**To order, place your Purchase Order directly with the quoting  
dealer**

\*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.