

CURVE TABLE					
NUMBER	ARC LENGTH	RADIUS	DELTA	CHORD BEARING	CHORD DISTANCE
C1	27.28'	20.00'	78 <b>°</b> 08'25"	S 58*41'53" E	25.21'
C2	117.20'	330.00'	20°20'57"	S 30°16'24" E	116.59'
C3	39.27'	25.00'	90°00'00"	N 65°05'56" W	35.36'
C4	39.40'	25.00'	90°17'52"	S 24°45'08" W	35.45'
C5	275.75'	60.00'	263°19'04"	N 33*53'26" E	89.65'
C6	49.29'	475.00'	5*56'44"	N 17 <b>°</b> 25'26" W	49.27
C7	39.14'	25.00'	89*42'08"	N 65°14'52" W	35.26'
C8	39.40'	25.00'	90°17'52"	N 24°45'08" E	35.45'
C9	21.03'	25.00'	48*11'21"	N 44°29'29" W	20.41'
C10	162.91'	50.00'	186 <b>°</b> 40'38"	S 24°45'10" W	99.83'
C11	21.03'	25.00'	48"11'25"	S 86°00'13" E	20.41'
C12	21.03'	25.00'	48"11'23"	N 45°48'23" E	20.41'
C13	162.39'	50.00'	186°04'53"	N 65°14'52" W	99.86'
C14	21.03'	25.00'	48"11'23"	S 03°41'53" W	20.41'
C15	39.14'	25.00'	89*42'08"	S 65°14'52" E	35.26'
C16	21.03'	25.00'	48 <b>°</b> 11'23"	N 45°48'23" E	20.41'
C17	160.19'	50.00'	183 <b>°</b> 33'32"	N 66°30'33" W	99.95'
C18	21.03'	25.00'	48"11'23"	S 01"10'32" W	20.41'
C19	38.04'	25.00'	87*10'46"	S 66°30'33" E	34.47'
C20	40.50'	25.00'	92*49'14"	S 23°29'27" W	36.21'
C21	21.03'	25.00'	48"11'23"	S 47°00'51" E	20.41'
C22	165.11'	50.00'	189"12'00"	N 23°29'27" E	99.68'
C23	21.03'	25.00'	48*11'23"	N 86°00'14" W	20.41'
C24	39.27'	25.00'	90°00'00"	S 24°54'04" W	35.36'
C25	95.89'	270.00'	20°20'57"	S 30°16'24" E	95.39'
C26	3.15'	25.00'	7*13'02"	S 44°03'23" E	3.15'
C27	39.14'	25.00'	89 <b>°</b> 42'08"	S 65°14'52" E	35.26'
C28	39.40'	25.00'	90°17'52"	S 24°45'08" W	35.45'
C29	38.04'	25.00'	87°10'46"	N 66°30'33" W	34.47'
C30	40.50'	25.00'	92*49'14"	N 23°29'27" E	36.21'
C31	39.14'	25.00'	89*42'08"	S 65°14'52" E	35.26'
C32	39.40'	25.00'	90°17'52"	S 24°45'08" W	35.45'
C33	38.04	25.00'	87°10'46"	N 66°30'33" W	34.47'
C34	40.50'	25.00'	92*49'14"	N 23°29'27" E	36.21'
C35	39.40'	25.00'	9017'52"	N 24°45'08" E	35.45'
C36	39.14	25.00'	89*42'08"	S 65°14'52" E	35.26'
C37	39.40'	25.00'	9017'52"	S 24°45'08" W	35.45'
C38	39.14'	25.00'	89*42'08"	N 65°14'52" W	35.26'
C39	36.36'	330.00'	618'44"	S 3717'31" E	36.34'
C40	45.29'	330.00	7*51'50"	S 3012'14" E	45.26'
C40 C41	35.55'	330.00	610'23"	S 23"1'07" E	35.54'
C42	32.15'	60.00'	30°41'56"	N 68*39'31" E	31.76'
C42 C43	32.15	60.00	30°41'56"	S 80°38'33" E	31.76
C44	25.72'		24°33'53"	S 53°00'38" E	25.53'
C44 C45		60.00'			
	27.52'	60.00'	26°16'37"	S 27°35'23" E	27.28'
C46	11.53'	475.00'	1*23'28"	N 15°08'49" W	11.53'
C47	37.76'	475.00'	4°33'16"	N 18°07'10" W	37.75'
C48	34.03'	270.00'	7°13'17"	S 36°50'14" E	34.01'
C49	61.86' 20.45'	270.00' 50.00'	13°07'39" 23°26'22"	S 26°39'45" E S 73°37'44" E	61.73' 20.31'

CURVE TABLE					
NUMBER	ARC LENGTH	RADIUS	DELTA	CHORD BEARING	CHORD DISTANCE
C51	38.38'	50.00'	43 <b>°</b> 58'39"	N 72°39'46" E	37.44'
C52	42.88'	50.00'	49*08'01"	N 26°06'26" E	41.58'
C53	39.93'	50.00'	45 <b>*</b> 45'22"	N 21°20'15" W	38.88'
C54	23.47'	50.00'	26 <b>°</b> 53'37"	N 57°39'44" W	23.25'
C55	11.52'	25.00'	26 <b>°</b> 23'55"	S 09*43'12" E	11.42'
C56	28.98'	25.00'	66 <b>°</b> 25'19"	S 36°41'25" W	27.39'
C57	28.88'	25.00'	66 <b>°</b> 11'43"	S 77*00'04" E	27.30'
C58	9.16'	25.00'	20 <b>°</b> 59'03"	S 33°24'41" E	9.10'
C59	3.14'	25.00'	7*12'15"	S 19*19'02" E	3.14'
C60	17.88'	25.00'	40*59'08"	S 04°46'39" W	17.50'
C61	29.14'	50.00'	33°23'47"	N 08°34'19" E	28.73'
C62	31.35'	50.00'	35 <b>*</b> 55'29"	N 26°05'18" W	30.84'
C63	26.99'	50.00'	30 <b>°</b> 55'55"	N 59°31'00" W	26.67'
C64	26.99'	50.00'	30 <b>°</b> 55'55"	S 89*33'04" W	26.67'
C65	42.23'	50.00'	48*23'33"	S 49*53'20" W	40.99'
C66	3.47'	50.00'	3 <b>*</b> 58'52"	S 23*42'07" W	3.47'
C67	0.77'	25.00'	1°45'14"	S 19°31'11" E	0.77
C68	20.26'	25.00'	46 <b>°</b> 26'09"	S 04*34'30" W	19.71'
C69	26.68'	50.00'	30 <b>°</b> 34'05"	N 12°30'32" E	26.36'
C70	33.65'	50.00'	38 <b>*</b> 33'43"	N 22°03'22" W	33.02'
C71	30.31'	50.00'	34 <b>°</b> 43'48"	N 58°42'07" W	29.85'
C72	33.81'	50.00'	38*44'17"	S 84*33'50" W	33.17'
C73	37.95'	50.00'	43*29'01"	S 43°27'12" W	37.04'
C74	17.69'	25.00'	40*33'07"	N 41°59'15" E	17.33'
C75	3.33'	25.00'	7*38'16"	N 66°04'56" E	3.33'
C76	20.80'	25.00'	47 <b>°</b> 39'59"	S 86°15'56" E	20.20'
C77	0.23'	25.00'	0°31'26"	S 62°10'14" E	0.23'
C78	50.88'	50.00'	58*18'18"	S 88*56'20" W	48.71
C79	30.57	50.00'	35 <b>°</b> 02'07"	S 42°16'08" W	30.10'
C80	34.57'	50.00'	39 <b>°</b> 36'35"	S 04°56'47" W	33.88'
C81	23.75'	50.00'	27"12'49"	S 28°27'55" E	23.53'
C82	23.14'	50.00'	26*30'49"	S 55°19'44" E	22.93'
C83	158.21'	60.00'	151°04'39"	S 22°13'46" E	116.20'

LINE TABLE				
NUMBER	BEARING	DISTANCE		
L1	S 45°04'10" W	107.74'		
L2	S 52°45'08" W	30.45'		
L3	S 69°34'25" W	45.00'		
L4	S 74°53'28" W	86.24'		
L5	S 40°26'52" E	45.49'		
L6	S 49*33'08" W	114.95'		
L7	S 61°05'21" W	61.29'		
L8	S 19*37'41" E	55.47'		
L9	S 36*41'27" E	128.82'		
L10	S 62°14'04" W	35.21'		
L11	S 75°07'18" W	64.47'		
L12	N 88*44'21" W	81.90'		
L13	N 51°53'12" W	93.72'		
L14	N 3012'28" W	49.29'		
L15	N 22*32'18" W	45.03'		
L16	N 08°27'42" W	45.99'		
L17	S 31°33'00" E	108.82		
L18	S 58 <b>°</b> 06'37" E	134.32'		
L19	S 35°15'14" E	42.67'		
L20	S 1719'16" E	75.83'		
L21	S 11 <b>°</b> 57'05" E	122.50'		
L22	S 40°26'52" E	57.47'		
L23	S 20°05'56" E	37.32'		
L24	S 14°27'05" E	51.73'		
L25	N 69*54'04" E	95.13'		
L26	S 69*54'04" W	94.87		
L27	S 69*54'04" W	96.35'		
L28	N 69°54'04" E	93.88'		
L29	N 20°05'56" W	37.32'		
L30	N 40°26'52" W	66.59'		
L31	S 20°05'56" E	55.00'		
L32	N 69°54'04" E	117.54'		
L33	S 69*51'27" W	118.48'		
L34	N 69°36'12" E	120.00'		
L35	N 69°36'12" E	120.00'		
L36	N 69°36'12" E	15.00'		
L37	S 69'36'12" W	98.54		
L38	S 70°09'27" W	95.24'		

RECORD LINE TABLE			
NUMBER	BEARING	DISTANCE	
(L17)	(S 31°32'54" E)	(108.82')	
(L18)	(S 58°07'07" E)	(134.34')	
(L19)	(S 3518'21" E)	(42.59')	
(L20)	(S 17°13'50" E)	(75.89')	

STREET NAMES						
STREET	R.O.W. WIDTH	PAVEMENT WIDTH	CENTERLINE LENGTH	DESIGN SPEED	MAINTENANCE AUTHORITY	CLASSIFICATION
BAUER LOOP	50 FEET	33 FEET	2,226 FEET	25 MPH	PUBLIC	LOCAL ROAD (URBAN)
DANIELSON STREET	50 FEET	33 FEET	851 FEET	25 MPH	PUBLIC	LOCAL ROAD (URBAN)
LANGHORNE BEND	50 FEET	33 FEET	2,138 FEET	25 MPH	PUBLIC	LOCAL ROAD (URBAN)
PLANT LANE	60 FEET	40 FEET	258 FEET	35 MPH	PUBLIC	COLLECTOR ROAD (URBAN)
TOTAL LINEAR FEET OF NEW STREETS:			5,473 FEET			

FINAL PLAT LARIAT SECTIONS 3 & 4

BGE, Inc. Austin, Texas 78728

## METES & BOUNDS DESCRIPTION

ALL THAT CERTAIN PARCEL OR TRACT OF LAND OUT OF THE JAMES HACKETT SURVEY, ABSTRACT NO. 312, SITUATED IN WILLIAMSON COUNTY, TEXAS; BEING ALL OF THAT CALLED 34.22 ACRE TRACT OF LAND AS CONVEYED TO PHAU-LARIAT 108, LLC, BY SPECIAL WARRANTY DEED RECORDED IN DOCUMENT NO. 2021138566 OF THE OFFICIAL PUBLIC RECORDS OF WILLIAMSON COUNTY, TEXAS; AND BEING MORE PARTICULARLY DESCRIBED BY METES AND BOUNDS AS FOLLOWS:

BEGINNING at a 1/2-inch iron rod with cap stamped "LSI SURVEY" found at the southwest corner of a called 42.34 acre tract of land as conveyed to Tri Pointe Homes Texas, Inc. by special warranty deed recorded in Document No. 2021138718 of the Official Public Records of Williamson County, Texas, being the most easterly southeast corner of the above described PHAU—LARIAT 108, LLC 34.22—acre tract for the most easterly southeast corner and POINT OF BEGINNING of the herein described tract;

THENCE, with the southeasterly lines of said PHAU—LARIAT 108, LLC 34.22 acre tract, the following seventeen (17) courses:

- 1.S 45°04'10" W a distance of 107.74 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an angle point;
- 2.S 52°45'08" W a distance of 30.45 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set for an angle point;
- 3.S 69°34'25" W a distance of 45.00 feet to a 1/2—inch iron rod with cap stamped 'BGE INC" set for an angle point;
- 4.S 74°53'28" W a distance of 86.24 feet to a 1/2—inch iron rod with cap stamped 'BGE INC" set for an interior corner of the herein described tract;
- 5.S 40°26'52" E a distance of 45.49 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an exterior corner of the herein described tract;
- 6.S 49°33'08" W a distance of 114.95 feet to a 1/2—inch iron rod with cap stamped 'BGE INC" set for an angle point;
- 7.S 61°05'21" W a distance of 61.29 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an angle point;
- 8.S 49°33'08" W a distance of 165.94 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an exterior corner of the herein described tract;
- 9.N 20°05'56" W a distance of 143.66 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set for an interior corner of the herein described tract;
- 10. S 69°54'04" W a distance of 277.97 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an exterior corner of the herein described tract;
- 11. S 19°37'41" E a distance of 55.47 feet to a 1/2—inch iron rod with cap stamped "BGE INC" at a point curvature of a curve to the left;
- 12. Along said curve to the left, an arc distance of 27.28 feet, having a radius of 20.00 feet, a central angle of 78°08'25" and a chord which bears S 58°41'53" E a distance of 25.21 feet a 1/2—inch iron rod
- with cap stamped 'BGE INC" set at a point of reverse curvature;

  13. Along said curve to the right, an arc distance of 158.21 feet, having a radius of 60.00 feet, a central angle of 151° 04' 39" and a chord which bears S 22° 13' 46" E a distance of 116.20 feet to a 1/2—inch
- 14. S 36\*41'27" E a distance of 128.82 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an exterior corner of the herein described tract;

iron rod with cap stamped "BGE INC" set at an interior corner of the herein described tract;

- 15. S 6244'04" W a distance of 35.21 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set for an
- 16. S 75°07'18" W a distance of 64.47 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set for an angle point, and
- 17.N 88°44'21" W a distance of 81.90 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an angle point;

THENCE, with the westerly lines of said PHAU-LARIAT 108, LLC 34.22 acre tract the following five (5)

- 1.N 51°53′12" W a distance of 93.72 feet to a 1/2-inch iron rod with cap stamped 'BGE INC' set for an
- 2.N 30°12'28" W a distance of 49.29 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an angle point;
- $3.N~22^{\circ}32'18"~W~a$  distance of 45.03~feet~to~a~1/2-inch~iron~rod~with~cap~stamped~'BGE~INC" set~for~an
- 4.N 08°27'42" W a distance of 45.99 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set for an angle point, and
- 5.N 20°23'48" W a distance of 1,515.23 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set on the southerly line of Hidden Creek Estates, a subdivision as recorded in Document No. 2016032981 of the Official Public Records of Williamson County, Texas, at the northwest corner of said PHAU-LARIAT 108, LLC 34.22 acre tract for the northwest corner of the herein described tract, from which a 5/8-inch iron rod found at the most westerly northwest corner of a called 678.09 acre tract of land as conveyed to River Oaks Land Partners II, LLC by special warranty deed in Document No. 2021137550 of the Official Public Records of Williamson County, Texas on the existing East right-of-way line of San Gabriel Ranch Road (R.O.W. Varies) bears S 69°34'54" E a distance of 34.21 feet;

THENCE, with the southerly line of Hidden Creek Estates and the northerly line of said PHAU-LARIAT 108, LLC 34.22-acre tract the following two (2) courses:

- 1.N 69°34'54" E a distance of 592.27 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an angle point, and
- 2.N 68°55'13" E a distance of 306.59 feet to a 1/2-inch iron rod with cap stamped "BGE INC" set at the northeastern corner of said PHAU-LARIAT 108, LLC 34.22 acre tract, bein the most westerly corner of said Tri Point Homes Texas, Inc. 42.34 acre tract for the northeast corner of the herein described tract;

THENCE, leaving the southerly line of said Hidden Creek Estates, with the common property line of said Tri Pointe Homes Texas, Inc. 42.43 acre tract and said PHAU-LARIAT 108, LLC 34.22 acre tract the following eight (8) courses:

- 1.S 20°28'34" E a distance of 169.24 feet to a 1/2—inch iron rod with cap stamped "BGE INC" set for an
- 2.S 31°33'00" E a distance of 108.82 feet to a 1/2—inch iron rod with cap stamped 'BGE INC" set for an angle point;
- 3.S 20°20'43" E a distance of 259.12 feet to a 1/2-inch iron rod with cap stamped "LSI SURVEY" found for
- 4.S 58°06'37" E a distance of 134.32 feet to a 1/2-inch iron rod with cap stamped "LSI SURVEY" found for an angle point;
- 5.S 35°15'14" E a distance of 42.67 feet to a 1/2—inch iron rod with cap stamped "LSI SURVEY" found for an angle point;
- 6.S 17°19'16" E a distance of 75.83 feet to a 1/2-inch iron rod with cap stamped "LSI SURVEY" found for an angle point;
- 7.S 11\*57'05" E a distance of 122.50 feet to a 1/2—inch iron rod with cap stamped "LSI SURVEY" found for an angle point, and
- 8.S 22°55'10" E a distance of 526.79 feet to the POINT OF BEGINNING and containing 34.217 acres of land, more or less:

FINAL PLAT

LARIAT SECTIONS 3 & 4

A SUBDIVISION OF 34.217 ACRES OF LAND LOCATED IN THE JAMES HACKETT SURVEY, A-312, IN WILLIAMSON COUNTY, TEXAS.



BGE, Inc.

101 West Louis Henna Blvd., Suite 400
Austin, Texas 78728

Tel: 512-879-0400 ● www.bgeinc.com
TBPELS Registration No. F-1046

TBPELS Licensed Surveying Firm No. 10106502

## LARIAT SECTIONS 3 & 4

A SUBDIVISION OF 34.217 ACRES OF LAND LOCATED IN THE JAMES HACKETT SURVEY, A-312, IN WILLIAMSON COUNTY, TEXAS.

BY:	
DEPUTY	



101 West Louis Henna Blvd., Suite 400 Austin, Texas 78728 Tel: 512-879-0400 • www.bgeinc.com TBPELS Registration No. F-1046 TBPELS Licensed Surveying Firm No. 10106502