

construction of the County Project. The County shall be responsible for the expense and construction of the improvements which constitute the City Project, subject to the reimbursement of 100% of the construction costs (estimated at \$1,617,893) as set out below. The City shall be responsible for all costs associated with the preliminary and final design for the City Project.

The City's 100% share of the actual construction costs for the City Project (estimated at \$1,617,893) shall be due and payable to the County 30 days after the City provides written acceptance of the completed City Project, and otherwise in accordance with the provisions of the Texas Prompt Payment Act, Chapter 2251 of the Texas Government Code. After acceptance, the City will own and maintain the facilities included within the City Project.

2.02 Construction Plans. The County will submit the plans and specifications related to the County Project to the City. The City has submitted the plans and specifications for the City Project, which are identified in Exhibit "A-1" attached hereto, to the County.

2.03 Inspection. The City may inspect all aspects of the County Project that are within the City Limits, and all aspects of the City Project, during construction. Upon receipt of notification from the City that the City's inspectors determine the construction by the County is not in accordance with the approved project plans, the County shall cease construction until the deficiency can be identified, and a corrective plan of construction implemented with the agreement of the City.

2.04. Permits. The County shall be responsible for obtaining permits, if any, required for the construction of the County Project. The City shall be responsible for obtaining permits, if any, required for the construction of the City Project.

2.05. Insurance, Bonds and Warranties. The County shall require the contractor for the Project to name the City as an additional insured on any policies related to the County Project that lie within the City limits, and for any portion of the City Project. The County shall require the contractor to provide performance bonds, and maintenance bonds in favor of the City for the County Project and City Project in amounts satisfactory to the City. The County shall transfer any warranties for portions of the County Project within the city limits, and for the City Project, to the City upon final completion and acceptance of the Projects.

B.

All other terms and conditions of the Agreement shall remain in full force and effect.

C.

MISCELLANEOUS PROVISIONS


1. **Execution.** This Agreement may be simultaneously executed in any number of counterparts, each of which will serve as an original and will constitute one and the same instrument.
2. **Governing Law.** This Agreement will be governed by the Constitution and laws of the State of Texas.

3. **Waiver.** Any waiver by any party of its rights with respect to a default or requirement under this Agreement will not be deemed a waiver of any subsequent default or other matter.
4. **Amendments.** This First Amended Agreement may be amended or modified only by written agreement duly authorized and executed by the duly authorized representatives of the Parties.
5. **Cooperation.** Each Party agrees to execute and deliver all such other and further instruments and undertake such actions as are or may become necessary or convenient to effectuate the purposes and intent of this Agreement.
6. **Venue.** All obligations of the Parties are performable in Williamson County, Texas and venue for any action arising hereunder will be in Williamson County.
7. **Third Party Beneficiaries.** Except as otherwise expressly provided herein, nothing in this Agreement, express or implied, is intended to confer upon any person, other than the Parties, any rights, benefits, or remedies under or by reason of this Agreement.
8. **Entire Agreement.** This Agreement, including any attached exhibits, contains the entire agreement between the Parties with respect to the subject matter and supersedes all previous communications, representations, or agreements, either verbal or written, between the Parties with respect to such matters.

IN WITNESS WHEREOF, the Parties hereto have caused this instrument to be signed, sealed and attested in duplicate by their duly authorized officers, as of the Effective Date.


(signatures on the following pages)

CITY OF HUTTO, TEXAS

By: 
James R. Earp, City Manager

Date: February 10, 2023

Attest:


Angela Lewis, City Secretary


APPROVED AS TO FORM:

By: _____

Name: _____


Its: _____

WILLIAMSON COUNTY

By: 
Bill Gravell (Mar 22, 2023 11:17 CDT)
Bill Gravell, Jr., County Judge

Date: Mar 22, 2023


Attest:


Nancy Rister, County Clerk

**EXHIBIT “A-1”
CITY PROJECT PLAN SHEETS FOLLOWS**

[illegible]

[illegible]





SILT FENCE NOTES:

RESULT FENCE NOTES:

STEEL POSTS WHICH SUPPORT THE SILT FENCE SHALL BE INSTALLED ON A SLOPE ANGLE TOWARD THE ANTICIPATED RUNOFF SURFACE. POSTS MUST BE EMBEDGED IN A MINIMUM OF ONE FOOT OF SOIL. THE TRENCH SHALL BE TRENCHED WITH A SPADE OR MECHANICAL TRENCHER, SO THAT THE DOWNSLOPE FACE OF THE TRENCH IS FLAT AND PERPENDICULAR TO THE LINE OF FLOW, WHERE FENCE CAN NOT BE CONSTRUCTED PERPENDICULAR TO THE LINE OF FLOW, A "V" SHAPED TRENCH SHALL BE CONSTRUCTED TO PREVENT FLOW UNDER FENCE.

THE TRENCH MUST BE A MINIMUM OF 6 INCHES DEEP AND 6 INCHES WIDE TO PREVENT FLOW UNDER FENCE. FACING TO BE Laid IN THE GROUND AND BACKFILLED WITH COMPACTED MATERIAL.

SILT FENCE SHOULD BE SECURELY FASTENED TO EACH STEEL SUPPORT POST OR TO EACH END OF EACH SECTION OF FENCE. THE FENCE SHOULD BE TIGHTLY STABILIZED SO AS NOT TO BLOCK OR IMPIDE STAGN FLOW OR DRAINAGE.

ACCUMULATED SILT SHALL BE REMOVED WHEN IT REACHES A DEPTH OF 6 INCHES. WHEN THE FENCE IS REMOVED, IT SHALL BE INSTALLED IN A NEW LOCATION AS TO NOT CONTRIBUTE TO ADDITIONAL SITUATION.

CONSTRUCTION ENTRANCE NOTES:

1. TYPE AREA: 3" x 6" OPEN FINISHED ROCK

2. LENGTH AS EFFECTIVE BUT NOT LESS THAN 50 FEET.

3. WIDTH: NOT LESS THAN FULL WIDTH OF ALL POINTS OF INGRESS/EGRESS.

4. WIDTH: NOT LESS THAN 24 INCHES WITH ALL POINTS OF INGRESS/EGRESS.

5. WORKING SURFACE: FINISHED, SMOOTH, AND UNIFORM PRIOR TO CONSTRUCTION OF CURB.

6. CURB: 6" MINIMUM THICKNESS. FINISHING REQUIRED. IT SHALL BE DONE ON AN AREA STABILIZED WITH CRUSHED STONE OR APPROVED EQUIVALENT. CURB SHALL BE FINISHED TO MATCH EXISTING ROADWAY TO THE TOP OF CURB.

7. STORM DRAIN: DITCH OR WATERCOURSE USING APPROVED METHODS.

8. DRAINAGE: DRAINAGE SHALL BE TO THE PUBLIC ROADWAY, THIS MAY BE PREVENTED THROUGH THE FLOWING OF SEDIMENT INTO THE DRAINAGE DITCH.

9. EROSION CONTROL: EROSION CONTROL SHALL BE USED TO PREVENT TRAILER AND CLEAR OUT OF ANY MEASURES USED TO TRAMP SEDIMENT. ALL SEDIMENT SHALL BE REMOVED FROM THE ROADWAY.


10. ROADWAY: PROPOSED WASHED OR TRACKED ON PUBLIC ROADWAY MUST BE REMOVED IMMEDIATELY.

11. DRAINAGE: DRAINAGE MUST BE LEAVING THE CONSTRUCTION SITE.

12. STORM DRAIN: STORM DRAIN MUST LEAVE THE CONSTRUCTION SITE.

SILT FENCE DETAIL (2)

STABILIZED CONSTRUCTION ENTRANCE DETAIL 3
N.T.S.



ROCK BERM DETAIL 4

ROCK BERM DETAIL 4

ROCK REFORM NOTES:

1. OPEN GRADED ROADS GRADED ROCK 4 INCHES OR GREATER FOR STREAM FLOW CONDITIONS USE
2. OPEN GRADED ROCK 3-5 INCH DIAMETER FOR OTHER CONDITIONS.
3. THE ROCK BERM SHALL BE SEGUED WITH A WOODEN WIRE SHEATHING HAVING MAXIMUM 1
4. THE ROCK BERM SHALL BE INSPECTED WEEKLY AFTER EACH RAIN, AND THE STONE
5. AND OF THE CORROSION MONITORING SHALL BE ACCUMULATING ALONG THE ROCKS
6. WASHOUT, CONSTRUCTION TRAFFIC DAMAGE, ETC., AND THE HEIGHT OF THE BERM OR ONE
7. FOR WHENEVER IS LESS, THE SILT SHALL BE REMOVED AND DEPOSED OF IN AN
8. APPROVED SITE AND IN A MANNER AS TO NOT CREATE A SILTATION PROBLEM.
9. WHEN THE ACCUMULATED SILT REACHES 6 INCHES, THE ROCK BERM SHALL BE
10. REMOVED WHEN ACCUMULATED SILT REACHES 6 INCHES.
11. WHEN THE SILT IS NOT COLLECTED, THE WASHOUT AND ACCUMULATED SILT SHALL BE

	REV. NO.	DATE	DESCRIPTION	PROJECT MANAGER:	WWW
				DESIGNED BY:	JPCR
				CHECKED BY:	JPH
				DRAWN BY:	JPCR
				RCS PROJECT NO:	Z0701498

DCS ENGINEERING, LLC
1101 S. CAPITAL OF TEXAS
HIGHWAY, BUILDING C-100
AUSTIN, TX 78746
TEL: (512) 614-6171



SE LOOP 801 PP AND 890 PP WATERLINES




7/11/2000
Jenifer F. Ford

MISCELLANEOUS DETAILS

EROSION CONTROL DETAILS


DATE: JULY 2022
SCALE: N.T.S.
DRAWING: 102C-01

[illegible]




LENGTH "L" IN FEET (MIN)		
DUCTILE IRON PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	11	
11.25	22	
22.5	45	
45	108	

LENGTH "L" IN FEET (MIN)		
C-400 POLYVINYL CHLORIDE PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	14	
11.25	27	
22.5	54	
45	108	



LENGTH "L" IN FEET (MIN)		
DUCTILE IRON PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	11	
11.25	22	
22.5	45	
45	113	

LENGTH "L" IN FEET (MIN)		
C-400 POLYVINYL CHLORIDE PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	14	
11.25	28	
22.5	56	
45	112	



LENGTH "L" IN FEET (MIN)		
DUCTILE IRON PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	11	
11.25	22	
22.5	45	
45	113	

LENGTH "L" IN FEET (MIN)		
C-400 POLYVINYL CHLORIDE PIPE (WORKING PRESSURE = 200 PSI)		
ANGLE (°)	36" DIAMETER	
"L"	14	
11.25	28	
22.5	56	
45	112	

HORIZONTAL JOINT RESTRAINT 1

VERTICAL DOWNWARD BENDS JOINT RESTRAINT 2

VERTICAL UPWARD BENDS JOINT RESTRAINT 3

- THRUST RESTRAINT SYSTEM GENERAL NOTES:
- THRUST RESTRAINT SYSTEMS HAVE BEEN DESIGNED FOR MAXIMUM LINE TEST PRESSURE PER SPECIFICATIONS.
 - BIDS SHALL BE PREPARED BASED ON USING RESTRAINED JOINTS TO RESIST THRUST LOADS SPECIFIED IN THE PROJECT MANUAL.
 - ALL PIPING SHALL UTILIZE RESTRAINED JOINTS FOR THE LENGTHS SPECIFIED AND FOR TEES, ELBOWS, AND OTHER FITTINGS. RESTRAINED JOINTS MAY BE USED IN COMBINATION WITH JOINT RESTRAINTS ONLY AS APPROVED BY THE ENGINEER.
 - PIPE SHALL BE MANUFACTURED TO TRANSFER THRUST FORCES WITHOUT EXCEEDING SPECIFICATIONS.
 - WHERE THRUST BLOCKS ARE SPECIFICALLY SHOWN, THEY SHALL BE INSTALLED IN ADDITION TO THE RESTRAINTS.
 - WHERE JOINT RESTRAINTS ARE SPECIFICALLY SHOWN, THEY SHALL BE INSTALLED IN ADDITION TO THE THRUST BLOCKS.
 - CONCRETE FOR THRUST BLOCKS SHALL BE 3000 PSI READY-MIX CONCRETE WITH A MINIMUM OF 4% STEEL FIBER REINFORCEMENT.
 - FOR DEFLECTION ANGLES NOT SHOWN, USE THE NEXT LARGER DEFLECTION ANGLE.
 - WHERE JOINT RESTRAINT ZONE ENDS MID-JOINT, RESTRAIN NEXT JOINT BEYOND CASING PIPE END.

REV. NO.	DATE	DESCRIPTION



FCS
ENGINEERING, LLC

DCS ENGINEERING, LLC
1101 W. CAPITAL OF TEXAS
AUSTIN, TX 78748
TEL: 512.454.1100
FAX: 512.454.1101
E-MAIL: info@dcse.com
WEB: www.dcse.com




Habco

SE LOOP 801 PP AND 890 PP WATERLINES



Jordan T. Hirt
17/11/2022

MISCELLANEOUS DETAILS	
JOINT RESTRAINT DETAILS	
DATE:	JULY 2022
SCALE:	N.T.S.
DRAWING:	02C-03




TAPER LENGTHS			
SPREAD (mm)	SPREAD* (mm)	LENGTH (mm)	LENGTH (feet)
30	20	11	35
40	25	1*	55
50	30	26	85
55	35	36	120
65	40	51	170
70	45	68	220
80	50	84	260
90	55	101	325
95	60	123	415
105	65	146	485

NOTES:

- [illegible]

GIVEN TRENCH WIDTH:	MINIMUM PLATE THICKNESS:
1.0 FOOT	1/2 INCH
1.5 FEET	3/4 INCH
2.0 FEET	7/8 INCH
3.0 FEET	1 INCH
4.0 FEET	1 1/4 INCH

NOTE: FOR SPANS GREATER THAN 4 FEET, A STRUCTURAL DESIGN SHALL BE PREPARED BY A LICENSED PROFESSIONAL ENGINEER IN THE STATE OF TEXAS.



TEMPORARY STEEL
PLATE TRENCH COVER

REV. NO.	DATE	DESCRIPTION	PROJECT MANAGER	WWW
			DESIGNED BY: JPCR	
			CHECKED BY: JTH	
			DRAWN BY: JPCR	
			QCS PROJECT NO: 20101499	



DCS ENGINEERING, LLC
1101 S. CAPITAL OF TEXAS
HIGHWAY, BUILDING C-100
AUSTIN, TX 78746
TEL: (512) 614-6171
T.B.P.E. FIRM NO. F-13162

SE LOOP 801 PP AND 890 PP WATERLINES



7/11/2012
Jach Fato

MISCELLANEOUS DETAILS

TRAFFIC CONTROL DETAILS

DATE:	JULY 2022
SCALE:	N.T.S.
DRAWING:	020C-05

GENERAL NOTES:

1. TRAFFIC CONTROL SHALL BE PROVIDED WHEN WORK IS BEING PERFORMED WITHIN THE TRAVEL LANES.
2. ALL OPEN TRENCHES WITHIN THE ROADWAY, ONE LANE SHALL REMAIN OPEN AND ACCESSIBLE TO THROUGH TRAFFIC AT ALL TIMES. NO OPEN TRENCHES WILL BE ALLOWED AT END OF WORK DAY. INSTALL STEEL PLATES PER CITY REGULATIONS WHEN WORK IN TRENCH IS NOT BEING CONDUCTED.
3. TEMPORARY LANE CLOSURES SHALL REQUIRE FLAGGER(S) AND SIGNAGE.

FLAGGER NOTES:


- [illegible]

ADVANCE WARNING SIGN SPACING	
POSTED SPEED (MPH)	SIGN SPACING "A" (FEET)
25	100
30	120
35	160
40	240
45	320
50	400
55*	500
60*	600
65*	700
70*	800
75*	900
80*	1000

• DISTANCE BETWEEN SIGNS SHOULD BE INCREASED TO HAVE 1500 FEET ADVANCE WARNING. (SEE SECTION 6C.04.07 OF THE TEXAS MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES)

4
TYPICAL LANE CLOSURE

NOTE:





2009-09-01 10:00 AM